

DV430FHM-NN1**Product Specification****Rev. B****Fuzhou BOE Optoelectronics CO., LTD**

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

REVISION HISTORY

() preliminary specification

(√) Final specification

Revision No.	Page	Description of changes	Date	Prepared
O	-	Initial Release	2019/05/28	Weng Z.W
A	36&37	Add portrait usage suggestion	2019/07/11	Geng W.B
B	5&38	Thickness adjusted 2D draft updated	2020/09/14	Han. J

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 2 OF 39
------------------------------	---	-----------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

Contents

No	ITEM	Page
	REVISIONS HISTORY	2
	CONTENTS	3
1	GENERAL DESCRIPTION	4
	1.1 Introduction	
	1.2 Features	
	1.3 Application	
	1.4 General Specification	
2	ABSOLUTE MAXIMUM RATINGS	6
3	ELECTRICAL SPECIFICATIONS	7
	3.1 TFT LCD Open Cell	
	3.2 LED Constant current source LED	
4	INTERFACE CONNECTION	12
	4.1 Open Cell Input Signal & Power	
	4.2 LVDS Interface	
	4.3 LVDS Rx Interface Eye Diagram	
	4.4 LVDS Receiver Differential Input	
5	SIGNAL TIMING SPECIFICATIONS	17
	5.1 Timing Parameters (DE only mode)	
	5.2 Signal Timing Waveform	
	5.3 Input Signals, Basic Display Colors and Gray Scale of Colors	
	5.4 Power Sequence	
6	OPTICAL SPECIFICATIONS	21
7	MECHANICAL CHARACTERISTICS	25
8	RELIABILITY TEST	26
9	DEFINITION OF LABELS	27
10	PACKING INFORMATION	28
11	PRECAUTIONS	32
12	APPENDIX	38


SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	3 OF 39

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

1.0 GENERAL DESCRIPTION

1.1 Introduction

DV430FHM-NN1 is a color active matrix TFT LCD MDL using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This MDL has a 42.5 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD panel is adapted for a low reflection and higher color type.



1.2 Features

- LVDS interface with 2 pixel / clock
- High-speed response
- Low color shift image quality
- 8-bit color depth, display 16.7M colors
- Wide viewing angle
- DE (Data Enable) only mode
- ADS technology is applied for high display quality
- RoHS compliant

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	4 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

1.3 Application

- Commercial Digital Display
- Display Terminals for Control System
- Landscape and Portrait Display

1.4 General Specification

< Table 1. General Specifications >

Parameter	Specification	Unit	Remarks
Active area	940.896(H) × 529.254(V)	mm	
Number of pixels	1920(H) × 1080(V)	pixels	
Pixel pitch	163.35(H) × 490.05(V)	um	
Pixel arrangement	Pixels RGB Vertical stripe		
Display colors	16.7M	colors	8bits True
Display mode	Normally Black		
Dimensional outline	962.1(H) × 550.5(V) × 12.9(B)	mm	Detail refer to drawing
Weight	8.36(Typ)	Kg	
Power Consumption	LED Driver:56.3	Watt	Typ.
Surface Treatment	Haze 1%		
Back-light	E-LED Backlight		
Possible display type	Landscape and Portrait Enabled		

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.


< Table 2. Open Cell Electrical Specifications >

[VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remark
Power Supply Voltage	VDD	VSS-0.3	13.5	V	Ta = 25 °C
Operating Temperature	T _{OP}	0	+50	°C	Note 1
Storage Temperature	T _{SUR}	-20	+60	°C	
	T _{ST}	-20	+60	°C	
Operating Ambient Humidity	Hop	10	80	%RH	
Storage Humidity	Hst	10	80	%RH	

Note 1 : Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39 °C max. and no condensation of water.



BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

3.0 ELECTRICAL SPECIFICATIONS


3.1 TFT LCD Open Cell


< Table 3. Open Cell Electrical Specifications >


[Ta =25 ± 2 °C]

Parameter		Symbol	Values			Unit	Remark
			Min	Typ	Max		
Power Supply Input Voltage		VDD	10.8	12	13.2	Vdc	
Power Supply Ripple Voltage		VRP	-	-	300	mV	
Power Supply Current		IDD	-	500	950	mA	Note 1
Power Consumption		PDD	-	6	11.4	Watt	
Rush current		IRUSH	-		3.0	A	Note 2
LVDS Interface	Differential Input High Threshold Voltage	VLVTH	+100	-	+300	mV	
	Differential Input Low Threshold Voltage	VLVTL	-300	-	-100	mV	
	Common Input Voltage	VLVC	1.0	1.2	1.4	V	
CMOS Interface	Input High Threshold Voltage	VIH	2.7	-	3.3		
	Input Low Threshold Voltage	VIL	0	-	0.6	V	

Note 1 : The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for VDD=12.0V,
Frame rate f_v=60Hz and Clock frequency = 74.25MHz.
Test Pattern of power supply current

a) Typ : Mosaic 7X5 (L0/L255)


b) Max : Horizontal 1 Line (L0/L255)


c) Flicker Pattern


Note 2 : The duration of rush current is about 2ms and rising time of Power Input is 1ms(min)

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	7 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

3.2 LED Constant current source LED

3.2.1 Input Electrical Characteristics

输入电压 Input voltage	22Vdc to 26Vdc
输入电流 Input current	Max.3.5A at 24Vdc input and full load

3.2.2 Output Electrical Characteristics

(LED DRIVER(DC/DC)ELECTRICAL REQUIREMENTS)

输出功率(Output Power)

输出功率 Outpur Power	Max. 64W
----------------------	----------

恒流输出特性(Constant Current Output Characteristics)

输出通道 Output Channel	最低电压 Min Voltage	典型电压 Type Voltage	最高电压 Max. Voltage	输出电流 Output current
LED	58V	62V	66V	480mA*2

背光控制(The Backlight On/Off Control)

BL Signal	Remark	Outputs
BL-High	≥2.5V & 2mA	Output
BL-Low	≤0.5V	X
BL-Open	--	X

备注：恒流源输出受控于一个 TTL 电平兼容的信号（BL），此信号电平需在 0-5V 之间
Remark: The Constant Current Source DC outputs current shall be enable with an active-TT L-compatible signal (BL). The signal level must be between 0-5V.

- BL 高电平，打开输出。
When BL is pulled to TTL high, the DC current outputs are to be enabled.
- BL 低电平或悬空，关闭输出。
When BL is pulled to TTL low or open circuit, the DC outputs are to be disabled.

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 8 OF 39
------------------------------	---	-----------------

调光(Adjust Backlight Brightness)

PWM Signal	Remark
PWM-High	≥2.5V & 2mA
PWM-Low	≤0.5V
PWM-Duty	10%-99%
PWM-Frequency	150-300Hz

DC Signal	Remark
DC-Voltage	0V-5V

备注(Remark):
I ADJ 脚接 PWM 信号,此 PWM 信号能调节背光亮度, PWM 信号占空比越宽, 背光越亮,此信号电平需在2.5V-5V 之间。
The ADJ pin must be connected to a PWM signal. The PWM signal can adjust the backlight brightness, the wider the duty cycle, the brighter the backlighting. The signal level must be between 2.5V-5V.
I ADJ脚接DC信号。此DC信号能调节背光亮度, 电压越高, 背光越暗, 此信号电平需在0V-5V之间。
The ADJ pin must be connected to a DC signal. The DC signal can adjust the backlight brightness, the higher the voltage, the darker the backlighting. The signal level must be between 0-5V.
I 调光方式: ☐ PWM调光 ☒ DC调光 ☐ Other

3.2.3 Interface Connections

CON1(Type : Pitch 2.0) Connect(XH2.5-14aW)

PIN号(Pin Number)	符号(Symbol)	功能(Function)	
1. 2. 3. 4. 5	+24V	INPUT VOLTAGE	
6. 7. 8. 9. 10	GND	Ground	
11. 14	NC	NC	
12	BL-ON	LED ON/OFF CONTROL(ON≥2.5)	
13	ADJ	Dimming control	0V=Brightness Max
			5V=Brightness Min

CON2(Type : Pitch 2.0mm)


PIN号(Pin Number)	符号(Symbol)	功能(Function)
1	LED1+	LED+ OUTPUT
2	LED1-	LED- OUTPUT

Notice: 1. PIN 13:External ADJ Control

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

3.2.4 Mechanical Characteristics

Outline Dimension
106.0(L)*73.0(W)*13(H) mm



SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 11 OF 39
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

4.0 INTERFACE CONNECTION

4.1 Open Cell Input Signal & Power

- LVDS Connector : PM.LVS.S040505101(UJC) 、 IS050-C51B-C39-S(UJU) or 0.5Ph H3.75 LVDS(DEREN).

< Table 4. Open Cell Input Connector Pin Configuration >

Pin No	Symbol	Description	Pin No	Symbol	Description
1	NC	No Connection	21	GND	Ground
2	SDA	I ² C Data	22	CH1[3]-	First pixel negative LVDS differential data input. Pair3
3	SCL	I ² C Clock	23	CH1[3]+	First pixel positive LVDS differential data input. Pair3
4	NC	Not Connected	24	NC	Not Connected
5	NC	Not Connected	25	NC	Not Connected
6	NC	Not Connected	26	NC	Not Connected
7	SELLVDS	High: JEIDA Low or Open: VESA	27	NC	Not Connected
8	NC	Not Connected	28	CH2[0]-	Second pixel negative LVDS differential data input. Pair0
9	NC	Not Connected	29	CH2[0]+	Second pixel positive LVDS differential data input. Pair0
10	NC	Not Connected	30	CH2[1]-	Second pixel negative LVDS differential data input. Pair1
11	GND	Ground	31	CH2[1]+	Second pixel positive LVDS differential data input. Pair1
12	CH1[0]-	First pixel negative LVDS differential data input. Pair0	32	CH2[2]-	Second pixel negative LVDS differential data input. Pair2
13	CH1[0]+	First pixel positive LVDS differential data input. Pair0	33	CH2[2]+	Second pixel positive LVDS differential data input. Pair2
14	CH1[1]-	First pixel negative LVDS differential data input. Pair1	34	GND	Ground
15	CH1[1]+	First pixel positive LVDS differential data input. Pair1	35	CH2CLK-	Second pixel negative LVDS clock
16	CH1[2]-	First pixel negative LVDS differential data input. Pair2	36	CH2CLK+	Second pixel positive LVDS clock
17	CH1[2]+	First pixel positive LVDS differential data input. Pair2	37	GND	Ground
18	GND	Ground	38	CH2[3]-	Second pixel negative LVDS differential data input. Pair3
19	CH1CLK-	First pixel negative LVDS clock	39	CH2[3]+	Second pixel positive LVDS differential data input. Pair3
20	CH1CLK+	First pixel positive LVDS clock			


SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 12 OF 39
------------------------------	---	------------------

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

Pin No	Symbol	Description	Pin No	Symbol	Description
40	NC	Not Connected	46	GND	Ground
41	NC	Not Connected	47	NC	Not Connected
42	NC	Not Connected	48	VCC	Input Voltage +12V
43	NC	Not Connected	49	VCC	Input Voltage +12V
44	GND	Ground	50	VCC	Input Voltage +12V
45	GND	Ground	51	VCC	Input Voltage +12V

- Notes : 1. NC(Not Connected) : This pins are only used for BOE internal operations.
2. Input Level of LVDS signal is based on the EIA-644 Standard.
3. LVDS_SEL : This pin is used for selecting LVDS signal data format.
- If this Pin : High (3.3V) →JEIDA LVDS format
- Otherwise : Low (GND) or Open (NC) → Normal NS LVDS format

Rear view of LCM



BIST Pattern

PT1:Black (2sec)	PT2:White (2sec)	PT3:Red (2sec)	PT4:Green (2sec)	PT5:Blue (2sec)


SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 13 OF 39
------------------------------	---	------------------

4.2 LVDS Interface

-LVDS Receiver : Timing Controller (LVDS Rx merged) / LVDS Data : Pixel Data

< Table 5. Open Cell Input Connector Pin Configuration >

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	10.31	13.47(10.78)	15.87	nsec	
Input Data 0	tRIP1	-0.42	0.0	+0.42	nsec	
Input Data 1	tRIP0	tRCIP/7-0.42	tRCIP/7	tRCIP/7+0.42	nsec	
Input Data 2	tRIP6	$2 \times \text{tRCIP}/7 - 0.42$	$2 \times \text{tRCIP}/7$	$2 \times \text{tRCIP}/7 + 0.42$	nsec	
Input Data 3	tRIP5	$3 \times \text{tRCIP}/7 - 0.42$	$3 \times \text{tRCIP}/7$	$3 \times \text{tRCIP}/7 + 0.42$	nsec	
Input Data 4	tRIP4	$4 \times \text{tRCIP}/7 - 0.42$	$4 \times \text{tRCIP}/7$	$4 \times \text{tRCIP}/7 + 0.42$	nsec	
Input Data 5	tRIP3	$5 \times \text{tRCIP}/7 - 0.42$	$5 \times \text{tRCIP}/7$	$5 \times \text{tRCIP}/7 + 0.42$	nsec	
Input Data 6	tRIP2	$6 \times \text{tRCIP}/7 - 0.42$	$6 \times \text{tRCIP}/7$	$6 \times \text{tRCIP}/7 + 0.42$	nsec	




$$* V_{diff} = (RXz+) - (RXz-), \dots, (RXCLK+) - (RXCLK-)$$

4.3 LVDS Rx Interface Eye Diagram

< Table 6. LVDS Rx Interface Eye Diagram>

Symbol	Min	Typ	Max	Unit	Note
A	—	100	—	mV	
B	—	100	—	mV	
C	—	0	—	mV	
D	—	-100	—	mV	
E	—	-100	—	mV	
F	—	0	—	mV	




- Notes:
1. Time F to A,B to C,C to D,E to F is 150p second.
 2. LVDS clock=85Mhz.
 3. The time A to B=1T-2*TRSKM-2*150ps.

4.4 LVDS Receiver Differential Input

< Table 7. LVDS Receiver Differential Input>

Symbol	Parameter	Min	Typ	Max	Unit	Condition
R_{xVTH}	Differential input high threshold voltage			+0.1v	V	$R_{xVCM} = 1.2V$
R_{xVTL}	Differential input low threshold voltage	-0.1V			V	
R_{xVIN}	Input voltage range (singled-end)	0		2.4	V	
R_{xVCM}	Differential input common mode voltage	$ V_{ID} /2$		$2.4 - V_{ID} /2$	V	
$ V_{ID} $	Differential input voltage	0.1		0.6	V	



5.0 SIGNAL TIMING SPECIFICATION

5.1 Timing Parameters (DE only mode)

< Table 8. Timing Table >

Item		Symbols		Min	Typ	Max	Unit
Clock	Frequency	1/Tc		60	74.25	78	MHz
	High Time	Tch		-	4/7Tc	-	
	Low Time	Tcl		-	4/7Tc	-	
Frame Period		Tv		1100	1125	1149	lines
				48.5	60	63	Hz
Horizontal Active Display Term		Valid	t _{HV}	-	960	-	t _{CLK}
		Total	t _{HP}	1060	1100	1200	t _{CLK}
Vertical Active Display Term		Valid	t _{VV}	-	1080	-	t _{HP}
		Total	t _{VP}	1100	1125	1149	t _{HP}



Notes: This product is DE only mode. The input of Hsync & Vsync signal does not have an effect on normal operation.

< Table 9. LVDS Input SSCG>

Symbol	Parameter	Condition	Min	Typ	Max	Unit
F	LVDS Input frequency	-	45	74.25	85	MHz
T _{LVSK}	LVDS channel to channel skew	F=100MHz V _{IC} =1.2V V _{ID} =±400mV	-380	-	+380	ps
F _{LVMOD}	Modulating frequency of input clock during SSC		-	-	85	KHz
F _{LVDEV}	Maximum deviation of input clock frequency during SSC		-3	-	+3	%
T _{CY-CY}	Cycle to Cycle jitter		-	-	100	ps

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

5.2 Signal Timing Waveform




5.3 Input Signals, Basic Display Colors and Gray Scale of Colors

< Table 10. Input Signal and Display Color Table >

Color & Gray Scale		Input Data Signal																							
		Red Data								Green Data								Blue Data							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
Gray Scale of White	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1
	▽	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

5.4 Power Sequence

To prevent a latch-up or DC operation of the Open Cell, the power on/off sequence shall be as shown in below



< Table 11. Sequence Table >

Parameter	Values			Units
	Min	Typ	Max	
T1	0.5	-	20	ms
T2	10	-	100	ms
T3	200	-	-	ms
T4	200	-	-	ms
T5	0	-	-	ms
T6	1	-	-	s

- Notes:
1. Back Light must be turn on after power for logic and interface signal are valid.
 2. Even though T1 is out of SPEC, it is still ok if the inrush current of VDD is below the limit.
 3. When $VDD < 0.9VDD(Typ.)$, Power off.
 4. T7 decreases smoothly, if there were rebounding voltage, it must smaller than 5 volts.

6.0 OPTICAL SPECIFICATIONS

Optical characteristics are determined after the unit has been 'ON' and stable in a dark environment at $25\pm2^{\circ}\text{C}$. The values are specified at an approximate distance 50cm from the LCD surface at a viewing angle of Φ and θ equal to 0° . It is presented additional information concerning the measurement equipment and method in FIG. 1.




FIG. 1 Optical Characteristic Measurement Equipment and Method

< Table 12. Optical Table >

[VDD = 12.0V, Frame rate = 60Hz, Ta = $25\pm2^{\circ}\text{C}$]

Parameter		Symbol	Condition	Min	Typ	Max	Unit	Remark
Viewing Angle	Horizontal	Θ_3	CR > 10		89		Deg.	Note 5
		Θ_9			89		Deg.	
	Vertical	Θ_{12}			89		Deg.	
		Θ_6			89		Deg.	
Color Temperature				9000	10,000	11,500	K	
Color Gamut				70	72	-	%	
Contrast ratio		CR	$\Theta = 0^\circ$ (Center) Normal Viewing Angle	800:1	1200:1	-		Note 1
Luminance of White		Y_w		350	400	-	cd/m ²	Note 2
White luminance uniformity		ΔY		70	75		%	Note 3
Reproduction of color	White	W_x		TYP. - 0.03	0.280	TYP. + 0.03		
		W_y			0.290			
	Red	R_x			0.640			
		R_y			0.334			
	Green	G_x			0.296			
		G_y			0.607			
	Blue	B_x			0.149			
		B_y			0.069			
Response Time	G to G	T_g	-	8	10	ms	Note 4	
Gamma Scale				2.0	2.2	2.4		Note 6

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

Note : 1. Contrast Ratio(CR) is defined mathematically as :

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

It is measured at center 1-point.

2. Surface luminance are determined after the unit has been ‘ON’ and 1 Hour after lighting the backlight in a dark environment at 25±2°C. Surface luminance is the luminance value at center 1-point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see the FIG. 2.

3. The variation in surface luminance , δ WHITE is defined as :

$$\delta \text{ WHITE(9P)} = \text{Minimum}(L_{on1}, L_{on2}, L_{on3}, L_{on4}, L_{on0}) / \text{Maximum}(L_{on1}, L_{on2}, L_{on3}, L_{on4}, L_{on9})$$

Where L_{on1} to L_{on9} are the luminance with all pixels displaying white at 9 locations .
For more information, see the FIG. 2.

4. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD module surface. For more information, see the FIG. 4.

5. Gray scale specification
Gamma Value is approximately 2.2.

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 22 OF 39
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

Measuring point for surface luminance & luminance variation**CA-310 ,Contact method)**




FIG. 2 9 Points for Luminance Measure

Response time is defined as the following figure and shall be measured by switching the input signal for “Gray(N)” and “Gray(M)”.




FIG. 3 Response Time

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	23 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

Definitions of viewing angle range




FIG. 4 Viewing Angle

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 24 OF 39
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

7.0 MECHANICAL CHARACTERISTICS

7.1 Dimensional Requirements

Figure 5 (located in Appendix) shows mechanical outlines for the model DV430FHM-NN1. Other parameters are shown in Table 13.

< Table 13. Dimensional Parameters >

Parameter	Specification	Unit
Dimensional outline	961.7(H) × 550.0(V) × 11.7(B)	mm
Weight	8.36	Kg
Active area	940.896(H) × 529.254(V)	mm
Pixel pitch	163.35(H) × 490.05(V)	mm
Number of pixels	1920(H) × 1080(V) (1 pixel = R + G + B dots)	pixels
Back-light	E-LED Backlight	

7.2 Mounting

See Figure 6. (Shown in Appendix)

7.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an low haze coating to reduce scratching. Front Polarizer hardness is at less 3H.

8.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

< Table 14. Reliability Test Parameters >

No	Test Items	Conditions	
1	High temperature storage test	Ta = 60 °C, 240 hrs	
2	Low temperature storage test	Ta = -20 °C, 240 hrs	
3	High temperature & high humidity operation test	Ta = 50 °C, 80%RH, 240hrs	
4	High temperature operation test	Ta = 50 °C, 240hrs	
5	Low temperature operation test	Ta = -5 °C, 240hrs	
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle	
7	Vibration test (non-operating)	Frequency	10 ~ 300 Hz, Random
		Gravity / AMP	1.0 G
		Period	X, Y, Z 30 min
8	Shock test (non-operating)	Gravity	50G
		Pulse width	11msec, sine wave
		Direction	± X, ± Y, ± Z Once for each
9	Electro-static discharge test	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV	

This test condition is based on BOE module.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

9.0 DEFINITION OF LABELS

MDL Label

He bar code nameplate is pasted on each module as illustration, and its definitions are as following explanation.

Label Size: 80mm (L) x 25mm (W)

Label Picture :

DP/N

XXXXXX

DV430FHM-NN1

B10

BOE

XXXX

XXXXXXXXXXXXXXXXXXXX

XXXXXX

XXXXXX

XXXXXX

XXXXXX

REV A00

MADE IN CHINA

1

2

3

4

5

6

7

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

1. Control Number

2. Rank / Grade

3. Line Classification

4. Year (2001 : 01, 2002 : 02, ...)

5. Month (1,2,3, ... , 9, X, Y, Z)

6. Internal Use

7. Serial Number

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	27 OF 39


10.0 PACKING INFORMATION





10.1 PACKING SPECIFICATIONS

- (1) 10 PCS LCD TV modules / 1 Box
- (2) Box dimensions: 1065(W) x 565(D) x 635(H)mm
- (3) 2 Box/ 1 Pallet

10.2 PACKING METHOD


- (1) Palletizing Sequence





NO.	DESCRIPTION	MATERIAL	QUANTITY
1	43~Module	/	60
2	Bag	PE	60
3	Tape-Bag	OPP	180
4	EPE (Down)	EPE	6
5	Box	K-K	6
6	Pallet	/	3
7	EPE (Up)	EPE	6
8	Corner Protect (Top)	K-K	6
9	Corner Protect (Side)	K-K	12
10	PP Belt	/	/
11	Protect Film	/	/

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14



Total size: 1150 (W) x1080 (D) x2325 (H) mm

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE OF 39
------------------------------	---	---------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

10.3 Box Label

- Label Size : 100 mm (L) × 50 mm (W)
- Contents
 - Model : DV430FHM-NN1
 - Q`ty : 10 Module in one box.
 - Serial No. : Box Serial No. See next page for detail description.
 - Date : Packing Date
 - FG Code : FG Code of Product

BOE FUZHOU JINGDONGFANG OPTOELECTRONICS TECHNOLOGY Co.,LTD

MODEL: DV430FHM-NN1 ①

Q'TY: 10 ②

SERIAL NO: XXXXXXXXXXXX ③

DATE: XXXX.XX.XX ④

Box ID 条形码

XXXX ⑤



- 打印标识，说明如下:
1. FG-CODE
 2. 产品数量
 3. Box ID, 编码规则如下
 4. Box Packing 日期
 5. FG-CODE 后四位

BOX ID编码原则

Digit	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	S	L	S	A	1	6	3	D	0	0	1	A	1
Description	Products GBN		Grade	Line	Year		Month	Revision Code	Serial No.				

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

11.0 PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD Module.

11.1 Mounting Precautions

- Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- You must mount a module using specified mounting holes (Details refer to the drawings)
- You should consider the mounting structure so that uneven force (ex. Twisted stress, Concentrated stress)is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- Do not apply mechanical stress or static pressure on module; Abnormal display cause by pressing some parts of module during assembly process , do not belong to product failure, the press should be agreed by two sides.
- Determine the optimum mounting angle, refer to the viewing angle range in the specification for each model.
- Do not apply mechanical stress or static pressure on module , and avoid impact, vibration and falling.
- Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- Protection film for polarizer on the module should be slowly peeled off before display.
- Be careful to prevent water & chemicals contact the module surface.
- You should adopt radiation structure to satisfy the temperature specification.
- Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
- When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzine. Normal-hexane & alcohol is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene , because they cause chemical damage to the polarizer.
- Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading..

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	32 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14
<ul style="list-style-type: none"> • This module has its circuitry PCB's on the rear side and Driver IC, should be handled carefully in order not to be stressed. • Avoid impose stress on PCB and Driver IC during assembly process ,Do not drawing, bending, COF package & wire • Do not disassemble the module. 			
<h3>11.2 Operating Precautions</h3> <ul style="list-style-type: none"> • Do not connector or disconnect the cable to/from the Module at the “Power On” Condition. • When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the module would be damaged. • Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged. • Do not allow to adjust the adjustable resistance or switch • The electrochemical reaction caused by DC voltage will lead to LCD module degradation, so DC drive should be avoided. • The LCD modules use C-MOS LSI drivers, so customers are recommended that any unused input terminal would be connected to Vdd or Vss, do not input any signals before power is turn on, and ground you body, work/assembly area, assembly equipment to protect against static electricity. • Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged. • Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference. • Design the length of cable to connect between the connector for back-light and the converter as shorter as possible and the shorter cable shall be connected directly , The long cable between back-light and Converter may cause the Luminance of LED to lower and need a higher startup voltage • The cables should be as short as possible between System Board and PCB interface. • Connectors are precision devices to transmit electrical signals, and operators should plug in parallel • Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur. 			
SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B		PAGE 33 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

11.3 Electrostatic Discharge Precautions

- Avoid the use work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.
- Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc.
- Do not close to static electricity to avoid product damage.
- Do not touch interface pin directly.

11.4 Precautions for Strong Light Exposure

- Do not leave the module operation or storage in Strong light . Strong light exposure causes degradation of polarizer and color filter.

11.5 Precautions for Storage

A. Atmosphere Requirement

ITEM	UNIT	MIN	MAX
Storage Temperature	(℃)	5	40
Storage Humidity	(%rH)	40	75
Storage Life	6 months		
Storage Condition	<ul style="list-style-type: none"> • The storage room should be equipped with a dark and good ventilation facility. • Prevent products from being exposed to the direct sunlight, moisture and water. • The product need to keep away from organic solvent and corrosive gas. • Be careful for condensation at sudden temperature change. • Storage condition is guaranteed under packing conditions. 		

B. Package Requirement

- The product should be placed in a sealed polythene bag.
- Product Should be placed on the pallet, Which is away from the floor, Be cautions not to pile the product up.
- The polarizer surface should not come in contact with any other object. It is recommended that they be stored in the container in which they were shipped.
- As the original protective film, do not use the adhesive protective film to avoid change of Pol color and characteristic.

SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 34 OF 39
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

11.6 Precautions for protection film

- Remove the protective film slowly, keeping the removing direction approximate 30-degree not vertical from panel surface, If possible, under ESD control device like ion blower, and the humidity of working room should be kept over 50%RH to reduce the risk of static charge.
- People who peeled off the protection film should wear anti-static strap and grounded well.

11.7 Appropriate Condition for Commercial Display

-Generally large-sized LCD modules are designed for consumer applications . Accordingly, long-term display like in Commercial Display application, can cause uneven display including image sticking. To optimize module's lifetime and function, several operating usages are required.

1. Normal operating condition

- Temperature: $20\pm15^{\circ}\text{C}$
- Operating Ambient Humidity : $55\pm20\%$
- Display pattern: dynamic pattern (Real display)
- Well-ventilated place is recommended to set up Commercial Display system

2. Special operating condition

a. Ambient condition

- Well-ventilated place is recommended to set up Commercial Display system.

b. Power and screen save

- Periodical power-off or screen save is needed after long-term display.

c. As the low temperature, the response time is greatly delayed. As the high temperatures (higher than the operating temperature) the LCD module may turn black screen. The above phenomenon cannot explain the failure of the display. When the temperature returns to the normal operating temperature, the LCD module will return to normal display.

d. When expose to drastic fluctuation of temperature (hot to cold or cold to hot) ,the LCD module may be affected; Specifically, drastic temperature fluctuation from cold to hot ,produces dew on the LCD module 's surface which may affect the operation of the polarizer and LCD module

e. Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.

f. Products exposed to low temperature environment for a long time, need to carry out necessary protection , low temperature environment is usually refrigerators , vending machine Etc...


g. Long time and large angle forward use or unconventional use , It is strongly recommended to contact BOE for filed application engineering advice

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	35 OF 39

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

- f. Product reliability and functions are only guaranteed when the product is used under right operation usages. If product will be used in extreme conditions such as high temperature, high humidity, high altitude, special display images, running time, long time operation, outdoor operation, etc. It is strongly recommended to contact BOE for filed application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at airports, transit stations, banks, stock market and controlling systems.
3. Operating usages to protect against image sticking due to long-term static display.
- a. Suitable operating time: under 20 hours a day.
 - b. Static information display recommended to use with moving image.
 - Cycling display between 5 minutes' information(static) display and 10 seconds' moving image.
 - c. Background and character (image) color change
 - Use different colors for background and character, respectively.
 - Change colors themselves periodically.
 - d. Avoid combination of background and character with large different luminance.
 - 1) Abnormal condition just means conditions except normal condition.
 - 2) Black image or moving image is strongly recommended as a screen save
4. Lifetime in this spec. is guaranteed only when Commercial Display is used according to operating usages.
5. Module should be turned clockwise based on front view when used in portrait mode.
- Landscape Mode


The default placement is TCON side on the lower side and the image is shown upright via viewing from the front.



SPEC. NUMBER S8-65-8D-082	SPEC. TITLE DV430FHM-NN1 Product Specification Rev.B	PAGE 36 OF 39
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14

- Portrait Mode
The default placement is that TCON side has to be placed on the left side via viewing from the front



11.8 Other Precautions

A. LC Leak

- If the liquid crystal material leaks from the panel, it is recommended to wash the LC with acetone or ethanol and then burn it.
- If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- If LC in mouth, mouth need to be washed, drink plenty of water to induce vomiting and follow medical advice.
- If LC touch eyes, eyes need to be washed with running water at least 15 minutes.

B. Rework


- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	37 OF 39

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. B	2020/09/14


12.0 APPENDIX

< Figure 5. TFT-LCD Module Outline Dimensions (Front View) >



SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8D-082	DV430FHM-NN1 Product Specification Rev.B	38 OF 39

< Figure 6. TFT-LCD Module Outline Dimensions (Rear View) >



Note:

1. ① -M3 Locking depth max 4.8mm,effective thread depth 2.3mm,Total:6pcs
2. ② -M3 Locking depth max 3.8mm,effective thread depth 2.3mm,Total:12pcs
3. ③ -M3 Locking depth max 6.8mm,effective thread depth 2mm,Total:15pcs
4. ④ -M6 Locking depth max 16mm,effective thread depth 10.5mm,Total:4pcs
5. USER MOUNTING TORQUE SPEC:
Torque value: M3 6kgf-cm,MAX
Rivet column: M6 20kgf-cm,MAX