



ED302YT~ED306YT

SUPERFAST RECOVERY RECTIFIERS

Voltage Range -200 to 600 Volts

Current -3.0 Amperes

Features

- * Superfast recovery times-epitaxial construction.
- * Low forward voltage, high current capability.
- * Exceeds environmental standards of MIL-S-19500/228.
- * Hermetically sealed.
- * Low leakage.
- * High surge capability.
- * Plastic package has Underwriters Laboratories Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.

Mechanical Data


Case: Molded plastic, TO-251AB

Terminals: Axial leads, solderable to MIL-STD-202, Method 208

Polarity: As marking

Weight: 0.015 ounces, 0.4grams.

TO-251AB



Dimensions in millimeters

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Resistive or inductive load, 60Hz.

	ED302YT	ED303YT	ED304YT	ED306YT	UNIT
Maximum Recurrent Peak Reverse Voltage	200	300	400	600	V
Maximum RMS Voltage	140	210	280	420	V
Maximum DC Blocking Voltage	200	300	400	600	V
Maximum Average Forward Current .375"(9.5mm) lead length at T _A =75°C	3.0				A
Peak Forward Surge Current, IFM (surge):8.3ms single half sine-wave superimposed on rated load(JEDEC method)	75				A
Maximum Forward Voltage at 3.0A DC	0.95	1.25		1.70	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	5.0				μA
Maximum DC Reverse Current at Rated DC Blocking Voltage T _A =125°C	300				μA
Maximum Reverse Recovery Time(Note 1)	35.0				ns
Typical Junction capacitance (Note 2)	45				pF
Typical Junction Resistance(Note 3) RθJA	25				°C/ W
Operating and Storage Temperature Range T _J	-55 to +150				°C

NOTES:

1. Thermal Resistance Junction to Ambient .



ED302YT~ED306YT

SUPERFAST RECOVERY RECTIFIERS

Voltage Range -200 to 600 Volts

Current -3.0 Amperes

Rating and Characteristic Curves




Fig.1-FORWARD CURRENT DERATING CURVE




Fig.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC




Fig.3-TYPICAL REVERSE CHARACTERISTICS




Fig.4-MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig.5-TYPICAL JUNCTION CAPACITANCE