

isc N-Channel MOSFET Transistor

EKV550

FEATURES

- Drain Current –I_D=50A@ T_C=25 °C
- Drain Source Voltage-
 - : V_{DSS}=50V(Min)
- Static Drain-Source On-Resistance
 - : $R_{DS(on)} = 15m \Omega (Max)$
- · 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation




 Designed for use in switch mode power supplies and general purpose applications.


ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{DSS}	Drain-Source Voltage	50	V
V _{GS}	Gate-Source Voltage-Continuous	±20	V
I _D	Drain Current-Continuous	50	А
P _D	Total Dissipation @T _C =25°C 85		W
TJ	Max. Operating Junction Temperature	150	$^{\circ}$
T _{stg}	Storage Temperature	rage Temperature -55~150	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	1.47	°C/W







isc N-Channel MOSFET Transistor

EKV550

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0; I _D = 0.1mA	250		V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = 10V; I _D =0.25mA	3	4.2	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} = 10V; I _D =25A		15	mΩ
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V;V _{DS} = 0		±10	μА
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =50V; V _{GS} = 0		100	μА
V _{SD}	Forward On-Voltage	I _S =50A; V _{GS} = 0		1.5	V



ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications. ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.