

Single N-channel MOSFET

ELM4N8066FDA-N

<https://www.elm-tech.com>

■General description

ELM4N8066FDA-N uses advanced trench technology to provide excellent $R_{ds(on)}$, low gate charge and low gate threshold voltage.

■Features

- $V_{ds}=80V$
- $I_d=60A$ ($V_{gs}=10V$)
- $R_{ds(on)} = 8.7m\Omega$ ($V_{gs}=10V$)
- $R_{ds(on)} = 12.5m\Omega$ ($V_{gs}=4.5V$)


■Maximum absolute ratings

Parameter		Symbol	Limit	Unit	Note
Drain-source voltage		V_{ds}	80	V	
Gate-source voltage		V_{gs}	± 20	V	
Continuous drain current ($V_{gs}=10V$)	$T_c=25^{\circ}C$	I_d	60	A	1
	$T_c=100^{\circ}C$		38		
Pulsed drain current		I_{dm}	200	A	2
Single pulsed avalanche energy		E_{as}	101	mJ	3
Avalanche current		I_{as}	45	A	
Total power dissipation	$T_c=25^{\circ}C$	P_d	52	W	4
Storage temperature range		T_{stg}	-55 to 150	$^{\circ}C$	
Operating junction temperature range		T_j	-55 to 150	$^{\circ}C$	

■Thermal characteristics


Parameter	Symbol	Typ.	Max.	Unit	Note
Thermal resistance junction-ambient	$R_{\theta ja}$	-	62.0	$^{\circ}C/W$	1
Thermal resistance junction-case	$R_{\theta jc}$	-	2.4		

■Pin configuration



Pin No.	Pin name
1	GATE
2	DRAIN
3	SOURCE

■Circuit



Single N-channel MOSFET

ELM4N8066FDA-N

<https://www.elm-tech.com>

■Electrical characteristics

T_j=25°C. Unless otherwise noted.

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
STATIC PARAMETERS							
Drain-source breakdown voltage	BV _{dss}	V _{gs} =0V, I _d =250μA	80	-	-	V	
Static drain-source on-resistance	R _{ds(on)}	V _{gs} =10V, I _d =15A	-	6.5	8.7	mΩ	2
		V _{gs} =4.5V, I _d =15A	-	9.0	12.5		
Gate threshold voltage	V _{gs(th)}	V _{gs} =V _{ds} , I _d =250μA	1.20	1.55	2.30	V	
Drain-source leakage current	I _{dss}	V _{ds} =64V, V _{gs} =0V	-	-	1	μA	
		V _{ds} =64V, V _{gs} =0V, T _j =55°C	-	-	5		
Gate-source leakage current	I _{gss}	V _{gs} =±20V, V _{ds} =0V	-	-	±100	nA	
Continuous source current	I _s	V _{gs} =V _{ds} =0V, Force current	-	-	30	A	1, 5
Diode forward voltage	V _{sd}	V _{gs} =0V, I _s =1A	-	-	1.2	V	2
DYNAMIC PARAMETERS							
Input capacitance	C _{iss}	V _{ds} =40V, V _{gs} =0V, f=1MHz	-	1738	-	pF	
Output capacitance	C _{oss}		-	317	-	pF	
Reverse transfer capacitance	C _{rss}		-	12	-	pF	
Gate resistance	R _g	V _{ds} =0V, V _{gs} =0V, f=1MHz	-	1.6	-	Ω	
SWITCHING PARAMETERS							
Total gate charge	Q _g	V _{ds} =40V, V _{gs} =10V I _d =15A	-	29.0	-	nC	
Gate-source charge	Q _{gs}		-	7.7	-	nC	
Gate-drain charge	Q _{gd}		-	5.3	-	nC	
Turn-on delay time	t _{d(on)}	V _{dd} =40V, V _{gs} =10V R _{gen} =3.3Ω, I _d =10A	-	6.2	-	ns	
Turn-on rise time	t _r		-	19.0	-	ns	
Turn-off delay time	t _{d(off)}		-	9.4	-	ns	
Turn-off fall time	t _f		-	36.0	-	ns	
Reverse recovery time	t _{rr}	I _f =10A, di/dt=100A/μs	-	35	-	nS	
Reverse recovery charge	Q _{rr}		-	62	-	nC	

NOTE :







1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
2. The data tested by pulsed, pulse width ≤ 300μs and duty cycle ≤ 2%.
3. The Eas data shows Max. rating . The test condition is V_{dd}=50V, V_{gs}=10V, L=0.1mH, I_{as}=45A.
4. The power dissipation is limited by 150°C junction temperature.
5. The data is theoretically the same as I_d and I_{dm}, in real applications, should be limited by total power dissipation.

Single N-channel MOSFET

ELM4N8066FDA-N

<https://www.elm-tech.com>

■ Typical characteristics



Single N-channel MOSFET

ELM4N8066FDA-N

<https://www.elm-tech.com>




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Switching Waveform

Single N-channel MOSFET

ELM4N8066FDA-N


<https://www.elm-tech.com>

■TO-252 dimension (2,500pcs/reel)



Symbols	Millimeters		Inches		Symbols	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	2.18	2.40	0.086	0.095	e	2.286BSC		0.09BSC	
A1	---	0.20	---	0.008	H	9.40	10.50	0.370	0.413
b	0.68	0.90	0.026	0.036	L	1.38	1.78	0.054	0.070
b3	4.95	5.46	0.194	0.215	L1	2.90REF		0.114REF	
c	0.43	0.89	0.017	0.035	L2	0.51BSC		0.020BSC	
D	5.97	6.22	0.235	0.245	L3	0.88	1.28	0.034	0.050
D1	5.300REF		0.209REF		L4	0.50	1.00	0.019	0.039
E	6.35	6.73	0.250	0.265	θ	0°	8°	0°	8°
E1	4.32	---	0.170	---					

■Marking



Symbols	Content
xxxxxx	Product code
a	Yearly code: 2019=K, 2020=L, 2021=M...
b, c	Weekly code: 01 to 53
d, e	Sequence: 01 to 99 or 0A to 0Z
f	Assembly code: A to Z (I, O excepted)