






SINGLE PHASE ENERGY METER-EM101+


TECHNICAL SPECIFICATIONS

Туре
■ Single Phase Two Wire
Accuracy
■ Class 1.0 as per IS:13779/IEC 61036
Electrical
■ Current
* I _b 2.5, 5,10A
* I _{max} up to 600% I _b
■ Voltage
* 240 V (p-n) (- 30% to + 20%)
■ Power factor Range
* 0.5 lag - UPF - 0.8 lead
■ Frequency Range
* 50 Hz <u>+</u> 5%
■ Starting Current
* 0.4% of Basic Current

LED indic	ation
* Pow	ver on.
* Rev	erse Current
* Eart	h Load Tamper
* kWh	Pulse output
	inues to operate satisfactorily under ng conditions :-
■ Phase/N	eutral Reversed.
■ Supply s	ide-Load side interchanged
■ Full Load	d/Partial Load terminated to Earth.
■ Combina	ntion of any of the above.
Display	
■ 6 digit Stepper Motor Counter (1 decimal digit)	
Operating	Temperature

■ 0 to 55°C ambient







Works.....KIADB Indl. Estate, Hebbal, Hootagalli, Mysore-570018. Ph: (0821) 402561. Fax: (0821) 402172.

New Delhi: Ph: (011) 25177883. Fax: (011) 25438624 **Bangalore:** Ph: (080) 5587825. Fax: (080) 5596397 **Kolkata:** Ph:(033) 22823302. Fax: (033) 22821025 **Chandigarh:** Ph:(0172) 370131. Fax:(0172) 792764 **Mumbai:** Ph:(022) 28581634. Fax:(022) 28582020

◆ *Chennai*: Ph:(044) 28462055 Fax: (044) 28462102.

Visit us at www.Intmps.com