

FERP15K

Ultra fast Plastic Power Rectifiers

VOLTAGE: 800V

CURRENT: 15.0A



FEATURE


- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Ideally suited for use in very high frequency switching power supplies, inverters and as free wheeling diodes
- Ultra fast recovery time for high efficiency
- Excellent high temperature switching
- Glass passivated junction
- High voltage and high reliability
- High speed switching

MECHANICAL DATA

Case: JEDEC ITO-220AB molded plastic body over passivated chip

Terminals: Plated Insert leads, solderable per MIL-STD-750, Method 2026

Mounting Position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	FERP15K	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	800	V
Maximum RMS Voltage	V _{rms}	560	V
Maximum DC blocking Voltage	V _{dc}	800	V
Maximum Average Forward Rectified at T _c =100°C	I _{f(av)}	15.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	120	A
Maximum Forward Voltage at Forward Current 7.5A and 25°C	V _f	2.2	V
Maximum Reverse Recovery Time (Note 1)	T _{rr}	70	nS
Typical thermal resistance junction to case	R _{th(jc)}	5.0	°C/W
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =125°C	I _r	10.0 100.0	μA
Storage and Operating Temperature Range	T _{stg} , T _j	-55 to +150	°C

Note:

Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A

RATINGS AND CHARACTERISTIC CURVES FERP15K

Fig. 1 – Forward Current Derating Curve




Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 – Typical Forward Voltyage




Fig. 4 – Typical Reverse Current




Fig. 5 – Typical Junction Capacitance

