



October 2008

# FGA30N60LSD

## Features

- Low saturation voltage:  $V_{CE(sat)} = 1.1V$  @  $I_C = 30A$
- High Input Impedance
- Low Conduction Loss



## Applications

- Solar Inverters
- UPS, Welder



## General Description

The FGA30N60LSD is a MOS gated high voltage switching device combining the best features of MOSFETs and bipolar transistors. This device has the high input impedance of a MOSFET and the low on-state conduction loss of a bipolar transistor.



## Absolute Maximum Ratings

| Symbol      | Description  | FGA30N60LSD | Units      |
|-------------|--|-------------|------------|
| $V_{CES}$   | Collector-Emitter Voltage  | 600         | V          |
| $V_{GES}$   | Gate-Emitter Voltage   | $\pm 20$    | V          |
| $I_C$       | Collector Current @ $T_C = 25^\circ C$                                     | 60          | A          |
|             | Collector Current @ $T_C = 100^\circ C$                                    | 30          | A          |
| $I_{CM(1)}$ | Pulsed Collector Current   | 90          | A          |
| $I_{FSM}$   | Non-repetitive Peak Surge Current<br>60Hz Single Half-Sine Wave            | 150         | A          |
| $P_D$       | Maximum Power Dissipation @ $T_C = 25^\circ C$                             | 480         | W          |
|             | Maximum Power Dissipation @ $T_C = 100^\circ C$                            | 192         | W          |
| $T_J$       | Operating Junction Temperature   | -55 to +150 | $^\circ C$ |
| $T_{stg}$   | Storage Temperature Range  | -55 to +150 | $^\circ C$ |
| $T_L$       | Maximum Lead Temp. for soldering<br>Purposes, 1/8" from case for 5 seconds | 300         | $^\circ C$ |

### Notes :

(1) Repetitive rating : Pulse width limited by max. junction temperature

## Thermal Characteristics

| Symbol                 | Parameter                               | Typ. | Max. | Units        |
|------------------------|---|------|------|--------------|
| $R_{\theta JC}(IGBT)$  | Thermal Resistance, Junction-to-Case    | --   | 0.26 | $^\circ C/W$ |
| $R_{\theta JC}(Diode)$ | Thermal Resistance, Junction-to-Case    | --   | 0.92 | $^\circ C/W$ |
| $R_{\theta JA}$        | Thermal Resistance, Junction-to-Ambient | --   | 40   | $^\circ C/W$ |

## Package Marking and Ordering Information

| Device Marking | Device        | Package | Packaging Type | Qty per Tube | Max Qty per Box |
|----------------|---------------|---------|----------------|--------------|-----------------|
| FGA30N60LSD    | FGA30N60LSDTU | TO-3PN  | Tube           | 30ea         | -               |

## Electrical Characteristics of the IGBT T<sub>C</sub> = 25°C unless otherwise noted

| Symbol   | Parameter                                    | Test Conditions  | Min. | Typ. | Max. | Units |
|--|--|--|------|------|------|-------|
| Off Characteristics                            |  |  |      |      |      |       |
| BV <sub>CES</sub>                              | Collector-Emitter Breakdown Voltage          | V <sub>GE</sub> = 0V, I <sub>C</sub> = 250uA   | 600  | --   | --   | V     |
| ΔB <sub>V<sub>CES</sub></sub> /ΔT <sub>J</sub> | Temperature Coefficient of Breakdown Voltage | V <sub>GE</sub> = 0V, I <sub>C</sub> = 250uA   | --   | 0.6  | --   | V/°C  |
| I <sub>CES</sub>                               | Collector Cut-Off Current                    | V <sub>CE</sub> = V <sub>CES</sub> , V <sub>GE</sub> = 0V  | --   | --   | 250  | uA    |
| I <sub>GES</sub>                               | G-E Leakage Current                          | V <sub>GE</sub> = V <sub>GES</sub> , V <sub>CE</sub> = 0V  | --   | --   | ±250 | nA    |
| On Characteristics                             |  |  |      |      |      |       |
| V <sub>GE(th)</sub>                            | G-E Threshold Voltage                        | I <sub>C</sub> = 250uA, V <sub>CE</sub> = V <sub>GE</sub>  | 4.0  | 5.5  | 7.0  | V     |
| V <sub>CE(sat)</sub>                           | Collector to Emitter Saturation Voltage      | I <sub>C</sub> = 30A, V <sub>GE</sub> = 15V  | --   | 1.1  | 1.4  | V     |
|  |  | I <sub>C</sub> = 30A, V <sub>GE</sub> = 15V, T <sub>C</sub> = 125°C  | --   | 1.0  | --   | V     |
|  |  | I <sub>C</sub> = 60 A, V <sub>GE</sub> = 15V   | --   | 1.3  | --   | V     |
| Dynamic Characteristics                        |  |  |      |      |      |       |
| C <sub>ies</sub>                               | Input Capacitance                            | V <sub>CE</sub> = 30V, V <sub>GE</sub> = 0V, f = 1MHz  | --   | 3550 | --   | pF    |
| C <sub>oes</sub>                               | Output Capacitance                           |  | --   | 245  | --   | pF    |
| C <sub>res</sub>                               | Reverse Transfer Capacitance                 |  | --   | 90   | --   | pF    |
| Switching Characteristics                      |  |  |      |      |      |       |
| t <sub>d(on)</sub>                             | Turn-On Delay Time                           | V <sub>CC</sub> = 400 V, I <sub>C</sub> = 30A, R <sub>G</sub> = 6.8Ω, V <sub>GE</sub> = 15V, Inductive Load, T <sub>C</sub> = 25°C | --   | 18   | --   | ns    |
| t <sub>r</sub>                                 | Rise Time                                    |  | --   | 46   | --   | ns    |
| t <sub>d(off)</sub>                            | Turn-Off Delay Time                          |  | --   | 250  | --   | ns    |
| t <sub>f</sub>                                 | Fall Time                                    |  | --   | 1.3  | 2.0  | us    |
| E <sub>on</sub>                                | Turn-On Switching Loss                       |  | --   | 1.1  | --   | mJ    |
| E <sub>off</sub>                               | Turn-Off Switching Loss                      | V <sub>CC</sub> = 400 V, I <sub>C</sub> = 30A, R <sub>G</sub> =6.8Ω, V <sub>GE</sub> = 15V, Inductive Load, T <sub>C</sub> = 125°C | --   | 21   | --   | mJ    |
| t <sub>d(on)</sub>                             | Turn-On Delay Time                           |  | --   | 17   | --   | ns    |
| t <sub>r</sub>                                 | Rise Time                                    |  | --   | 45   | --   | ns    |
| t <sub>d(off)</sub>                            | Turn-Off Delay Time                          |  | --   | 270  | --   | ns    |
| t <sub>f</sub>                                 | Fall Time                                    |  | --   | 2.6  | --   | us    |
| E <sub>on</sub>                                | Turn-On Switching Loss                       | V <sub>CE</sub> = 300 V, I <sub>C</sub> = 30A, V <sub>GE</sub> = 15V   | --   | 1.1  | --   | mJ    |
| E <sub>off</sub>                               | Turn-Off Switching Loss                      |  | --   | 36   | --   | mJ    |
| Q <sub>g</sub>                                 | Total Gate Charge                            |  | --   | 225  | --   | nC    |
| Q <sub>ge</sub>                                | Gate-Emitter Charge                          | V <sub>CE</sub> = 300 V, I <sub>C</sub> = 30A, V <sub>GE</sub> = 15V   | --   | 30   | --   | nC    |
| Q <sub>gc</sub>                                | Gate-Collector Charge                        |  | --   | 105  | --   | nC    |
| L <sub>e</sub>                                 | Internal Emitter Inductance                  | Measured 5mm from PKG  | --   | 7    | --   | nH    |

**Electrical Characteristics of the Diode**  $T_C = 25^\circ\text{C}$  unless otherwise noted

| Parameter | Conditions  |                           | Min. | Typ. | Max | Units         |
|-----------|---|---------------------------|------|------|-----|---------------|
| $V_{FM}$  | $I_F = 15\text{A}$  | $T_C = 25^\circ\text{C}$  | -    | 1.8  | 2.2 | V             |
|           | $I_F = 15\text{A}$  | $T_C = 125^\circ\text{C}$ | -    | 1.6  | -   | V             |
| $I_{RM}$  | $V_R = 600\text{V}$   | $T_C = 25^\circ\text{C}$  | -    | -    | 100 | $\mu\text{A}$ |
| $t_{rr}$  | $I_F = 1\text{A}$ , $di/dt = 100\text{A}/\mu\text{s}$ , $V_{CC} = 30\text{V}$   | $T_C = 25^\circ\text{C}$  | -    | -    | 35  | ns            |
|           | $I_F = 15\text{A}$ , $di/dt = 100\text{A}/\mu\text{s}$ , $V_{CC} = 390\text{V}$ | $T_C = 25^\circ\text{C}$  | -    | -    | 40  | ns            |
| $t_a$     | $I_F = 15\text{A}$ , $di/dt = 100\text{A}/\mu\text{s}$ , $V_{CC} = 390\text{V}$ | $T_C = 25^\circ\text{C}$  | -    | 18   | -   | ns            |
| $t_b$     |   | $T_C = 25^\circ\text{C}$  | -    | 13   | -   | ns            |
| $Q_{rr}$  |   | $T_C = 25^\circ\text{C}$  | -    | 27.5 | -   | nC            |

## Typical Performance Characteristics

Figure 1. Typical Output Characteristics




Figure 2. Typical Saturation Voltage Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Transfer characteristics




Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level





Figure 6. Saturation Voltage vs. Vge



## Typical Performance Characteristics (Continued)

Figure 7. Saturation Voltage vs.  $V_{GE}$




Figure 8. Capacitance characteristics




Figure 9. Gate Charge Characteristics




Figure 10. SOA Characteristics




Figure 11. Load Current Vs. Frequency





Figure 12. Turn-On Characteristics vs. Gate Resistance



## Typical Performance Characteristics (Continued)

Figure 13. Turn-Off Characteristics vs. Gate Resistance




Figure 14. Turn-On Characteristics vs. Collector Current




Figure 15. Turn-Off Characteristics vs. Collector Current




Figure 16. Switching Loss vs. Gate Resistance




Figure 17. Switching Loss vs. Collector Current




Figure 18. Turn-Off Switching SOA Characteristics




Figure 19. Transient Thermal Impedance of IGBT




Figure 20. Typical Forward Voltage Drop

Figure 21. Typical Reverse Current






Figure 22. Typical Reverse Recovery Time



## TO-3PN







## TRADEMARKS


The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Build it Now™  
CorePLUS™  
CorePOWER™  
CROSSVOLT™  
CTL™  
Current Transfer Logic™  
EcoSPARK®  
EfficientMax™  
EZSWITCH™ \*  
  
  
Fairchild®  
Fairchild Semiconductor®  
FACT Quiet Series™  
FACT®  
FAST®  
FastvCore™  
FlashWriter® \*

FPST™  
F-PFST™  
FRFET®  
Global Power ResourceSM  
Green FPS™  
Green FPS™ e-Series™  
GTO™  
IntelliMAX™  
ISOPLANAR™  
MegaBuck™  
MICROCOUPLER™  
MicroFET™  
MicroPak™  
MillerDrive™  
MotionMax™  
Motion-SPM™  
OPTOLOGIC®  
OPTOPLANAR®  


PDP SPM™  
Power-SPM™  
PowerTrench®  
Programmable Active Droop™  
QFET®  
QS™  
Quiet Series™  
RapidConfigure™  
Saving our world, 1mW at a time™  
SmartMax™  
SMART START™  
SPM®  
STEALTH™  
SuperFET™  
SuperSOT™-3  
SuperSOT™-6  
SuperSOT™-8  
SuperMOS™  
SyncFET™



The Power Franchise®  
  
TinyBoost™  
TinyBuck™  
TinyLogic®  
TINYOPTO™  
TinyPower™  
TinyPWM™  
TinyWire™  
  
UHC®  
Ultra FRFET™  
UniFET™  
VCX™  
VisualMax™

\* EZSWITCH™ and FlashWriter® are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any authorized coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition  |
|--------------------------|-----------------------|---|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.   |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.   |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.  |

Rev. 135