

FAIRCHILD

A Schlumberger Company

FRP1000/FRP2000CC Series

Ultra-fast POWERplanar™

Rectifiers 10-20 A, 50-200 V


Power And Discrete Division

T-03-17

Description


Designed for use in switching power supplies, inverters and as free-wheeling diodes, these state-of-the-art devices have the following features:

- Ultrafast 35 ns Reverse Recovery Time
- Soft Recovery ($S > 0.5$)
- Low $I_{R(REC)}$
- Dual Rectifiers Matched to ± 50 mV
- 150°C Operating Junction Temperature
- Popular TO-220AC and TO-220AB Packages
- Low V_{FM}

TO-220AC

1500030F

FRP1005
FRP1010
FRP1015
FRP1020

TO-220AB

1500010F

FRP2005CC
FRP2010CC
FRP2015CC
FRP2020CC

Maximum Ratings

Symbol	Rating	FRP1005 FRP2005CC	FRP1010 FRP2010CC	FRP1015 FRP2015CC	FRP1020 FRP2020CC	Unit
V_{RRM}	Peak Repetitive Reverse Voltage	50	100	150	180	V
V_{RSM}	Non-repetitive Peak Reverse Voltage	50	100	150	200	
V_R	DC Blocking Voltage	50	100	150	180	
$I_{F(AV)}$	Average Rectified Forward Current, $T_C = 117^\circ\text{C}$, Rated V_R ; FRP1000 Series FRP2000CC Series	10 20	10 20	10 20	10 20	A
I_{FSM}	Non-repetitive Peak Surge Current per Diode, Halfwave, 60 Hz	150	150	150	150	A
T_J, T_{stg}	Operating Junction Temperature and Storage Temperature	-55 to +150	-55 to +150	-55 to +150	-55 to +150	$^\circ\text{C}$

Maximum Thermal Characteristics

Symbol	Rating	FRP1005 FRP2005CC	FRP1010 FRP2010CC	FRP1015 FRP2015CC	FRP1020 FRP2020CC	Unit
$R_{\theta JC}$	Maximum Thermal Resistance, Junction to Case FRP1000 Series FRP2000CC Series	2.5 1.5	2.5 1.5	2.5 1.5	2.5 1.5	$^\circ\text{C/W}$
$R_{\theta JA}$	Maximum Thermal Resistance, Junction to Ambient	60	60	60	60	

Notes

For information concerning connection diagram and package outline, refer to Section 7.



FRP1000/FRP2000CC Series

J. 03-17

Symbol	Rating	FRP1005 FRP2005CC	FRP1010 FRP2010CC	FRP1015 FRP2015CC	FRP1020 FRP2020CC	Unit
Electrical Characteristics per Diode						
V_{FM}^1	Maximum Instantaneous Forward Voltage $I_F = 10.0$ A, $T_C = 150^\circ\text{C}$ $I_F = 10.0$ A, $T_C = 25^\circ\text{C}$	0.91 1.0	0.91 1.0	0.91 1.0	0.91 1.0	V
I_{RRM}^1	Maximum Instantaneous Repetitive Reverse Current Rated DC Voltage, $T_C = 125^\circ\text{C}$ Rated DC Voltage, $T_C = 25^\circ\text{C}$	5.0 5	5.0 5	5.0 5	5.0 5	mA μA
t_{rr}	Maximum Reverse Recovery Time $I_F = 1.0$ A, $di_F/dt = 50$ A/ μs $I_F = 10$ A, $di_F/dt = 100$ A/ μs	35 50	35 50	35 50	35 50	ns
$I_{R(REC)}^2$	Maximum Reverse Recovery Current $I_F = 10$ A, $di_F/dt = 100$ A/ μs , V_{RRM}	2.5	2.5	2.5	2.5	A

Notes

1. Pulse Test: Pulse Width = 300 μs . Duty Cycle $\leq 2.0\%$
2. See Figure 11 for test conditions.


Performance Curves per Diode**Figure 1 Maximum Forward Voltage Drop****Figure 2 Maximum Power Dissipation**

FRP1000/FRP2000CC Series

T-03-17


Performance Curves per Diode (Cont.)

Figure 3 Transient Thermal Resistance




PC11200F

Figure 4 Typical Reverse Leakage Current




PC11270F

Figure 5 Typical Reverse Leakage Current




PC11200F

Figure 6 Power Derating




PC11220F

Figure 7 Reverse Recovery Charge



PC11230F

Figure 8 Reverse Recovery Time



PC11240F

Performance Curves per Diode (Cont.)

Figure 9 Reverse Recovery Current




Figure 10 Reverse Recovery Softness




Figure 11 Reverse Recovery Test Waveform

