

Flyback Transformer For Microchip Technology's Isolated AC LED driver





- Developed specifically for Microchip Technology's Isolated AC LED driver to operate with PIC16HV785 CMOS Microcontroller and MCP1402 Gate Driver
- Universal ac input; 20 V, 0.7 A output; Operates at 125 kHz
- 3000 Vrms, one minute isolation from the primary and bias to the secondary winding
- · Bias winding supplies 12 V to power the microprocessor

Core material Ferrite

Terminations RoHS tin-silver over tin over copper clad steel. Other terminations available at additional cost.

Weight 11.7 g

Ambient temperature -40°C to +85°C

Storage temperature Component: -40°C to +85°C. Packaging: -40°C to +80°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF) 38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 117 parts per tray

PCB washing Only pure water or alcohol recommended

Part	Power	Inductance at 0 A ¹	Inductance at Ipk ²	DCR max (Ohms)			Leakage inductance ³	Turns ratio	Ipk ²	
number	(W)	±10% (μΗ)	min (µH)	pri	sec	bias	max (µH)	pri : sec pri : bias	(Å)	Output ⁴
GA3172-AL	14	500	450	0.675	0.245	0.325	8.25	1:0.214 1:0.131	0.78	20 V, 0.7 A

1. Inductance measured at 125 kHz, 0.1 Vrms, 0 Adc.

2. Peak primary current drawn at minimum input voltage.

3. Leakage inductance is for the primary and is measured with the secondary shorted.

4. Output is for the secondary. Bias winding output is 12 V.

5. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.





10





inches Dimensions are in mm



US +1-847-639-6400 sales@coilcraft.com UK +44-1236-730595 sales@coilcraft-europe.com Taiwan +886-2-2264 3646 sales@coilcraft.com.tw China +86-21-6218 8074 sales@coilcraft.com.cn Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 682 Revised 09/01/09

© Coilcraft Inc. 2012

This product may not be used in medical of high risk applications without prior Coilcraft approval Specification subject to change without notice. Please check out web site for latest information.