

KYCON Modular Jacks

KYCON

KYCON RIGHT ANGLE MODULAR JACKS

- Snap-In board retention tabs
- Housing Material: PBT Thermoplastic, UL94V-0 rated
- Contact Material: Phosphor Bronze
- Current Rating: 1.5 Amps
- Shield Material: Copper Alloy, Nickel plated
- Insulation Resistance: 500 Megohms min.
- Dielectric Withstanding Voltage: 1000VAC for 1 minute
- Contact Resistance: 20 Milliohms max.
- Standard Contact Plating: 15µ" Gold over Nickel
- 50µ" Gold plating available upon request



For quantities of 10000 and up, call for quote.

MOUSER STOCK NO.	Kycon Part No.	Fig.	USOC Type	Positions- Contacts	Price Each					
					1	25	100	500	1000	5000
Grey Body - .570" Height										
806-GL-N-44	GL-N-44	A	Handset	4-4	.43	.35	.30	.22	.20	.18
806-GL-N-64	GL-N-64	A	RJ11	6-4	.37	.30	.25	.19	.18	.17
806-GL-N-66	GL-N-66	A	RJ12	6-6	.51	.42	.36	.27	.24	.22
Grey Body with Panel Stops - .570" Height										
806-GL-A-44	GL-A-44	B	Handset	4-4	.39	.32	.28	.20	.18	.16
806-GL-A-64	GL-A-64	B	RJ11	6-4	.33	.27	.23	.19	.18	.17
806-GL-A-66	GL-A-66	B	RJ12	6-6	.51	.42	.36	.27	.24	.22
Grey Short Body with Panel Stops - .570" Height										
806-GL-N-88M	GL-N-88M	B	RJ45	8-8	1.11	1.04	.74	.66	.60	.54
806-GL-N-1010M	GL-N-1010M	B	RJ45/10	10-10	1.31	1.23	.88	.78	.70	.63
Black Body with Panel Stops - .595" Height										
806-GD-A-44	GD-A-44	C	Handset	4-4	.60	.52	.43	.33	.30	.27
806-GD-A-64	GD-A-64	C	RJ11	6-4	.63	.52	.43	.33	.30	.27
806-GD-A-66	GD-A-66	C	RJ12	6-6	.83	.68	.55	.43	.39	.35
806-GD-A-88	GD-A-88	C	RJ45	8-8	1.06	.87	.71	.55	.49	.44
*806-GD-A-88K	GD-A-88K	C	RJ45	8-8	1.06	.87	.71	.55	.49	.44
Black Body - .492" Height										
806-GDL-N-64	GDL-N-64	D	RJ11	6-4	.69	.65	.46	.41	.37	.33
806-GDL-N-66	GDL-N-66	D	RJ12	6-6	.81	.77	.54	.49	.44	.39
806-GDL-N-88	GDL-N-88	D	RJ45	8-8	.92	.87	.62	.55	.49	.44
*806-GDL-N-88K	GDL-N-88K	D	RJ45	8-8	.92	.87	.62	.55	.49	.44
Black Body with Panel Stops - .492" Height										
806-GDL-A-64	GDL-A-64	E	RJ11	6-4	.76	.71	.50	.45	.43	.38
806-GDL-A-66	GDL-A-66	E	RJ12	6-6	.88	.83	.59	.53	.50	.45
806-GDL-A-88	GDL-A-88	E	RJ45	8-8	1.01	.95	.67	.60	.57	.51
*806-GDL-A-88K	GDL-A-88K	E	RJ45	8-8	1.01	.95	.67	.60	.57	.51
Shielded Black Body with Panel Stops - .492" Height										
806-GDL-S-64	GDL-S-64	E	RJ11	6-4	1.28	1.20	.85	.76	.72	.64
806-GDL-S-66	GDL-S-66	E	RJ12	6-6	1.41	1.33	.94	.84	.79	.70
806-GDL-S-88	GDL-S-88	E	RJ45	8-8	1.33	1.25	.89	.80	.72	.64
*806-GDL-S-88K	GDL-S-88K	E	RJ45	8-8	1.33	1.25	.89	.80	.72	.64
Surface Mount Black Body with Panel Stops - .492" Height - High Temperature/Reflow Compatible										
806-GDL-SMT-N-64	GDL-SMT-N-64	F	RJ11	6-4	.96	.90	.74	.57	.54	.48
806-GDL-SMT-N-88	GDL-SMT-N-88	F	RJ45	8-8	1.28	1.20	.98	.76	.72	.64

* Keyed

KYCON LOW PROFILE RIGHT ANGLE MODULAR JACKS

- Snap-In board retention tabs
- Housing Material: PBT Thermoplastic, UL94V-0 rated
- Contact Material: Phosphor Bronze
- Current Rating: 1.5 Amps
- Shield Material: Copper Alloy, Nickel plated
- Low Profile
- Insulation Resistance: 500 Megohms min.
- Dielectric Withstanding Voltage: 1000VAC for 1 minute
- Contact Resistance: 20 Milliohms max.
- Standard Contact Plating: 15µ" Gold over Nickel
- 50µ" Gold plating available upon request



For quantities of 10000 and up, call for quote.

MOUSER STOCK NO.	Kycon Part No.	Fig.	USOC Type	Positions- Contacts	Price Each					
					1	25	100	500	1000	5000
Black Body - .450" Height										
806-GM-N-44	GM-N-44	G	Handset	4-4	.67	.63	.45	.40	.37	.33
806-GM-N-64	GM-N-64	G	RJ11	6-4	.67	.63	.45	.40	.37	.33
806-GM-N-66	GM-N-66	G	RJ12	6-6	.87	.82	.58	.52	.48	.43
806-GM-N-88	GM-N-88	G	RJ45	8-8	.94	.89	.63	.56	.51	.46
806-GM-N-1010	GM-N-1010	G	RJ45/10	10-10	1.34	1.27	.90	.80	.74	.66
Shielded Black Body - .450" Height										
806-GM-S-64	GM-S-64	H	RJ11	6-4	1.51	1.42	1.01	.90	.85	.76
806-GM-S-66	GM-S-66	H	RJ12	6-6	1.48	1.39	.99	.88	.80	.71
806-GM-S-88	GM-S-88	H	RJ45	8-8	1.62	1.53	1.08	.97	.87	.78
806-GM-S-1010	GM-S-1010	H	RJ45/10	10-10	1.89	1.78	1.26	1.13	1.04	.93
Surface Mount Black Body - .450" Height - High Temperature/ Reflow Compatible										
806-GM-SMT2-N-44	GM-SMT2-N-44	I	Handset	4-4	.88	.83	.59	.53	.48	.43
806-GM-SMT2-N-64	GM-SMT2-N-64	I	RJ11	6-4	1.00	.94	.67	.60	.54	.48
806-GM-SMT2-N-66	GM-SMT2-N-66	I	RJ12	6-6	1.00	.94	.67	.60	.54	.48
806-GM-SMT2-N-88	GM-SMT2-N-88	I	RJ45	8-8	1.17	1.10	.78	.70	.63	.56
806-GM-SMT2-N-1010	GM-SMT2-N-1010	I	RJ45/10	10-10	1.33	1.25	.89	.80	.72	.64
Surface Mount Shielded Black Body - .450" Height - High Temperature/ Reflow Compatible										
806-GM-SMT2-S-64	GM-SMT2-S-64	J	RJ11	6-4	1.55	1.46	1.04	.93	.83	.75
806-GM-SMT2-S-66	GM-SMT2-S-66	J	RJ12	6-6	1.61	1.52	1.08	.96	.87	.78
806-GM-SMT2-S-88	GM-SMT2-S-88	J	RJ45	8-8	1.99	1.88	1.33	1.19	1.07	.96
806-GM-SMT2-S-1010	GM-SMT2-S-1010	J	RJ45/10	10-10	1.97	1.86	1.32	1.18	1.06	.95
Surface Mount Black Body (No Mounting Pegs) - .453" Height - High Temperature/ Reflow Compatible										
806-GM-SMT4-N-64	GM-SMT4-N-64	K	RJ11	6-4	1.18	1.11	.79	.70	.65	.58
806-GM-SMT4-N-88	GM-SMT4-N-88	K	RJ45	8-8	1.52	1.43	1.02	.91	.84	.75

 Catalog #624, November 2005 - January 2006
 © Copyright 2005 Mouser Electronics

 Catalog #624, November 2005 - January 2006
 © Copyright 2005 Mouser Electronics

www.mouser.com/kycon


Mouser Catalog Download

(800) 346-6873

865