


GM965

NPN EPITAXIAL PLANAR TRANSISTOR


Description

The GM965 is designed for use as AF output amplifier and flash unit.

Package Dimensions



Marking :



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	4.4	4.6	G	3.00	REF.
B	4.05	4.25	H	1.50	REF.
C	1.50	1.70	I	0.40	0.52
D	1.30	1.50	J	1.40	1.60
E	2.40	2.60	K	0.35	0.41
F	0.89	1.20	L	5°	TYP.
			M	0.70	REF.

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Junction Temperature	T _j	+150	°C
Storage Temperature	T _{stg}	-55 ~ +150	°C

Absolute Maximum Ratings at Ta = 25°C

Collector to Base Voltage	BVCBO	40	V
Collector to Emitter Voltage	BVCEO	20	V
Emitter to Base Voltage	BVEBO	7.0	V
Collector Current (Continuous)	I _C	5	A
Collector Current (Peak PT=10mS)	I _C	8	A
Total Power Dissipation at Ta = 25°C	PD	1.2	W

Characteristics at Ta = 25°C


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	40	-	-	V	I _C =100uA
BVCEO	20	-	-	V	I _C =1mA
BVEBO	7	-	-	V	I _E =10uA
ICBO	-	-	0.1	uA	VCB=60V
IEBO	-	-	0.1	uA	VEB=7V
*VCE(sat)	-	0.35	1	V	I _C =3A, I _B =0.1A
*hFE1	230	-	800		VCE=2V, I _C =0.5A
*hFE2	150	-	-		VCE=2V, I _C =2A
f _T	-	150	-	MHz	VCE=6V, I _E =50mA
Cob	-	-	50	pF	VCB=20V, f=1MHz

* Pulse Test: Pulse Width ≤ 380us, Duty Cycle ≤ 2%

Classification Of hFE1

Rank	Q	R	S
Range	230-380	340-600	560-800

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
TEL : 86-21-5895-7671 FAX : 86-21-38950165