GRM155F51H472ZA01# "#" indicates a package specification code.













Last Time Buy Date: 31 Mar 2018

Date of discontinuation: 30 Sep 2018

0.5 ±0.05mm

0.15 to 0.35mm

0.3mm min.

0402 (1005M)

< List of part numbers with package codes >


GRM155F51H472ZA01D , GRM155F51H472ZA01W , GRM155F51H472ZA01J

Shape

L size

W size

Tsize



References

Packaging	Specifications	Minimum quantity
D	φ180mm Paper taping	10000
J	φ330mm Paper taping	50000
W	φ180mm Paper taping (W8P1*) * Width: 8mm, Pocket pitch: 1mm	20000

Mass (typ.)	
1 piece	1.6mg
φ180mm Reel	118g

Specifications

Size code in inch(mm)

External terminal width e

Distance between external terminals g

Capacitance	4700pF +80/-20%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	Y5V(EIA)
Capacitance change rate	+22.0/-82.0%
Temperature range of temperature characteristics	-30 to 85°C
Operating temperature range	-30 to 85°C

1 of 1



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.