


Normal Indicator LEDs


RoHS Conformity


Step Type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λp	λd		IV1	IV2	
















1. 8	HS2-142	hi-red	colored diffused	700	658	2.20	1.0	1.0	55
	HS2-145R	hi-eff red		625	618	2.05	10.0	10.0	
	HS2-143	yellow green		570	567	2.15	15.0	15.0	
	HS2-144	yellow		589	585	2.10	8.0	8.0	
	HS2-145	orange		625	618	2.05	10.0	10.0	
	HS2-446AR	super red	water clear	660	645	1.90	800.0	800.0	30

2									
	HS2N-132	hi-red	colored diffused	700	658	2.20	0.8	0.8	125
	HS2N-135R	hi-eff red		625	618	2.05	7.0	7.0	
	HS2N-133	yellow green		570	567	2.15	7.0	7.0	
	HS2N-134	yellow		589	585	2.10	6.0	6.0	
	HS2N-135	orange		625	618	2.05	7.0	7.0	


2									
	HS3-142	hi-red	colored diffused	700	658	2.20	1.7	1.9	30
	HS3-145R	hi-eff red		625	618	2.05	11.0	11.0	
	HS3-143	yellow green		570	567	2.15	12.0	12.0	
	HS3-144	yellow		589	585	2.10	10.0	10.0	
	HS3-145	orange		625	618	2.05	11.0	11.0	
	HS3-146DR	super red		660	645	1.80	45.0	45.0	

IV1:Labsphere LED-1100 IV2:EXELTRON 2001.




Normal Indicator LEDs



RoHS Conformity



Step & 3mm Round type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λp	λd		IV1	IV2	

2. 5									60
	HS5-132	hi-red			700	658	2.20	2.9	1.2
	HS5-135R	hi-eff red			625	618	2.05	20.0	12.0
	HS5-133	yellow green	colored diffused		570	567	2.15	30.0	15.0
	HS5-134	yellow			589	585	2.10	20.0	12.0
	HS5-135	orange			625	618	2.05	20.0	12.0
	HS5-136DR	super red			660	643	1.80	40.0	50.0

3									60
	HB3J-142	hi-red			700	658	2.20	5.0	5.0
	HB3J-145R	hi-eff red			625	618	2.05	50.0	35.0
	HB3J-143	yellow green	colored diffused		570	567	2.15	50.0	40.0
	HB3J-144	yellow			589	585	2.10	40.0	30.0
	HB3J-145	orange			625	618	2.05	50.0	35.0
	HB3J-146ARA/P	super red			660	645	1.86	100.0	200.0

									
φ 3	HB3N-142	hi-red	colored diffused	700	658	2.20	5.0	5.0	60
	HB3N-145R	hi-eff red		625	618	2.05	50.0	35.0	
	HB3N-143	yellow green		570	567	2.15	50.0	40.0	
	HB3N-144	yellow		589	585	2.10	40.0	30.0	
	HB3N-145	orange		625	618	2.05	50.0	35.0	
	HB3N-146CR	super red	660	643	1.8	50.0	130.0	50	
	HB3N-242	hi-red	700	658	2.20	15.0	15.0		
	HB3N-243	yellow green	570	567	2.15	150.0	125.0		
	HB3N-243CG	yellow green	570	567	2.15	550.0	500.0		
	HB3N-244	yellow	589	585	2.10	125.0	95.0		
	HB3N-246CR	super red	660	643	1.80	500.0	400.0		


Normal Indicator LEDs


Standard Diameter 3mm type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λ_p	λ_d		IV1	IV2	












3	HB3b-122	hi-red	colored diffused	700	658	2.20	3.5	5.0	50
	HB3b-125R	hi-eff red		625	618	2.05	18.0	15.0	
	HB3b-123	yellow green		570	567	2.15	25.0	25.0	
	HB3b-124	yellow		589	585	2.10	15.0	15.0	
	HB3b-125	orange		625	618	2.05	12.0	15.0	

φ 3									
	HB3b-142	hi-red	colored diffused	700	658	2.20	5.0	5.0	40
	HB3b-145R	hi-eff red		625	618	2.05	50.0	35.0	
	HB3b-143	yellow green		570	567	2.15	50.0	40.0	
	HB3b-144	yellow		589	585	2.10	40.0	30.0	
	HB3b-945	orange		625	618	2.05	50.0	35.0	
	HB3b-147	Amber		610	607	2.05	50.0	30.0	
	HB3b-242	hi-red	color transparent	700	658	2.20	10.0	8.0	24
	HB3b-245R	hi-eff red		625	618	2.05	90.0	50.0	
	HB3b-243	yellow green		570	567	2.15	120.0	80.0	
	HB3b-244	yellow		589	585	2.10	90.0	50.0	
	HB3b-245	orange		625	618	2.05	90.0	50.0	
	HB3b-246CR	super red		660	643	1.8	650.0	900.0	
	HB3b-442	hi-red	water clear	700	658	2.20	10.0	8.0	
	HB3b-443	yellow green		570	567	2.15	120.0	80.0	
	HB3b-444	yellow		589	585	2.10	90.0	50.0	
	HB3b-445	orange		625	618	2.05	90.0	50.0	

IV1:Labsphere LED-1100 IV2:EXELTRON 2001.



Normal Indicator LEDs



RoHS Conformity



4mm & 4.7mm Round type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λp	λd		IV1	IV2	

									
φ 4	HB4a-132	hi-red	colored diffused	700	658	2.20	5.0	20.0	40
	HB4a-135R	hi-eff red		625	618	2.05	55.0	45.0	
	HB4a-133	yellow green		570	567	2.15	55.0	50.0	
	HB4a-134	yellow		589	585	2.10	45.0	40.0	
	HB4a-135	orange		625	618	2.05	55.0	45.0	
	HB4a-233	yellow green	colored transparent	570	567	2.15	90.0	80.0	30
	HB4a-234	yellow		589	585	2.10	70.0	60.0	25
	HB4a-236DR	super red	pink transparent	660	643	1.80	300.0	250.0	30
	HB4a-636DR	super red		660	643	1.80	300.0	250.0	
	HB4a-436CR	super red		660	643	1.80	570.0	500.0	

φ 4.7									Pb
	HB4b-436DR	super red	water clear	660	643	1.80	300.0	250.0	30

									
φ	HB4-132	hi-red	colored diffused	700	658	2.20	5.0	5.0	50
4.	HB4-135R	hi-eff red		625	618	2.05	20.0	18.0	
7	HB4-133	yellow green		570	567	2.15	25.0	20.0	
	HB4-433DG	yellow green	water clear	570	567	2.15	130.0	130.0	40
	HB4-134	yellow	colored diffused	589	585	2.10	18.0	15.0	50
	HB4-135	orange		625	618	2.05	20.0	18.0	
	HB4-436DR	super red	water	660	645	1.80	300.0	300.0	30
	HB4-436CR	super red	clear	660	645	1.80	600.0	600.0	

IV1:Labsphere LED-1100 IV2:EXELTRON 2001.




Normal Indicator LEDs




RoHS Conformity




Rectangular type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λ_p	λ_d		IV1	IV2	

1x5.0									
	HR1-122	hi-red	colored diffused	700	658	2.20	0.3	1.0	120
	HR1-125R	hi-eff red		625	618	2.05	5.0	7.0	
	HR1-123	yellow green		570	567	2.15	3.0	8.0	
	HR1-124	yellow		589	585	2.10	5.0	6.0	
	HR1-125	orange		625	618	2.05	5.0	7.0	

1x5.0									
	HR1-132	hi-red	colored diffused	700	658	2.20	0.6	1.0	120
	HR1-135R	hi-eff red		625	618	2.05	6.0	7.0	
	HR1-133	yellow green		570	567	2.15	4.0	8.0	
	HR1-134	yellow		589	585	2.10	6.0	6.0	
	HR1-135	orange		625	618	2.05	6.0	7.0	

1X4.8									
	HR1b-132	hi-red	colored diffused	700	658	2.20	0.6	1.0	120
	HR1b-135R	hi-eff red		625	618	2.05	6.0	7.0	
	HR1b-133	yellow green		570	567	2.15	4.0	8.0	
	HR1b-134	yellow		589	585	2.10	6.0	6.0	
	HR1b-135	orange		625	618	2.05	6.0	7.0	

IV1:Labsphere LED-1100 IV2:EXELTRON 2001.




Normal Indicator LEDs




RoHS Conformity




Rectangular type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λ_p	λ_d		IV1	IV2	

2X5.0									
	HR2-132	hi-red	colored diffused	700	658	2.20	0.8	1.0	125
	HR2-135R	hi-eff red		625	618	2.05	6.0	7.0	
	HR2-133	yellow green		570	567	2.15	5.3	8.0	
	HR2-134	yellow		589	585	2.10	6.0	6.0	
	HR2-135	orange		625	618	2.05	6.0	7.0	

2x5.0									
	HR2N-122	hi-red	colored diffused	700	658	2.20	0.6	0.8	150
	HR2N-125R	hi-eff red		625	618	2.05	5.0	5.0	
	HR2N-123	yellow green		570	567	2.15	4.0	6.0	
	HR2N-124	yellow		589	585	2.10	5.0	5.0	
	HR2N-125	orange		625	618	2.05	5.0	5.0	

2x5.0									
	HR2N-132	hi-red	colored diffused	700	658	2.20	0.7	1.0	150
	HR2N-135R	hi-eff red		625	618	2.05	6.0	7.0	
	HR2N-133	yellow green		570	567	2.15	5.0	8.0	
	HR2N-134	yellow		589	585	2.10	6.0	6.0	
	HR2N-135	orange		625	618	2.05	6.0	7.0	




IV1:Labsphere LED-1100 IV2:EXELTRON 2001.




Normal Indicator LEDs




Rectangular type LEDs

IF=20mA Ta=25°C

Device No	Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)		View Angle 2θ1/2
	Emitter	Lens	λp	λd		IV1	IV2	

5.0x5.0									
	HLR5-132	hi-red	colored diffused	700	658	2.20	0.7	0.6	110
	HLR5-135R	hi-eff red		625	618	2.05	9.0	6.0	
	HLR5-133	yellow green		570	567	2.15	4.5	7.0	
	HLR5-134	yellow		589	585	2.10	9.0	5.0	
	HLR5-135	orange		625	618	2.05	9.0	6.0	

5.0X5.0									
	HLR5N-132	hi-red	colored diffused	700	658	2.20	0.7	0.6	110
	HLR5N-135R	hi-eff red		625	618	2.05	9.0	6.0	
	HLR5N-133	yellow green		570	567	2.15	4.5	7.0	
	HLR5N-134	yellow		589	585	2.10	9.0	5.0	
	HLR5N-135	orange		625	618	2.05	9.0	6.0	

2.5X5.0									
	HR5b-132	hi-red	colored diffused	700	658	2.20	1.0	1.1	120
	HR5b-135R	hi-eff red		625	618	2.05	6.0	6.0	
	HR5b-133	yellow green		570	567	2.15	5.0	6.0	
	HR5b-134	yellow		589	585	2.10	6.0	5.5	
	HR5b-135	orange		625	618	2.05	6.0	6.0	

IV1:Labsphere LED-1100 IV2:EXELTRON 2001.

