

Shielded Vertical 1x1 RJ45

8P/8C Vertical Shielded RJ45 Ethernet Connectors



Product Features:


- Shielded RJ45 Connectors
- Minimum of 750 Mating Cycles
- Multiple Gold Contact Plating Options
- DWV - 1500VAC Contact to Shield
- Current Rating - 1.5A
- Voltage Rating - 125V
- UL94V-0 Flammability Rating

Part Number	LED's L/R	Contact Plating (min)	Latch Orientation	Operating Temp Range
HCJV1-802SK	None	6 μ "	Vertical - Top Entry	-40°C to +85°C
HCJV1-804SK	None	30 μ "	Vertical - Top Entry	-40°C to +85°C
HCJV1-805SK	None	50 μ "	Vertical - Top Entry	-40°C to +85°C

Notes:

1. Unshielded, alternate footprints, and panel stop tab variations available. Please contact the factory for additional information.
2. Part specific datasheets available upon request.

Mechanical



DIMENSIONS: mm [inch]
TOLERANCE: .XX ±0.25 [0.010]
.X ±0.30 [0.012]



2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.halo-electronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.

© Copyright 2018 HALO Electronics, Inc. All rights reserved.

Revised 3/2018. Download the latest version at <http://www.halo-electronics.com/pdf/connector-8p8c-shielded-vertical1x1.pdf>