

规格书编号

SPEC NO :

产品规格书 SPECIFICATION

www.DataSheet4U.com

CUSTOMER 客 户: _____
PRODUCT 产 品: **SAW FILTER**
MODEL NO 型 号: **HDVF45A1Dc SIP5Dc**
PREPARED 编 制: _____ CHECKED 审 核: _____
APPROVED 批 准: _____ D A T E 日 期: 2008-11-28

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子有限公司
Shoulder Electronics Limited

更改历史记录 History Record

[illegible]

1.SCOPE

SHOULDER's SAW filter series have broad line up products meeting all broadcast standard including NTSC,PAL and SECAM systems. These filters are composed of two interdigital transducers on a single-crystal, piezoelectrical chip. they are used in electronic equipments such as TV and so on.


2.Construction

2.1 Dimension and materials


Manufacturer's name : SHOULDER ELECTRONICS Co. LTD(CHINA)

Type : VF45A1Dc

www.DataSheet4U.com



2.2. Circuit construction, measurement circuit



Test circuit for SIP-5 filter
Input impedance of the symmetrical post-amplifier: 2 kΩ in parallel with 3 pF

3.Characteristics

Items	Conditions	Specifications
Standard atmospheric conditions	Unless otherwise specified , the standard rang of atmospheric conditions for making measurements and tests is as follows; Ambient temperature : 15℃ to 35℃ Relative humidity : 25% to 85% Air pressure : 86kPa to 106kPa	There shall be no damage.
Operating temperature rang	Operating temperature rang is the rang of ambient temperatures in which the filter can be operated continuously. -10℃ ~ +60℃	
Storage temperature rang	Storage temperature rang is the rang of ambient temperatures at which the filter can be stored without damage. Conditions are as specified elsewhere in these specifications. -40℃ ~ +70℃	
Reference temperature	+25℃	

3.1 Maximum Rating

DC voltage	VDC	12	V	Between any terminals
-------------------	------------	-----------	----------	------------------------------

3.2 Electrical Characteristics

Source impedance

$Z_s=50\ \Omega$

Load impedance


$Z_L=2k\ \Omega //3pF$

$T_A=25^\circ C$

Item	Freq	min	typ	max	
Insertion attenuation	44.06MHz	10.0	12.0	14.0	dB
Reference level					
Relative attenuation	45.81MHz	4.4	5.9	7.4	dB
	42.23MHz	0.7	2.2	3.7	dB
	41.31MHz	25.0	35.0	-	dB
	39.81MHz	42.0	55.0	-	dB
	47.31MHz	40.0	51.0	-	dB
Sidelobe	35.06~39.81MHz	36.0	42.0	-	dB
	47.31~55.06MHz	35.0	40.0	-	dB
Reflected wave signal suppression					
1.1 us ... 6.0 us after main pulse (test pulse 250 ns , carrier frequency 44.06 MHz)		40.0	52.0		dB
Feedthrough signal suppression					
1.2 us ... 1.1 us after main pulse (test pulse 250 ns , carrier frequency 44.06 MHz)		45.0	55.0		dB
Group delay ripple (p-p)		-	50	-	ns
Temperature coefficient of frequency		-72			Ppm/k

3.3 Environmental Performance Characteristics

Item	Condition	Specifications
High temperature	The specimen shall be store at a temperature of $80\pm2^\circ C$ for $96\pm4h$. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.	Mechanical characteristics and specifications in electrical characteristics shall be satisfied. There
Low temperature	The specimen shall be store at a temperature of $-20\pm3^\circ C$ for $96\pm4h$. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.	
Humidity	The specimen shall be store at a temperature of $40\pm2^\circ C$ with relative humidity of 90% to 96%	


	for 96±4h. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.	shall be no excessive change in appearance.																					
Thermal shock	<p>The specimen shall be subjected to 8 continuous cycles each as shown below. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.</p> <table border="1"> <thead> <tr> <th></th><th>Temperature</th><th>Duration</th></tr> </thead> <tbody> <tr> <td>1</td><td>+25 °C=>-40 °C</td><td>0.5h</td></tr> <tr> <td>2</td><td>-40 °C</td><td>4h</td></tr> <tr> <td>3</td><td>-40 °C=>+85 °C</td><td>2h</td></tr> <tr> <td>4</td><td>+85 °C</td><td>4h</td></tr> <tr> <td>5</td><td>+85 °C=>+25 °C</td><td>0.5h</td></tr> <tr> <td>6</td><td>+25 °C</td><td>1h</td></tr> </tbody> </table>		Temperature	Duration	1	+25 °C=>-40 °C	0.5h	2	-40 °C	4h	3	-40 °C=>+85 °C	2h	4	+85 °C	4h	5	+85 °C=>+25 °C	0.5h	6	+25 °C	1h	
	Temperature	Duration																					
1	+25 °C=>-40 °C	0.5h																					
2	-40 °C	4h																					
3	-40 °C=>+85 °C	2h																					
4	+85 °C	4h																					
5	+85 °C=>+25 °C	0.5h																					
6	+25 °C	1h																					
Resistance to Soldering heat	<p>Reflow soldering method Peak: 255 ±5 °C, 220 ±5 °C, 40s At electrode temperature of the specimen.</p>  <p>The specimen shall be passed through the reflow furnace with the condition shown in the above profile for 1 time. The specimen shall be stored at standard atmospheric conditions for 1h, after which the measurement shall be made. Test board shall be 1.6 mm thick. Base material shall be glass fabric base epoxy resin.</p>																						
Solder ability	Immerse the pins melt solder at 260°C+5/-0°C for 5 sec.	More then 95% of total area of the pins should be covered with solder																					

3.4 Mechanical Test



Items	Conditions	Specifications
Vibration	600-3300rpm amplitude 1.5mm 3 directions 2 H each	There shall be no damage.
Drop	On maple plate from 1 m high 3 times	
Lead pull	Pull with 1 kg force for 30 seconds	
Lead bend	90° bending with 500g weigh 2 times	

www.DataSheet4U.com

3.5 Voltage Discharge Test

Item	Condition	Specifications
Surge	<p>Between any two electrode</p> 	There shall be no damage

3.6 Frequency response



www.DataSheet4U.com

