



Micro Commercial Components 21201 Itasca Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

HER101G THRU HER108G

Features

- Fast Switching Speed
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: -55°C to +150°C
 Typical Thermal Resistance; 60°C/W Junction To Case
- 18°C/W Junction To Case


MCC Part	Device	Maximum	Maximum	Maximum
Number	Marking	Recurrent Peak	RMS	DC
		Reverse	Voltage	Blocking
		Voltage		Voltage
HER101G	HER101G	50V	35V	50V
HER102G	HER102G	100V	70V	100V
HER103G	HER103G	200V	140V	200V
HER104G	HER104G	300V	210V	300V
HER105G	HER105G	400V	280V	400V
HER106G	HER106G	600V	420V	600V
HER107G	HER107G	V008	560V	800V
HER108G	HER108G	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward	I	1.0A	$T_A = 55^{\circ}C$
Current	I _{F(AV)}	1.0/	I IA = 355 C
	ı	30A	9.2mc half sino
Peak Forward Surge Current	I _{FSM}	30A	8.3ms, half sine
Maximum			
Instantaneous			
Forward Voltage	V_{F}		
HER101G-104G	VF	1.0V	
HER105G		1.3V	l _{FM} = 1.0A;
HER106G-108G		1.7V	$T_{J} = 25^{\circ}C$
Maximum DC			
Reverse Current At	I _R	5.0uA	$T_{J} = 25^{\circ}C$
Rated DC Blocking		150uA	$T_1 = 125^{\circ}C$
Voltage			.5 .=5 5
Maximum Reverse			
Recovery Time	_		
HÉR101G-105G	Trr	50ns	l ₌ =0.5A, l _R =1.0A
HER106G-108G		75ns	I _{RR} =0.25A
Typical Junction			W. CC.
Capacitance			
HER101G-105G	CJ	20pF	Measured at
HER106G-108G		20pi 15pF	
HEK 100G-100G		ιυρΓ	1.0MHz, V_R =4.0V

1.0 Amp Glass
Passivated High
Efficient Rectifier
50 to 1000 Volts

DO-41



DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.166	.205	4.10	5.20			
В	.080	.107	2.00	2.70			
С	.028	.034	.70	.90			
D	1.000		25.40				

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

HER101G thru HER108G



FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM

50Ω NONINDUCTIVE 10Ω NONINDUCTIVE

(+) 50Vdc (approx) 1Ω NOSCILLOSCOPE (NOTE 1)

NOTES: 1. Rise Time=7ns max. Input Impedance= 1 megohm 22pf 2. Rise Time=10ns max. Sourse Impedance= 50 ohms 50 ohms


FIG.2- MAXIMUM FORWARD CURRENT DERATING CURVE


2.0


Single Phase Half Wave 60Hz Resistive or Inductive Load 0.375° (9.5mm) Lead Length


25 50 75 100 125 150 175 AMBIENT TEMPERATURE. (°C)

FIG.3- TYPICAL REVERSE CHARACTERISTICS











Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 50Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.