

Features


- * Low Forward Voltage Drop
- * High Current Capability
- * High Reliability
- * High Surge Current Capability



RoHS
COMPLIANT

Package Outline Dimensions

DO-15:



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	2.6	3.6	0.102	0.142
B	0.7	0.9	0.027	0.035
C	25.4	-	1.0	-
D	5.8	7.6	0.228	0.300
E	25.4	-	1.0	-

Mechanical Data

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting Position: Any

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Type Number	Symbol	HER 151	HER 152	HER 153	HER 154	HER 155	HER 156	HER 157	HER 158	Unit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	300	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	210	280	420	560	700	V
Maximum D.C Blocking Voltage	V _{DC}	50	100	200	300	400	600	800	1000	V
Maximum Average Forward Rectified Current .375" (9.5mm)Lead Length @ T _A =55℃	I _{F(AV)}	1.5								A
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I _{FSM}	50								A
Maximum Instantaneous Forward Voltage at 1.5A	V _F	1.0				1.3	1.7			V
Maximum D.C Reverse Current @ T _A =25℃ at Rated D.C Blocking Voltage @ T _A =100℃	I _R	5.0 100								μ A
Maximum Reverse Recovery Time(Note1)	T _{rr}	50					75			nS
Typical Junction Capacitance(Note2)	C _J	50					30			pF
Operating and Storage Temperature Range	T _J /T _{STG}	-55 to +125 / -55 to +150								℃

Note:1、 Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$. 2、 Measured at 1MHz and Applied Reverse Voltage of 4.0V D.C.

Ratings and Characteristic Curves

FIG. 1 – TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTICS




FIG. 2 – TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 – TYPICAL REVERSE CHARACTERISTICS




FIG. 4 – TYPICAL FORWARD CHARACTERISTICS




FIG. 5 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT





FIG. 6 – TYPICAL JUNCTION CAPACITANCE





HER151 THRU HER158

1.5 Amps. High Efficiency Rectifiers

Ordering Information

Part No.	Package	Packing
HER151~HER158	DO-15	2K/AMMO box
HER151~HER158	DO-15	3K/AMMO box
HER151~HER158	DO-15	4K/13" Paper reel
HER151~HER158	DO-15	0.5K/Bulk packing