



PROPRIETARY NOTE

THIS SPECIFICATION IS THE PROPERTY OF BOE CQ AND SHALL NOT BE
REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE CQ
AND MUST BE RETURNED TO BOE CQ UPON ITS REQUEST

TITLE : HV320WHB-N82

Product Specification

Rev. O

Chongqing BOE Optoelectronics Technology Co., Ltd

SPEC. NUMBER S871-C010	PRODUCT GROUP TFT-LCD	Rev. O	ISSUE DATE 2015.8.24	PAGE 1 OF 25
---------------------------	--------------------------	--------	-------------------------	-----------------

	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

REVISION HISTORY

Revision No.	Page	Description of changes	Date	Prepared
O	25	Initial Release	2015.08.24	SH.Gao

--

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 2 OF 25
---------------------------	---	-----------------

	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

Contents

No.	Item	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	8
5.0	Interface Connection	10
6.0	Signal Timing Specifications	14
7.0	Signal Timing Waveforms of Interface Signal	15
8.0	Input Signals, Display Colors & Gray Scale of Colors	16
9.0	Power Sequence	17
10.0	Mechanical Characteristics	18
11.0	Reliability Test	19
12.0	Handling& Cautions	20
13.0	Product Serial Number	21
14.0	Packing	22
15.0	Appendix	24


SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 3 OF 25
---------------------------	---	-----------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

1.0 GENERAL DESCRIPTION

1.1 Introduction

HV320WHB-N82 is a color active matrix TFT LCD open cell using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This open cell has a 31.51 inch diagonally measured active area with HD resolutions (1366 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this open cell can display 16.7M colors. The TFT-LCD panel used for this open cell is adapted for a low reflection and higher color type.



1.2 Features

- LVDS interface with 1 pixel / clock
- High-speed response
- Low color shift image quality
- 8-bit color depth, display 16.7M colors
- High luminance and contrast ratio, low reflection and wide viewing angle
- DE (Data Enable) only mode
- ADS technology is applied for high display quality
- RoHS compliant

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 4 OF 25
---------------------------	---	-----------------

1.3 Application

- Home Alone Multimedia TFT-LCD TV
- Display Terminals for Control System
- High Definition TV(HD TV)
- TV application Products

1.4 General Specification

< Table 1. General Specifications >

Parameter	Specification	Unit	Remark
Active area	697.685(H) × 392.256(V)	mm	
Number of pixels	1366(H) × 768(V)	pixels	
Pixel pitch	510.75(H) × RGB × 510.75(V)	μm	
Pixel arrangement	Pixels RGB Vertical stripe		
Display colors	16.7M(8bits-true)	colors	
Display mode	Transmission mode, Normally Black		
Open Cell Transmittance	6.2 (typ.)	%	At center point with BOE BLU
Weight	880 (typ.)	gram	
Power Consumption	4.0 (typ.)	Watt	
Surface Treatment	Front Polarizer : Haze 1%, 3H, Semi-glare or Anti-glare treatment Bottom Polarizer : Clear		

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.


< Table 2. Open Cell Electrical Specifications >

[VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remark
Power Supply Voltage	VDD	VSS-0.3	13.2	V	Ta = 25 °C
Operating Temperature	T _{OP}	0	+50	°C	Note 1
	T _{SUR}	0	+60	°C	
Storage Temperature	T _{ST}	-20	+60	°C	
Operating Ambient Humidity	Hop	10	90	%RH	
Storage Humidity	Hst	10	90	%RH	

Note 1 : Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39 °C max. and no condensation of water.






3.0 ELECTRICAL SPECIFICATIONS

< Table 3. Open Cell Electrical Specifications > [Ta =25±2 ℃]

Parameter		Symbol	Values			Unit	Remark
			Min	Typ	Max		
Power Supply Input Voltage		VDD	10.8	12	13.2	Vdc	
Power Supply Ripple Voltage		VRP			600	mV	
Power Supply Current		IDD	-	350	550	mA	Note 1
Power Consumption		PDD		4.2	6.6	Watt	
Rush current		IRUSH	-	-	3.0	A	Note 2
LVDS Interface	Differential Input High Threshold Voltage	VLVTH	+100		+300	mV	
	Differential Input Low Threshold Voltage	VLVTL	-300		-100	mV	
	Common Input Voltage	VLVC	1.0	1.2	1.4	V	
CMOS Interface	Input High Threshold Voltage	VIH	2.7	-	3.3	V	
	Input Low Threshold Voltage	VIL	0	-	0.6	V	

Note 1 : The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for VDD=12.0V,
Frame rate f_v=60Hz and Clock frequency = 75.4MHz.
Test Pattern of power supply current
a) Typ : Mosaic 8 x 6 Pattern(L0/L255) b) Max : Gray Level Pattern L255 c) Flicker Test Pattern



Note 2 : The duration of rush current is about 2ms and rising time of Power Input is 1ms(min)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

4.0 OPTICAL SPECIFICATION

The test of optical specifications shall be measured in a dark room (ambient luminance≤1 lux and temperature=25±2℃) with the equipment of Luminance meter system (Goniometer system and PR730) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0°. We refer to θ₀₌₀ (=θ₃) as the 3 o'clock direction (the “right”), θ₀₌₉₀ (= θ₁₂) as the 12 o'clock direction (“upward”), θ₀₌₁₈₀ (= θ₉) as the 9 o'clock direction (“left”) and θ₀₌₂₇₀(= θ₆) as the 6 o'clock direction (“bottom”). While scanning θ and/or Ø, the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 12.0V +/-10% at 25℃. Optimum viewing angle direction is 6 ’clock.

< Table 4. Optical Table >
[VDD = 12.0V, Frame rate = 60Hz, Ta =25±2 ℃]

Parameter		Symbol	Condition	Min	Typ	Max	Unit	Remark
Viewing Angle	Horizontal	Θ_3	CR > 10		89		Deg.	Note 1
		Θ_9			89		Deg.	
	Vertical	Θ_{12}			89		Deg.	
		Θ_6			89		Deg.	
Contrast ratio		CR	$\Theta = 0^\circ$ (Center) Normal Viewing Angle With BOE Module	900:1	1200:1	-		Note 2
Reproduction of color	White	W_x		TYP. - 0.03	0.290	TYP. + 0.03		Note 3 (O/C在C光下模拟值)
		W_y			0.328			
	Red	R_x			0.655			
		R_y			0.325			
	Green	G_x			0.265			
		G_y			0.584			
	Blue	B_x			0.141			
		B_y			0.132			
Response Time	G to G	T_g		-	8	10	ms	Note 4
Gamma Scale				2.0	2.2	2.4		
Cell Transmittance					6.2		%	Note 5

Note :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
2. Contrast measurements shall be made at viewing angle of $\theta = 0^\circ$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See Figure 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. The color chromaticity coordinates specified in Table 9. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
4. Response time T_g is the average time required for display transition by switching the input signal as below table and is based on Frame rate $f_V = 60\text{Hz}$ to optimize.
Each time in below table is defined as Figure 2 and shall be measured by switching the input signal for "any level of gray(bright)" and "any level of gray(dark)".

Measured Response Time		Target																
		0	15	31	47	63	79	95	111	127	143	159	175	191	207	223	239	255
Start	0																	
	15																	
	31																	
	47																	
	63																	
	79																	
	95																	
	111																	
	127																	
	143																	
	159																	
	175																	
	191																	
	207																	
	223																	
239																		
255																		

5. Definition of Transmittance (T%) :

Module is with white(L255) signal input

$$\text{Transmittance} = \frac{\text{Luminance of LCD Module}}{\text{Luminance of BLU}} \times 100 \%$$

5.0 INTERFACE CONNECTION.

5.1 Open Cell Input Signal & Power

- Connector : IS100-L30B-C23(Manufactured by UJU) or Equivalent.

< Table 5. Open Cell Input Connector Pin Configuration >

Pin No	Symbol	Description	Pin No	Symbol	Description
1	VDD	Power Supply +12.0V	16	RX1+	LVDS Receiver Signal(+)
2	VDD	Power Supply +12.0V	17	GND	Ground
3	VDD	Power Supply +12.0V	18	RX2-	LVDS Receiver Signal(-)
4	VDD	Power Supply +12.0V	19	RX2+	LVDS Receiver Signal(+)
5	GND	Ground	20	GND	Ground
6	GND	Ground	21	RCLK-	LVDS Receiver Clock Signal(-)
7	GND	Ground	22	RCLK+	LVDS Receiver Clock Signal(+)
8	GND	Ground	23	GND	Ground
9	LVDS_SEL	'L'=JEIDA , 'H'or NC= VESA	24	RX3-	LVDS Receiver Signal(-)
10	NC	No Connection	25	RX3+	LVDS Receiver Signal(+)
11	GND	Ground	26	GND	Ground
12	RX0-	LVDS Receiver Signal(-)	27	BIST	'L' or NC=Free run mode , 'H'= BIST mode
13	RX0+	LVDS Receiver Signal(+)	28	NC	No Connection
14	GND	Ground	29	NC	No Connection
15	RX1-	LVDS Receiver Signal(-)	30	GND	Ground

Notes : 1. NC(Not Connected) : This pins are only used for BOE internal operations.

2. Input Level of LVDS signal is based on the IEA 664 Standard.

3. LVDS_SEL : This pin is used for selecting LVDS signal data format.

If this Pin : High (3.3V) or Open (NC) → Normal NS LVDS format

Otherwise : Low (GND) → JEIDA LVDS format

4. BIST : This pin is used for selecting display pattern mode when input DE or input CLOCK quits toggling.

If this Pin : Low (GND) or Open (NC) → Free run mode(Black Pattern)


Otherwise : High(3.3V) → BIST mode(BIST Pattern)

Sequence : On = VDD ≥ LVDS Option , BIST Option ≥ Interface signal

Off = Interface signal ≥ LVDS Option , BIST Option ≥ VDD

Rear view of LCM

BIST Pattern



BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

5.2 LVDS Interface

- LVDS Receiver : Timing Controller (LVDS Rx merged) / LVDS Data : Pixel Data

< Table 6. Open Cell Input Connector Pin Configuration >

	LVDS Pin	Vesa Data format	JEIDA Data format	Remark
TxOUT/RxIN0	TxIN/RxOUT0	Red0 [LSB]	R2	
	TxIN/RxOUT1	Red1	R3	
	TxIN/RxOUT2	Red2	R4	
	TxIN/RxOUT3	Red3	R5	
	TxIN/RxOUT4	Red4	R6	
	TxIN/RxOUT6	Red5	R7 [MSB]	
	TxIN/RxOUT7	Green0 [LSB]	G2	
TxOUT/RxIN1	TxIN/RxOUT8	Green1	G3	
	TxIN/RxOUT9	Green2	G4	
	TxIN/RxOUT12	Green3	G5	
	TxIN/RxOUT13	Green4	G6	
	TxIN/RxOUT14	Green5	G7 [MSB]	
	TxIN/RxOUT15	Blue0 [LSB]	B2	
	TxIN/RxOUT18	Blue1	B3	
TxOUT/RxIN2	TxIN/RxOUT19	Blue2	B4	
	TxIN/RxOUT20	Blue3	B5	
	TxIN/RxOUT21	Blue4	B6	
	TxIN/RxOUT22	Blue5	B7 [MSB]	
	TxIN/RxOUT24	HSYNC	HSYNC	
	TxIN/RxOUT25	VSYNC	VSYNC	
	TxIN/RxOUT26	DEN	DEN	
TxOUT/RxIN3	TxIN/RxOUT27	Red6	R0 [LSB]	
	TxIN/RxOUT5	Red7 [MSB]	R1	
	TxIN/RxOUT10	Green6	G0 [LSB]	
	TxIN/RxOUT11	Green7 [MSB]	G1	
	TxIN/RxOUT16	Blue6	B0 [LSB]	
	TxIN/RxOUT17	Blue7 [MSB]	B1	
	TxIN/RxOUT23	Reserved	Reserved	


SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 11 OF 25
---------------------------	---	------------------

5.3 LVDS Rx Interface Timing Parameter

The Specification of the LVDS Rx interface timing parameter is shown in Table6

< Table 6. LVDS Rx Interface Timing Specification >

Item	Symbol	Min	Typ	Max	Unit	Note
CLKIN Period	T	11.8	13.3	17.9	nsec	
Input Data0	tRCIP1	0.5T/7-0.4	0.5T/7	0.5T/7+0.4	nsec	
Input Data1	tRCIP0	1.5T/7-0.4	1.5T/7	1.5T/7+0.4	nsec	
Input Data2	tRCIP6	2.5T/7-0.4	2.5T/7	2.5T/7+0.4	nsec	
Input Data3	tRCIP5	3.5T/7-0.4	3.5T/7	3.5T/7+0.4	nsec	
Input Data4	tRCIP4	4.5T/7-0.4	4.5T/7	4.5T/7+0.4	nsec	
Input Data5	tRCIP3	5.5T/7-0.4	5.5T/7	5.5T/7+0.4	nsec	
Input Data6	tRCIP2	6.5T/7-0.4	6.5T/7	6.5T/7+0.4	nsec	




Notes: Input frequency range from 25MHz to 110MHz

5.4 LVDS Rx Interface Eye Diagram

< Table 6. LVDS Rx Interface Eye Diagram>

Symbol	Min	Typ	Max	Unit	Note
A	—	100	—	mV	
B	—	100	—	mV	
C	—	0	—	mV	
D	—	-100	—	mV	
E	—	-100	—	mV	
F	—	0	—	mV	



- Notes: 1. Time F to A,B to C,C to D,E to F is 150p second.
 2. LVDS clock=85Mhz.
 3. The time A to B=1T-2*TRSKM-2*150ps.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

6.0 SIGNAL TIMING SPECIFICATION

< Table 7. Timing Table >

ITEM	Symbol		Min	Typ	Max	Unit	Note
CLK	Period	t _{CLK}	11.8	13.3	17.9	ns	
	Frequency	-	56	75.4	85.0	MHz	
Hsync	Period	t _{HP}	1450	1560	2000	t _{CLK}	
	Frequency	f _H	39.4	48.4	55	KHz	
Vsync	Period	t _{VP}	778	806	1200	t _{HP}	
	Frequency	f _V	47	60	65	Hz	
Horizontal Active Display Term	Valid	t _{HV}	-	1366	-	t _{CLK}	
	Total	t _{HP}	1450	1560	2000	t _{CLK}	
Vertical Active Display Term	Valid	t _{VV}	-	768	-	t _{HP}	
	Total	t _{VP}	778	806	1200	t _{HP}	



Notes: This product is DE only mode. The input of Hsync & Vsync signal does not have an effect on normal operation.

< Table 8. LVDS Input SSC>

Symbol	Parameter	Condition	Min	Typ	Max	Unit
F	LVDS Input frequency	-	56	75.4	85.0	MHz
T _{LVSK}	LVDS channel to channel skew	F=65MHz V _{IC} =1.2V V _{ID} =±200mV	-600	-	+600	ps
F _{LVMOD}	Modulating frequency of input clock during SSC	F=85MHz V _{IC} =1.2V V _{ID} =±200mV	10	-	300	KHz
F _{LVDEV}	Maximum deviation of input clock frequency during SSC		-3	-	+3	%
T _{CY-CY}	Cycle to Cycle jitter		-	-	200	ps

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 14 OF 25
---------------------------	---	------------------

7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL



BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24


8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

< Table 8. Input Signal and Display Color Table >

Color & Gray Scale		Input Data Signal																			
		Red Data								Green Data								Blue Data			
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	△																				
	▽																				
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
	△																				
	▽																				
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0
Gray Scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△																				
	▽																				
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1
Gray Scale of White	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0
	△																				
	▽																				
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	0
	▽	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the Open Cell, the power on/off sequence shall be as shown in below



< Table 9. Sequence Table >

Parameter	Values			Units
	Min	Typ	Max	
T1	0.5	-	20	ms
T2	0	-	50	ms
T3	200	-	-	ms
T4	200	-	-	ms
T5	0	-	50	ms
T6	1	-	-	s

- Notes: 1. Even though T1 is over the specified value, there is no problem if I2T spec of fuse is satisfied.
2. Back Light must be turn on after power for logic and interface signal are valid.

	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

10.0 MECHANICAL CHARACTERISTICS

Figure 3 (located in Appendix) shows mechanical outlines for the model HV320WHB-N82. Other parameters are shown in Table 10.

< Table 10. Dimensional Parameters >

Parameter	Specification	Unit
Active area	697.685 (H) × 392.256(V)	mm
Pixel pitch	0.51(H) × 0.51(V)	mm
Number of pixels	1366(H) × 768(V) (1 pixel = R + G + B dots)	pixels
Weight	880(typ.)	gram

The surface of the LCD has an semi-glare coating to minimize reflection and a coating to reduce scratching.

11.0 RELIABILITY TEST

< Table 11. Reliability Test Condition >

Item	Test Condition
High-Temp/STG	Ta = 60 °C , 240 hrs
Low-Temp/STG	Ta = -20 °C , 240 hrs
Temp-Humi/OP	Ta = 50 °C , 80%RH, 240hrs
High-Temp/OP	Ta = 50 °C , 240hrs
Low-Temp/OP	Ta = -5 °C , 240hrs
TST	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle

This test condition is based on BOE module.

	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24
12.0 HANDLING & CAUTIONS (1) Cautions when taking out the Panel • Pick the pouch only, when taking out panel from a shipping package. (2) Cautions for handling the panel • As the electrostatic discharges may break the LCD panel, handle the LCD panel with care. Peel a protection sheet off from the LCD panel surface as slowly as possible. • As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD panel should be avoided. • As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning. • Do not pull the interface connector in or out while the LCD panel is operating. • Put the panel display side down on a flat horizontal plane. • Handle connectors and cables with care. (3) Cautions for the operation • When the panel is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged. • Obey the supply voltage sequence. If wrong sequence is applied, the panel would be damaged. (4) Cautions for the atmosphere • Dew drop atmosphere should be avoided. • Do not store and/or operate the LCD panel in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended. (5) Cautions for the panel characteristics • Do not apply fixed pattern data signal to the LCD panel at product aging. • Applying fixed pattern for a long time may cause image sticking. (6) Other cautions • Do not disassemble and/or re-assemble LCD panel. • Do not re-adjust variable resistor or switch etc. • When returning the panel for repair or etc., Please pack the panel not to be broken. We recommend to use the original shipping packages.			
SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O		PAGE 20 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

13.0 PRODUCT SERIAL NUMBER



MDL ID Naming Rule:

Digit Code	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	S	L	S	F	1	2	3	5	9	0	0	0	0
Description	Model Code /GBN		Grade	Line	Year		Month	Model Extension Code		Serial No 0001-ZZZZ			

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 21 OF 25
---------------------------	---	------------------


BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

14.0 Packing


BOE provides the standard shipping container for customers, unless customer specifies their packing information. The standard packing method and Barcode information are shown in below.

14.1 Packing Order


Put EPE pad and panels into the box, 15pcs panels per box



Put the box on the pallet,8ea boxes per quarter pallet, a cover on the top of the boxes



Use wrapping film to bind up them



16ea boxes and 2covers per pallet

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 22 OF 25
---------------------------	---	------------------


	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

14.2 Packing Note

- Box Dimension : 857mm(L)×558mm(W)×142mm(G)
- Package Quantity in one Box : 15pcs

14.3 Box Label

- Label Size : 100 mm (L) × 50 mm (W)
- Contents
 - Model : HV320WHB-N82
 - Q`ty : 15pcs Open Cell in one box.
 - Serial No. : Box Serial No.
 - Date : Packing Date



Box ID Naming Rule:


Digit	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	S	L	S	F	1	2	3	D	0	0	0	6	8
Description	Products GBN		Grade	Line	Year		Month	Revision Code	Serial No				

SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 23 OF 25
---------------------------	---	------------------


BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

15.0 APPENDIX

< Figure 1. Measurement Set Up >




< Figure 2. Response Time Testing >



SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 24 OF 25
---------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer SPEC	Rev. O	2015.8.24

< Figure 3. TFT-LCD Open Cell Outline Dimensions (Front View) >



SPEC. NUMBER S871-C010	SPEC. TITLE HV320WHB-N82 Product Specification Rev.O	PAGE 25 OF 25
---------------------------	---	------------------