

HY-226M/HY-256M

3 tones electronic buzzer

- Compact, light weight and composed of 3 melodies
- Front LED lighted when operating the buzzer
- Excellent attachment due to the panel type
- Low power consumption



Suffix code

Model	Code	Description
HY-	☐ ☐	3 tones electronic buzzer
Dimension	226	Ø22 / Ø25 dual usage (Rectangular shaped front)
	256	For Ø25 installation (Round shaped front)
Power supply voltage	MD	12 – 24 V d.c
	MA	100 – 240 V a.c

Specification

Model	HY-226MD	HY-226MA	HY-256MD	HY-226MA
Installation diameter	Ø22 / Ø25 dual usage		Ø25	
Power supply voltage	12 – 24 V d.c	100 – 240 V a.c (50 – 60 Hz)	12 – 24 V d.c	100 – 240 V a.c (50 – 60 Hz)
Power consumption	0.6 W	13.5 W	0.6 W	13.5 W
Volume	80 dB	80 dB	80 dB	80 dB

Tone selection

Tone selection	Tone symbol	Information
SELECT-1	🔊.....	fast beeping
SELECT-2	🔊-----	slow beeping
REMOVE	🔊—————	Continuous tone


HY-226M/HY-256M

Dimension (unit : mm)


Model	Appearance	Dimension	
HY-226			
HY-256			

Panel cutout dimension (unit : mm)

• HY-226



• HY-226 / HY-256


Control
switch
Combination
display light

Power switch
Main switch
Cam switch

Limit switch
Micro switch

Hoist switch
Foot switch
Mono lever switch

Sign tower
Signal light

Buzzer
Terminal block
Fuse holder

Control box
Cable connector

Discontinued
Products