


P-Channel Enhancement Mode MOSFET

FeatureDescription


- -30V/-8A
 $R_{DS(ON)} = 21.6m\Omega (typ.) @ V_{GS} = -10V$
 $R_{DS(ON)} = 42 m\Omega (typ.) @ V_{GS} = -4.5V$
- 100% Avalanche Tested
- Reliable and Rugged
- Halogen Free and Green Devices Available
(RoHS Compliant)

Pin Description



Applications

- Power Management for DC/DC
- Switching Application
- Battery protection



Ordering and Marking Information

P-Channel MOSFET

 S G260P03 XXXYWXXXXX	<table><tr><td data-bbox="821 1400 1002 1435">Package Code</td><td data-bbox="837 1444 965 1480">S: SOP-8L</td></tr><tr><td data-bbox="821 1529 954 1565">Date Code</td><td data-bbox="821 1563 1013 1599">XXXYWXXXXX</td></tr><tr><td data-bbox="1086 1529 1305 1565">Assembly Material</td><td data-bbox="1102 1563 1294 1599">G:Halogen Free</td></tr></table>	Package Code	S: SOP-8L	Date Code	XXXYWXXXXX	Assembly Material	G:Halogen Free
Package Code	S: SOP-8L						
Date Code	XXXYWXXXXX						
Assembly Material	G:Halogen Free						

Note:HUAYI lead-free products contain molding compounds/die attach materials and 100% matte tin plateTerminationfinish;which are fully compliant with RoHS.HUAYI lead-free products meet or exceed the lead-Free requirements of IPC/JEDEC J-STD-020 for MSL classification at lead-free peak reflow temperature.HUAYI defines “Green” to mean lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

HUAYI reserves the right to make changes, corrections, enhancements, modifications, and improvements to this product and/or to this document at any time without notice.

Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (Tc=25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		-30	V
V _{GSS}	Gate-Source Voltage		±20	V
T _J	Junction Temperature Range		-55 to 175	°C
T _{STG}	Storage Temperature Range		-55 to 175	°C
I _S	Source Current-Continuous(Body Diode)	Tc=25°C	-8	A
Mounted on Large Heat Sink				
I _{DM}	Pulsed Drain Current *	Tc=25°C	-32	A
I _D	Continuous Drain Current	Tc=25°C	-8	A
		Tc=100°C	-5.6	A
P _D	Maximum Power Dissipation	Tc=25°C	3	W
		Tc=100°C	1.5	W
R _{θJA}	Thermal Resistance, Junction-to-Ambient **		50	°C/W
E _{AS}	SinglePulsed-Avalanche Energy ***	L=0.3mH	50***	mJ

Note: * Repetitive rating; pulse width limited by max.junction temperature.
 ** Surface mounted on 1in2 FR-4 board t≤10sec.
 *** Limited by T_{Jmax}, starting T_J=25°C, L = 0.3mH, R_G= 25Ω, V_{GS}=-10V.

Electrical Characteristics(Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG260P03LR1			Unit
			Min	Typ.	Max	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =-250uA	-30	-	-	V
I _{DSS}	Drain-to-Source LeakageCurrent	V _{DS} =-30V, V _{GS} =0V	-	-	1	μA
			T _J =125°C	-		50
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250uA	-1.0	-1.9	-3.0	V
I _{GSS}	Gate-Source Leakage Current	V _{GS} = ± 20V,V _{DS} =0V	-	-	±100	nA
R _{DS(ON)*}	Drain-Source On-State Resistance	V _{GS} =-10V,I _{DS} =-6A	-	21.6	30	mΩ
		V _{GS} =-4.5V,I _{DS} =-4A	-	42	55	
Diode Characteristics						
V _{SD} *	Diode Forward Voltage	I _{SD} =-1A,V _{GS} =0V	-	-0.7	-1	V
t _{rr}	Reverse Recovery Time	I _{SD} =-3A,dI _{SD} /dt=100A/us	-	29	-	ns
Q _{rr}	Reverse Recovery Charge		-	12	-	nC

Electrical Characteristics (Cont.) (Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG260P03LR1			Unit
			Min	Typ.	Max	
Dynamic Characteristics						
R _G	Gate Resistance	V _{GS} =0V,V _{DS} =0V, Frequency=1.0MHz	-	8.5	-	Ω
C _{iss}	Input Capacitance	V _{GS} =0V,	-	1210	-	pF
C _{oss}	Output Capacitance	V _{DS} =-25V,	-	120	-	
C _{rss}	Reverse Transfer Capacitance	Frequency=1.0MHz	-	86	-	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =-15V,R _G =1Ω, I _{DS} =-3A,V _{GS} =-10V	-	8	-	ns
T _r	Turn-on Rise Time		-	5	-	
t _{d(OFF)}	Turn-off Delay Time		-	15	-	
T _f	Turn-off Fall Time		-	11	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge	V _{DS} = -24V, V _{GS} = -10V, I _D = -6A,	-	18.5	-	nC
Q _{gs}	Gate-Source Charge		-	5.4	-	
Q _{gd}	Gate-Drain Charge		-	2.8	-	

Note: *Pulse test, pulse width ≤ 300us, duty cycle ≤ 2%

Typical Operating Characteristics

Figure 1: Power Dissipation




Figure 2: Drain Current




Figure 3: Safe Operation Area




Figure 4: Thermal Transient Impedance




Figure 5: Output Characteristics





Figure 6: Drain-Source On Resistance



Typical Operating Characteristics(Cont.)

Figure 7: On-Resistance vs. Temperature




Figure 8: Source-Drain Diode Forward




Figure 9: Capacitance Characteristics









Figure 10: Gate Charge Characteristics





Avalanche Test Circuit



Switching Time Test Circuit



Gate Charge Test Circuit




Device Per Unit

Package Type	Unit	Quantity
SOP-8L	Reel	2500


Package Information

SOP-8L



	SOP-8L			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	-	1.75	-	0.069
A1	0.10	0.25	0.004	0.010
A2	1.25	-	0.049	-
b	0.31	0.51	0.012	0.020
c	0.17	0.25	0.007	0.010
D	4.80	5.00	0.189	0.197
E	5.80	6.20	0.228	0.244
E1	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
h	0.25	0.50	0.010	0.020
L	0.40	1.27	0.016	0.050
θ	0°	8°	0°	8°


RECOMMENDED LAND PATTERN



- Note: 1. Follow JEDEC MS-012 AA.
 2. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion or gate burrs shall not exceed 6 mil per side.
 3. Dimension "E" does not include inter-lead flash or protrusions. Inter-lead flash and protrusions shall not exceed 10 mil per side.

HYG260P03LR1S


Carrier Tape & Reel Dimensions




Application	A	H	T1	C	d	D	W	E1	F
SOP-8L	330.0 2.00	50 MIN.	12.4+2.00 -0.00	13.0+0.50 -0.20	1.5 MIN.	20.2 MIN.	12.0 0.30	1.75 0.10	5.5 0.05
	P0	P1	P2	D0	D1	T	A0	B0	K0
	4.0 0.10	8.0 0.10	2.0 0.05	1.5+0.10 -0.00	1.5 MIN.	0.6+0.00 -0.40	6.40 0.20	5.20 0.20	2.10 0.20

(mm)

Taping Direction Information



Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak		
Temperature min (T_{smin})	100 °C	150 °C
Temperature max (T_{smax})	150 °C	200 °C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60-120 seconds
Average ramp-up rate (T_{smax} to T_P)	3 °C/second max.	3 °C/second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time at liquidous (t_L)	60-150 seconds	60-150 seconds
Peak package body Temperature (T_P)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (t_P)** within 5°C of the specified classification temperature (T_c)	20** seconds	30** seconds
Average ramp-down rate (T_P to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.
*Tolerance for peak profile Temperature (T_P) is defined as a supplier minimum and a user maximum.		
** Tolerance for time at peak profile temperature (t_P) is defined as a supplier minimum and a user maximum.		

Table 1. SnPb Eutectic Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2. Pb-free Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ ≥2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HTRB	JESD-22, A108	168 Hrs \ 500Hrs\ 1000 Hrs, Bias @ 125°C
PCT	JESD-22, A102	96 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	500 Cycles, -55°C~150°C

Customer Service

Worldwide Sales and Service: sales@hymexa.com

Technical Support: Technology@hymexa.com

Xi'an Huayi Microelectronics Co., Ltd.

No.8928, Shangji Road, Economic and Technological Development Zone, Xi'an, China

TEL: (86-029) 86685706

FAX: (86-029) 86685705

E-mail: sales@hymexa.com

Web net: www.hymexa.com