



3.3V CMOS 12-BIT TO 24-BIT REGISTERED BUS EXCHANGER WITH 3-STATE OUTPUTS AND BUS-HOLD

IDT74ALVCH16270

FEATURES:

- 0.5 MICRON CMOS Technology
- Typical $t_{SK(O)}$ (Output Skew) < 250ps
- ESD > 2000V per MIL-STD-883, Method 3015; > 200V using machine model (C = 200pF, R = 0)
- $V_{CC} = 3.3V \pm 0.3V$, Normal Range
- $V_{CC} = 2.7V$ to $3.6V$, Extended Range
- $V_{CC} = 2.5V \pm 0.2V$
- CMOS power levels ($0.4\mu W$ typ. static)
- Rail-to-Rail output swing for increased noise margin
- Available in SSOP, TSSOP, and TVSOP packages

DRIVE FEATURES:

- High Output Drivers: $\pm 24mA$
- Suitable for heavy loads

APPLICATIONS:

- 3.3V high speed systems
- 3.3V and lower voltage computing systems

DESCRIPTION:


This registered bus exchanger is built using advanced dual metal CMOS technology. The ALVCH16270 is used in applications in which data must be transferred from a narrow high-speed bus to a wide lower-frequency bus.

This device provides synchronous data exchange between the two ports. Data is stored in the internal registers on the low-to-high transition of the clock (CLK) input when the appropriate clock-enable (CLKEN) inputs are low. The select (SEL) line selects 1B or 2B data for the A outputs. For data transfer in the A-to-B direction, a two-stage pipeline is provided in the A-to-1B path, with a single storage register in the A-to-2B path. Proper control of the CLKENA input allows two sequential 12-bit words to be presented synchronously as a 24-bit word on the B-port. Data flow is controlled by the active-low output enables (\overline{OEA} and \overline{OEB}). The control terminals are registered to synchronize the bus-direction changes with CLK.

The ALVCH16270 has been designed with a $\pm 24mA$ output driver. This driver is capable of driving a moderate to heavy load while maintaining speed performance.

The ALVCH16270 has "bus-hold" which retains the inputs' last state whenever the input goes to a high impedance. This prevents floating inputs and eliminates the need for pull-up/down resistors.


FUNCTIONAL BLOCK DIAGRAM



The IDT logo is a registered trademark of Integrated Device Technology, Inc.

INDUSTRIAL TEMPERATURE RANGE

PIN CONFIGURATION



SSOP/ TSSOP/ TVSOP
TOP VIEW

A-TO-B STORAGE ($\overline{OEB} = L$ AND $\overline{OEA} = H$)

| Inputs | | | Outputs | | |
|---------|---------|--------|---------|--------------------------------|--------------------------------|
| CLKENA1 | CLKENA2 | CLK | Ax | 1Bx | 2Bx |
| L | H | ↑ | L | 1B ₀ ⁽²⁾ | 2B ₀ ⁽²⁾ |
| L | H | ↑ | H | 1B ₀ ⁽²⁾ | 2B ₀ ⁽²⁾ |
| L | L | ↑ | L | L ⁽³⁾ | L |
| L | L | ↑ | H | H ⁽³⁾ | H |
| H | L | ↑ | L | 1B ₀ ⁽⁴⁾ | L |
| H | L | ↑ | H | 1B ₀ ⁽⁴⁾ | H |
| H | H | X or ↑ | X | 1B ₀ ⁽²⁾ | 2B ₀ ⁽²⁾ |

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

| Symbol | Description | Max | Unit |
|------------------------------------|--|-----------------|------|
| VTERM ⁽²⁾ | Terminal Voltage with Respect to GND | -0.5 to +4.6 | V |
| VTERM ⁽³⁾ | Terminal Voltage with Respect to GND | -0.5 to Vcc+0.5 | V |
| TSTG | Storage Temperature | -65 to +150 | °C |
| IOUT | DC Output Current | -50 to +50 | mA |
| I _{IK} | Continuous Clamp Current, V _i < 0 or V _i > Vcc | ±50 | mA |
| I _{OK} | Continuous Clamp Current, V _o < 0 | -50 | mA |
| I _{CC} I _{SS} | Continuous Current through each Vcc or GND | ±100 | mA |

NOTES:

- Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
- Vcc terminals.
- All terminals except Vcc.

CAPACITANCE (TA = +25°C, F = 1.0MHz)

| Symbol | Parameter ⁽¹⁾ | Conditions | Typ. | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|------|
| C _{IN} | Input Capacitance | V _{IN} = 0V | 5 | 7 | pF |
| C _{OUT} | Output Capacitance | V _{OUT} = 0V | 7 | 9 | pF |
| C _{I/O} | I/O Port Capacitance | V _{IN} = 0V | 7 | 9 | pF |

NOTE:

- As applicable to the device type.

FUNCTION TABLES⁽¹⁾

OUTPUT ENABLE

| Inputs | | | Outputs | |
|--------|------------------|------------------|---------|----------|
| CLK | \overline{OEA} | \overline{OEB} | Ax | 1Bx, 2Bx |
| ↑ | H | H | Z | Z |
| ↑ | H | L | Z | Active |
| ↑ | L | H | Active | Z |
| ↑ | L | L | Active | Active |

B-TO-A STORAGE ($\overline{OEA} = L$ AND $\overline{OEB} = H$)

| Inputs | | | | | | Outputs |
|---------|---------|-----|-----|-----|-----|-------------------------------|
| CLKENB1 | CLKENB2 | CLK | SEL | 1Bx | 2Bx | Ax |
| H | X | X | H | X | X | A ₀ ⁽²⁾ |
| X | H | X | L | X | X | A ₀ ⁽²⁾ |
| L | X | ↑ | H | L | X | L |
| L | X | ↑ | H | H | X | H |
| X | L | ↑ | L | X | L | L |
| X | L | ↑ | L | X | H | H |

NOTES:

- H = HIGH Voltage Level
L = LOW Voltage Level
X = Don't Care
Z = High Impedance
↑ = LOW-to-HIGH transition
- Output level before the indicated steady-state input conditions were established.
- Two CLK edges are needed to propagate data.
- Data present at the output of the first register.

PIN DESCRIPTION

| Pin Names | I/O | Description |
|-----------------------------|-----|---|
| Ax(1:12) | I/O | Bidirectional Data Port A. Usually connected to the CPU's Address/Data bus. ⁽¹⁾ |
| 1Bx(1:12) | I/O | Bidirectional Data Port 1B. Usually connected to the even path or even bank of memory. ⁽¹⁾ |
| 2Bx(1:12) | I/O | Bidirectional Data Port 2B. Usually connected to the odd path or odd bank of memory. ⁽¹⁾ |
| CLK | I | Clock Input |
| $\overline{\text{CLKENA1}}$ | I | Clock Enable Input for the A-1B Register. If $\overline{\text{CLKENA1}}$ is LOW during the rising edge of CLK, data will be clocked into register A-1B (Active LOW). |
| $\overline{\text{CLKENA2}}$ | I | Clock Enable Input for the A-2B Register. If $\overline{\text{CLKENA2}}$ is LOW during the rising edge of CLK, data will be clocked into register A-2B (Active LOW). |
| $\overline{\text{CLKEN1B}}$ | I | Clock Enable Input for the 1B-A Register. If $\overline{\text{CLKEN1B}}$ is LOW during the rising edge of CLK, data will be clocked into register 1B-A (Active LOW). |
| $\overline{\text{CLKEN2B}}$ | I | Clock Enable Input for the 2B-A Register. If $\overline{\text{CLKEN2B}}$ is LOW during the rising edge of CLK, data will be clocked into register 2B-A (Active LOW). |
| $\overline{\text{SEL}}$ | I | 1B or 2B Port Selection. When HIGH during the rising edge of CLK, $\overline{\text{SEL}}$ enables data transfer from 1B Port to A Port. When LOW during the rising edge of CLK, $\overline{\text{SEL}}$ enables data transfer from 2B Port to A Port. |
| $\overline{\text{OE A}}$ | I | Synchronous Output Enable for A Port (Active LOW) |
| $\overline{\text{OE B}}$ | I | Synchronous Output Enable for B Port (Active LOW) |

NOTE:

1. These pins have "Bus-Hold". All other pins are standard inputs, outputs, or I/Os.

DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

Operating Condition: TA = -40°C to +85°C

| Symbol | Parameter | Test Conditions | Min. | Typ. ⁽¹⁾ | Max. | Unit |
|-----------------------|--|---|------|---------------------|------|------|
| VIH | Input HIGH Voltage Level | VCC = 2.3V to 2.7V | 1.7 | — | — | V |
| | | VCC = 2.7V to 3.6V | 2 | — | — | |
| VIL | Input LOW Voltage Level | VCC = 2.3V to 2.7V | — | — | 0.7 | V |
| | | VCC = 2.7V to 3.6V | — | — | 0.8 | |
| IiH | Input HIGH Current | VCC = 3.6V | — | — | ±5 | µA |
| IiL | Input LOW Current | VCC = 3.6V | — | — | ±5 | µA |
| IoZH IoZL | High Impedance Output Current (3-State Output pins) | VCC = 3.6V | — | — | ±10 | µA |
| | | Vo = GND | — | — | ±10 | |
| VIK | Clamp Diode Voltage | VCC = 2.3V, IIN = -18mA | — | -0.7 | -1.2 | V |
| VH | Input Hysteresis | VCC = 3.3V | — | 100 | — | mV |
| ICCL ICCH IC CZ | Quiescent Power Supply Current | VCC = 3.6V VIN = GND or VCC | — | 0.1 | 40 | µA |
| ΔIcc | Quiescent Power Supply Current Variation | One input at VCC - 0.6V, other inputs at VCC or GND | — | — | 750 | µA |

NOTE:

1. Typical values are at VCC = 3.3V, +25°C ambient.

BUS-HOLD CHARACTERISTICS

| Symbol | Parameter ⁽¹⁾ | Test Conditions | | Min. | Typ. ⁽²⁾ | Max. | Unit |
|----------------|----------------------------------|------------------------|----------------------------|------|---------------------|------|------|
| IBHH IBHL | Bus-Hold Input Sustain Current | V _{CC} = 3V | V _I = 2V | -75 | — | — | μA |
| | | | V _I = 0.8V | 75 | — | — | |
| IBHH IBHL | Bus-Hold Input Sustain Current | V _{CC} = 2.3V | V _I = 1.7V | -45 | — | — | μA |
| | | | V _I = 0.7V | 45 | — | — | |
| IBHHO IBHLO | Bus-Hold Input Overdrive Current | V _{CC} = 3.6V | V _I = 0 to 3.6V | — | — | ±500 | μA |

NOTES:

1. Pins with Bus-Hold are identified in the pin description.
2. Typical values are at V_{CC} = 3.3V, +25°C ambient.

www.DataSheet4U.com

OUTPUT DRIVE CHARACTERISTICS

| Symbol | Parameter | Test Conditions ⁽¹⁾ | | Min. | Max. | Unit |
|-----------------|---------------------|--------------------------------|--------------------------|-----------------------|------|------|
| V _{OH} | Output HIGH Voltage | V _{CC} = 2.3V to 3.6V | I _{OH} = -0.1mA | V _{CC} - 0.2 | — | V |
| | | V _{CC} = 2.3V | I _{OH} = -6mA | 2 | — | |
| | | V _{CC} = 2.3V | I _{OH} = -12mA | 1.7 | — | |
| | | V _{CC} = 2.7V | | 2.2 | — | |
| | | V _{CC} = 3V | | 2.4 | — | |
| | | V _{CC} = 3V | I _{OH} = -24mA | 2 | — | |
| V _{OL} | Output LOW Voltage | V _{CC} = 2.3V to 3.6V | I _{OL} = 0.1mA | — | 0.2 | V |
| | | V _{CC} = 2.3V | I _{OL} = 6mA | — | 0.4 | |
| | | | I _{OL} = 12mA | — | 0.7 | |
| | | V _{CC} = 2.7V | I _{OL} = 12mA | — | 0.4 | |
| | | V _{CC} = 3V | I _{OL} = 24mA | — | 0.55 | |

NOTE:

1. V_{IH} and V_{IL} must be within the min. or max. range shown in the DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE table for the appropriate V_{CC} range. T_A = -40°C to +85°C.

OPERATING CHARACTERISTICS, T_A = 25°C

| Symbol | Parameter | Test Conditions | V _{CC} = 2.5V ± 0.2V | V _{CC} = 3.3V ± 0.3V | Unit |
|--------|--|---------------------------------|-------------------------------|-------------------------------|------|
| | | | Typical | Typical | |
| CPD | Power Dissipation Capacitance Outputs enabled | C _L = 0pF, f = 10Mhz | 87 | 120 | pF |
| CPD | Power Dissipation Capacitance Outputs disabled | | 80.5 | 118 | |

SWITCHING CHARACTERISTICS⁽¹⁾

| Symbol | Parameter | V _{CC} = 2.5V ± 0.2V | | V _{CC} = 2.7V | | V _{CC} = 3.3V ± 0.3V | | Unit |
|--------------------------------------|---|-------------------------------|------|------------------------|------|-------------------------------|------|------|
| | | Min. | Max. | Min. | Max. | Min. | Max. | |
| f _{MAX} | | 150 | — | 150 | — | 150 | — | MHz |
| t _{PLH} t _{PHL} | Propagation Delay CLK to xBx | 1.5 | 5.9 | — | 5.8 | 1.1 | 5.1 | ns |
| t _{PLH} t _{PHL} | Propagation Delay CLK to Ax | 1.2 | 5.4 | — | 5.4 | 1 | 4.7 | ns |
| t _{PLH} t _{PHL} | Propagation Delay $\overline{\text{SEL}}$ to Ax | 1.4 | 6.2 | — | 6.4 | 1 | 5.5 | ns |
| t _{PZH} t _{PZL} | Output Enable Time CLK to xBx | 1.5 | 7 | — | 6.8 | 1 | 6 | ns |
| t _{PZH} t _{PZL} | Output Enable Time CLK to Ax | 1.5 | 7 | — | 6.8 | 1 | 6 | ns |
| t _{PHZ} t _{PLZ} | Output Disable Time CLK to xBx | 1.9 | 7.2 | — | 6.5 | 1.1 | 5.8 | ns |
| t _{PHZ} t _{PLZ} | Output Disable Time CLK to Ax | 1.9 | 7.2 | — | 6.5 | 1.1 | 5.8 | ns |
| t _{SU} | Set-up Time, Ax data before CLK↑ | 4.1 | — | 3.8 | — | 3.1 | — | ns |
| t _{SU} | Set-up Time, Bx data before CLK↑ | 0.9 | — | 1.2 | — | 0.9 | — | ns |
| t _{SU} | Set-up Time, $\overline{\text{CLKENA1}}$ or $\overline{\text{CLKENA2}}$ before CLK↑ | 3.5 | — | 3.2 | — | 2.7 | — | ns |
| t _{SU} | Set-up Time, $\overline{\text{CLKEN1B}}$ or $\overline{\text{CLKEN2B}}$ before CLK↑ | 3.4 | — | 3 | — | 2.6 | — | ns |
| t _{SU} | Set-up Time, $\overline{\text{OEB}}$ or $\overline{\text{OEA}}$ before CLK↑ | 4.4 | — | 3.9 | — | 3.2 | — | ns |
| t _H | Hold Time, Ax data after CLK↑ | 0 | — | 0 | — | 0.2 | — | ns |
| t _H | Hold Time, Bx data after CLK↑ | 1.4 | — | 1 | — | 1.7 | — | ns |
| t _H | Hold Time, $\overline{\text{CLKENA1}}$ or $\overline{\text{CLKENA2}}$ after CLK↑ | 0 | — | 0.1 | — | 0.3 | — | ns |
| t _H | Hold Time, $\overline{\text{CLKEN1B}}$ or $\overline{\text{CLKEN2B}}$ after CLK↑ | 0 | — | 0 | — | 0.6 | — | ns |
| t _H | Hold Time, $\overline{\text{OEB}}$ or $\overline{\text{OEA}}$ after CLK↑ | 0 | — | 0 | — | 0.1 | — | ns |
| t _w | Pulse Width, CLK HIGH or LOW | 3.3 | — | 3.3 | — | 3.3 | — | ns |
| t _{SK(0)} | Output Skew ⁽²⁾ | — | — | — | — | — | 500 | ps |

NOTES:


1. See TEST CIRCUITS AND WAVEFORMS. T_A = - 40°C to + 85°C.
2. Skew between any two outputs of the same package and switching in the same direction.

TEST CIRCUITS AND WAVEFORMS

TEST CONDITIONS

| Symbol | V _{CC} ⁽¹⁾ =3.3V±0.3V | V _{CC} ⁽¹⁾ =2.7V | V _{CC} ⁽²⁾ =2.5V±0.2V | Unit |
|-------------------|---|--------------------------------------|---|------|
| V _{LOAD} | 6 | 6 | 2 x V _{CC} | V |
| V _{IH} | 2.7 | 2.7 | V _{CC} | V |
| V _T | 1.5 | 1.5 | V _{CC} / 2 | V |
| V _{LZ} | 300 | 300 | 150 | mV |
| V _{HZ} | 300 | 300 | 150 | mV |
| C _L | 50 | 50 | 30 | pF |

www.DataSheet4U.com



Test Circuit for All Outputs

DEFINITIONS:


C_L = Load capacitance: includes jig and probe capacitance.
R_T = Termination resistance: should be equal to Z_{OUT} of the Pulse Generator.

NOTES:

1. Pulse Generator for All Pulses: Rate ≤ 1.0MHz; t_r ≤ 2.5ns; t_r ≤ 2.5ns.
2. Pulse Generator for All Pulses: Rate ≤ 1.0MHz; t_r ≤ 2ns; t_r ≤ 2ns.

SWITCH POSITION

| Test | Switch |
|---|-------------------|
| Open Drain Disable Low Enable Low | V _{LOAD} |
| Disable High Enable High | GND |
| All Other Tests | Open |




$$tsk(x) = |t_{PLH2} - t_{PLH1}| \text{ or } |t_{PHL2} - t_{PHL1}|$$


Output Skew - tsk(x)

NOTES:

1. For tsk(o) OUTPUT1 and OUTPUT2 are any two outputs.
2. For tsk(b) OUTPUT1 and OUTPUT2 are in the same bank.




Propagation Delay



Enable and Disable Times


NOTE:

1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH.




ALVC Link

Set-up, Hold, and Release Times



Pulse Width

ORDERING INFORMATION



www.DataSheet4U.com



CORPORATE HEADQUARTERS
 2975 Stender Way
 Santa Clara, CA 95054

for SALES:
 800-345-7015 or 408-727-6116
 fax: 408-492-8674
 www.idt.com

for Tech Support:
 logichelp@idt.com
 (408) 654-6459