


**HEXFET® Power MOSFET**

- Ultra Low Gate Charge
- Reduced Gate Drive Requirement
- Enhanced 30V V<sub>GS</sub> Rating
- Isolated Package
- High Voltage Isolation= 2.5KVrms ⑤
- Sink to Lead Creepage Dist.= 4.8mm
- Repetitive Avalanche Rated




**V<sub>DSS</sub> = 500V**  
**R<sub>DS(on)</sub> = 0.85Ω**  
**I<sub>D</sub> = 4.5A**

**Description**

This new series of Low Charge HEXFETs achieve significantly lower gate charge over conventional MOSFETs. Utilizing advanced HEXFET technology, the device improvements allow for reduced gate drive requirements, faster switching speeds and increased total system savings. These device improvements combined with the proven ruggedness and reliability that are characteristic of HEXFETs offer the designer a new standard in power transistors for switching applications.

The TO-220 Fullpak eliminates the need for additional insulating hardware. The moulding compound used provides a high isolation capability and low thermal resistance between the tab and external heatsink.

**TO-220 FULLPAK****Absolute Maximum Ratings**

	Parameter	Max.	Units
I <sub>D</sub> @ T <sub>C</sub> = 25°C	Continuous Drain Current, V <sub>GS</sub> @ 10 V	4.5	
I <sub>D</sub> @ T <sub>C</sub> = 100°C	Continuous Drain Current, V <sub>GS</sub> @ 10 V	2.9	A
I <sub>DM</sub>	Pulsed Drain Current ①	18	
P <sub>D</sub> @ T <sub>C</sub> = 25°C	Power Dissipation	40	W
	Linear Derating Factor	0.32	W/°C
V <sub>GS</sub>	Gate-to-Source Voltage	±30	V
E <sub>AS</sub>	Single Pulse Avalanche Energy ②	300	mJ
I <sub>AR</sub>	Avalanche Current ①	4.5	A
E <sub>AR</sub>	Repetitive Avalanche Energy ①	4.0	mJ
dv/dt	Peak Diode Recovery dv/dt ③	3.5	V/ns
T <sub>J</sub>	Operating Junction and	-55 to +150	
T <sub>STG</sub>	Storage Temperature Range		°C
	Soldering Temperature, for 10 seconds	300 (1.6mm from case)	
	Mounting Torque, 6-32 or M3 screw	10 lbf.in (1.1 N·m)	

**Thermal Resistance**

	Parameter	Min.	Typ.	Max.	Units
R <sub>θJC</sub>	Junction-to-Case	—	—	3.1	°C/W
R <sub>θJA</sub>	Junction-to-Ambient	—	—	65	°C/W

**Electrical Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	500	—	—	V	$V_{\text{GS}}=0\text{V}$ , $I_D=250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$	Breakdown Voltage Temp. Coefficient	—	0.63	—	$\text{V}^\circ\text{C}$	Reference to $25^\circ\text{C}$ , $I_D=1\text{mA}$
$R_{\text{DS(on)}}$	Static Drain-to-Source On-Resistance	—	—	0.85	$\Omega$	$V_{\text{GS}}=10\text{V}$ , $I_D=2.7\text{A}$ ④
$V_{\text{GS(th)}}$	Gate Threshold Voltage	2.0	—	4.0	V	$V_{\text{DS}}=V_{\text{GS}}$ , $I_D=250\mu\text{A}$
$g_{\text{fs}}$	Forward Transconductance	4.0	—	—	S	$V_{\text{DS}}=50\text{V}$ , $I_D=4.8\text{A}$ ④
$I_{\text{DSS}}$	Drain-to-Source Leakage Current	—	—	25	$\mu\text{A}$	$V_{\text{DS}}=500\text{V}$ , $V_{\text{GS}}=0\text{V}$
		—	—	250		$V_{\text{DS}}=400\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=125^\circ\text{C}$
$I_{\text{GSS}}$	Gate-to-Source Forward Leakage	—	—	100	nA	$V_{\text{GS}}=20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	-100		$V_{\text{GS}}=-20\text{V}$
$Q_g$	Total Gate Charge	—	—	39		$I_D=8.0\text{A}$
$Q_{gs}$	Gate-to-Source Charge	—	—	10	nC	$V_{\text{DS}}=400\text{V}$
$Q_{gd}$	Gate-to-Drain ("Miller") Charge	—	—	19		$V_{\text{GS}}=10\text{V}$ See Fig. 6 and 13 ④
$t_{\text{d(on)}}$	Turn-On Delay Time	—	12	—		$V_{\text{DD}}=250\text{V}$
$t_r$	Rise Time	—	25	—	ns	$I_D=8.0\text{A}$
$t_{\text{d(off)}}$	Turn-Off Delay Time	—	27	—		$R_G=9.1\Omega$
$t_f$	Fall Time	—	19	—		$R_D=30\Omega$ See Figure 10 ④
$L_D$	Internal Drain Inductance	—	4.5	—	nH	Between lead, 6 mm (0.25in.) from package and center of die contact
$L_S$	Internal Source Inductance	—	7.5	—		
$C_{\text{ISs}}$	Input Capacitance	—	1100	—	pF	$V_{\text{GS}}=0\text{V}$
$C_{\text{OSS}}$	Output Capacitance	—	170	—		$V_{\text{DS}}=25\text{V}$
$C_{\text{rss}}$	Reverse Transfer Capacitance	—	18	—		$f=1.0\text{MHz}$ See Figure 5
C	Drain to Sink Capacitance	—	12	—	pF	$f=1.0\text{MHz}$

**Source-Drain Ratings and Characteristics**

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
$I_S$	Continuous Source Current (Body Diode)	—	—	4.5	A	MOSFET symbol showing the integral reverse p-n junction diode.
$I_{\text{SM}}$	Pulsed Source Current (Body Diode) ①	—	—	18		
$V_{\text{SD}}$	Diode Forward Voltage	—	—	2.0	V	$T_J=25^\circ\text{C}$ , $I_S=4.5\text{A}$ , $V_{\text{GS}}=0\text{V}$ ④
$t_{rr}$	Reverse Recovery Time	—	490	740	ns	$T_J=25^\circ\text{C}$ , $I_f=8.0\text{A}$
$Q_{rr}$	Reverse Recovery Charge	—	3.0	4.5	$\mu\text{C}$	$dI/dt=100\text{A}/\mu\text{s}$ ④
$t_{\text{on}}$	Forward Turn-On Time	Intrinsic turn-on time is negligible (turn-on is dominated by $L_s+L_d$ )				

Notes:

① Repetitive rating; pulse width limited by max. junction temperature (See Figure 11)

③  $I_{\text{SD}} \leq 8.0\text{A}$ ,  $dI/dt \leq 100\text{A}/\mu\text{s}$ ,  $V_{\text{DD}} \leq V_{(\text{BR})\text{DSS}}$ ,  $T_J \leq 150^\circ\text{C}$ ⑤  $t=60\text{s}$ ,  $f=60\text{Hz}$ ②  $V_{\text{DD}}=50\text{V}$ , starting  $T_J=25^\circ\text{C}$ ,  $L=26\text{mH}$   
 $R_G=25\Omega$ ,  $I_{AS}=4.5\text{A}$  (See Figure 12)④ Pulse width  $\leq 300\ \mu\text{s}$ ; duty cycle  $\leq 2\%$ .




Fig 1. Typical Output Characteristics,  
 $T_C = 25^\circ\text{C}$




Fig 2. Typical Output Characteristics,  
 $T_C = 150^\circ\text{C}$




Fig 3. Typical Transfer Characteristics







Fig 4. Normalized On-Resistance  
Vs. Temperature




**Fig 5.** Typical Capacitance Vs.  
Drain-to-Source Voltage



**Fig 6.** Typical Gate Charge Vs.  
Gate-to-Source Voltage



**Fig 7.** Typical Source-Drain Diode  
Forward Voltage



**Fig 8.** Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms







Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




**Fig 12a.** Unclamped Inductive Test Circuit




**Fig 12b.** Unclamped Inductive Waveforms



**Fig 12c.** Maximum Avalanche Energy Vs. Drain Current



**Fig 13a.** Basic Gate Charge Waveform





**Fig 13b.** Gate Charge Test Circuit

## Appendix A

### Peak Diode Recovery dv/dt Test Circuit


**Fig 14.** For N-Channel HEXFETs



## Package Outline

### TO-220 FullPak Outline


Dimensions are shown in millimeters (inches)



## Part Marking Information

### TO-220 FULL-PAK

EXAMPLE: THIS IS AN IRFI840G WITH ASSEMBLY LOT CODE E401



Printed on Signet recycled offset:  
made from 50% recycled waste paper, including  
10% de-inked, post-consumer waste.



**International**  
**IOR** Rectifier

WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, Tel: (310) 322-3331, Twx: 4720403  
EUROPEAN HEADQUARTERS: Hurst Green, Oxted, Surrey RH8 9BB England, Tel: (0863) 713215, Twx: 95219

IR CANADA: 101 Bentley St., Markham, Ontario L3R 3L1, Tel: (416) 475-1897. IR GERMANY: Saalburgstrasse 157, D-6380 Bad Homburg, Tel: 6172-37066. IR ITALY: Via Liguria 49 10071 Borgaro, Torino, Tel: (011) 470 1484. IR FAR EAST: K&H Building, 30-4 Nishikobukuro 3-Chome, Toshima-ku, Tokyo 171 Japan, Tel: (03) 983 0641. IR SOUTHEAST ASIA: 190 Middle Road, #X-10-01 Fortune Centre, Singapore 0718, Tel: (65) 336 3922.

Sales Offices, Agents and Distributors in Major Cities Throughout the World.