

isc N-Channel Mosfet Transistor

IRF621

• FEATURES

- Low $R_{DS(on)}$
- V_{GS} Rated at $\pm 20V$
- Silicon Gate for Fast Switching Speed
- Rugged
- Low Drive Requirements

• DESCRIPTION



- Designed for high speed applications, such as switching power supplies , AC and DC motor controls,relay and solenoid drivers and other pulse.

• ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	150	V
V_{GS}	Gate-Source Voltage-Continuous	± 20	V
I_D	Drain Current-Continuous	5	A
I_{DM}	Drain Current-Single Plused	20	A
P_D	Total Dissipation @ $T_C=25^{\circ}C$	40	W
T_j	Max. Operating Junction Temperature	-55~150	$^{\circ}C$
T_{stg}	Storage Temperature	-55~150	$^{\circ}C$

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance,Junction to Case	3.12	$^{\circ}C/W$
$R_{th\ j-a}$	Thermal Resistance,Junction to Ambient	80	$^{\circ}C/W$



isc N-Channel Mosfet Transistor**IRF621****ELECTRICAL CHARACTERISTICS** $T_c=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0$; $I_D=0.25\text{mA}$	150		V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$; $I_D=0.25\text{mA}$	2	4	V
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10\text{V}$; $I_D=2.5\text{A}$		0.8	Ω
I_{GSS}	Gate-Body Leakage Current	$V_{GS}=\pm 20\text{V}$; $V_{DS}=0$		± 500	nA
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=150\text{V}$; $V_{GS}=0$		250	μA
V_{SD}	Forward On-Voltage	$I_S=5\text{A}$; $V_{GS}=0$		1.8	V
C_{iss}	Input Capacitance	$V_{DS}=25\text{V}$, $V_{GS}=0\text{V}$, $F=1.0\text{MHz}$		600	pF
C_{oss}	Output Capacitance			300	pF
C_{rss}	Reverse Transfer Capacitance			80	pF

• SWITCHING CHARACTERISTICS ($T_c=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$T_d(on)$	Turn-on Delay Time	$V_{DD}=100\text{V}$, $I_D=5.0\text{A}$ $V_{GS}=10\text{V}$, $R_{GEN}=9.1\Omega$ $R_{GS}=9.1\Omega$			40	ns
T_r	Rise Time				60	ns
$T_d(off)$	Turn-off Delay Time				100	ns
T_f	Fall Time				60	ns