



18.8×10.6×15.3

J Z C - 3 2 F



CH0054068-2000



R2133923



on Pending

Features

- 5A, 10A switching capabilities.
- SPSTNO and SPDT(B-M) configurations.
- Subminiature, standard PC layout.
- Sealed & Unsealed types available.

Contact Data

Contact Arrangement	1A, 1C	
Contact Material	Silver Alloy	
Contact Rating (resistive)	1A(0.2W):3A/250VAC,30VDC; 1A(0.45W):5A/250VAC,30VDC;10A/125VAC	
	1C:3A,5A/250VAC, 30VDC	
Max. Switching Power	150W 1250VA	
Max. Switching Voltage	30VDC 277VAC	Max. Switching Current:10A
Contact Resistance or Voltage drop	≤100mΩ	Item 3.12 of IEC255-7
Operation life	Electrical	10 ⁵ Item 3.30 of IEC255-7
	Mechanical	10 ⁷ Item 3.31 of IEC255-7

Coil Parameter

Coil voltage VDC		Coil resistance Ω±10%		Pickup voltage VDC(max) (75%of rated voltage)	release voltage VDC(min) (5% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
Rated	Max.							
3	3.9	45	20	2.25	0.15	0.20/0.45	≤8	≤5
5	6.5	125	56	3.75	0.25			
6	7.8	180	80	4.50	0.20			
9	11.7	405	180	6.75	0.45			
12	15.6	720	320	9.00	0.60			
18	23.4	1620	720	13.5	0.90			
24	31.2	2880	1280	18.0	1.20			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition

Insulation Resistance	100MΩ min (at 500VDC)	Item 7 of IEC255-5
Dielectric Strength		
Between contacts	50Hz 1000V	Item 6 of IEC255-5
Between contact and coil	50Hz 2500V 4000V	Item 6 of IEC255-5
Shock resistance	100m/s ² 11ms	IEC68-2-27 Test Ea method 1
Vibration resistance	10~55Hz double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	10N	IEC68-2-21 Test Ua1
Solderability	230℃ ±2℃ 10 ±0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-40~70℃	
Relative Humidity	95% (at 35℃)	IEC68-2-3Test Ca
Mass	6g	

Qualification inspection:

Perform the qualification test as specified in the table IV of IEC255-19-1 and minimum sample size 24.

