

KAB-DF14-20S-1.25C-0500RK



Displaykabel, einseitig offen m

Hirose DF14-20S-1.25C Steckverbinder

it

DISCLAIMER:

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

1. Funktionale Beschreibung

Dieser Kabelsatz bietet Ihnen die Möglichkeit, schnell und einfach eine Verbindung zwischen einem Display mit einem Steckverbinder der DF14 Serie und einem beliebigen Grafikboardsteckverbinder herzustellen. Wir liefern Ihnen ein Twisted Pair Rundkabel mit 20 montierten Kontakten und einem passenden Leergehäuse, die zweite Seite des Kabels ist unbearbeitet. Sie können dann ganz einfach nach Ihren Kabelplänen die Kontakte in die entsprechenden Gehäusekammern bestücken und so eine optimale Funktion und Zuweisung der Paare zu den Signalstrukturen erzielen. Dieses Kabel ist besonders für Muster und Kleinstserien geeignet.

Technische Daten:

- Seite 1: montierte Crimpkontakte Typ DF14-2628SCF für Steckverbinder DF14-20S-1.25C, ungesteckt anbei
- Seite 2: unbearbeitet, offen
- Rundkabel, DCY 10 x 2 x 0,09 mm², L = 500 mm

Vorteile auf einen Blick

- sofort ab Lager verfügbar
- individuell bestückbar
- andere Längen kurzfristig lieferbar
- abgeschirmt
- mit Twisted Pair
- für LVDS und DVI geeignet
- **dieses Kabel wird ungesteckt mit beiliegender Buchse angeliefert! (Siehe Abb. 3 und 4)**

Die Konfektionierung dieser Leitung sowie die Herstellung des gesamten anschlussfertigen Kabels bieten wir Ihnen gerne auch als Mustermenge an. Bitte kontaktieren Sie uns. Wir machen Ihnen gerne ein unverbindliches Angebot.

Dieses Kabel passt zu folgenden Stiftheuten:

DF14-20P-1.25H, MSB240420, MSB240420-E, P240420, GT123-20P-H16, GT123-20S-CS, 3804-F20N-06R, CWY20G-A0D1T

Dieses Kabel passt zu folgenden Displays:

AA150XN01, AA150XN02, G150XG01, G150XG02, G150XG03, LB150X02, LB150X06, LC150X01, LC150X01-A3, LC150X01-SL01, LC150X02, LC150X02-A4, LC150X02-

DISCLAIMER:

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

Not checked!!! For internal use only!!!

TL01, LC151X01-C3, LC171W03, LC171W03-A4, LC171W03-C4, LC230W01, LC230W01-A2, LC260W01, LC260W01-A5K1, LM150X08, LQ150X1LG45, LQ150X1LG55, LQ150X1LGB1, LQ150X1LGN2, LQ150X1LGN2A, LQ150X1LGN2E, LQ150X1LW71N, LQ150X1LW72, LTM150XH, LTM150XH-L01, LTM150XO-L01, M150XN07, M170XW01, NL10276BC30-17, NL10276BC30-18, NL10276BC30-18C, NL10276BC30-32D, NL10276BC30-33D, NL128102AC31-02, NL12876BC26-25, T140VN01, T201VN02V0, T-51863D150J-FW-A-AA, T-51863D150J-FW-A-AB, T-51863D150J-FW-A-AD, T-51863D150J-FW-A-AE, G150X1, G121SN01, G121SN01V1, G121SN01V2, G121SN01V3, G150XG03V2, G121SN01V4, NL10276BC30-33D, LQ150X1LW71N, LQ150X1LG82, G150XG02V1, T-55519D150J-LW-A-AAN, G121SN01-V4, NL10276BC30-34D, HT15X15, G121NX01, G150XG01 V3, LQ150X1LG91

2. Bilder



3. Abmessung

Größe: 500,0 (L) (in mm)

DISCLAIMER:

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support



DATASHEET

KAB-DF14-20S-1.25C-0500RK

Not checked!!! For internal use only!!!

4. Temperaturbereiche

Betriebstemperatur: -20°C bis 85°C

Lagertemperatur: -40°C bis 85°C

5. Gewicht

Gewicht ohne Verpackung: 35,1 g

Gewicht mit Verpackung: 28,9 g

ES&S Solutions GmbH · Gewerbering 2 · 41751 Viersen · GERMANY · www.esskabel.de
fon: +49 (0)2162 - 266 18 0 · fax: +49 (0)2162 - 266 18 88 · info@esskabel.de

REV: 1.00 4/5
Copyright© 2013










DISCLAIMER:

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-DF14-20S-1.25C-0500RK

DATASHEET

6. Adern Farbcode

Div. Farbcode nach internationalen Normen / different color codes of international rules						
wire	twisted pair	Farbe	Color	DIN VDE 47100	OKI	flat cable untwisted
1	TP1	weiss	white			
2		braun	brown			
3	TP2	grün	green			
4		gelb	yellow			
5	TP3	grau	grey			
6		rosa	pink			
7	TP4	blau	blue			
8		rot	red			
9	TP5	schwarz	black			
10		lila	magenta			
11	TP6	...	...			
12		...	...			
13	TP7					
14						
15	TP8					
16						
17	TP9					
18						
19	TP10					
20						
21	TP11					
22						
23	TP12					
24						
25	TP13					
26						
27	TP14					
28						
29	TP15					
30						
31	TP16					
32						

DISCLAIMER:

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support