

# KAB-SET-FI-S20S-DF14-XXS-0500RK



LVDS Display cable set

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

## 1. Functional description

This cable set allows a quick and easy connection between a display with a STM connector FI-S20S and any graphics board connector of the Hirose series DF14, 20- or 30-pin.

We supply a 20-pin round cable with a connector FI-S20S-TW on side 1. Two Hirose connectors DF14-20S-1.25C, DF14-30S-1.25C for the second side are included. The cable has mounted crimp contacts on both sides and will be supplied unplugged.

The connectors can easily be assembled according to your cable layouts to achieve an optimum function and allocation of the pairs to the signal structures.

The cable is especially suited for samples, the prototype construction or very small series.

Technical Data:

- side 1: FI-S20S
- side 2: DF14-20S-1.25C, DF14-30S-1.25C
- both sides unplugged, 20-pin, highly flexible round cable, twin stranded, UL2560, AWG28, shielded, length = 500 mm

Pros:

- small quantities available from stock
- individual assembling on both sides possible
- different lengths available on short notice
- shielded
- with twisted pair
- suitable for LVDS
- this cable will be supplied unplugged on both sides including matching connector housings!

This cable fits to the following pin headers:

DF14-20P-1.25H, MSB240420, MSB240420-E, P240420, GT123-20P-H16, GT123-20S-CS, 3804-F20N-06R, CWY20G-A0D1T

The following displays will be supported:

AA150XN01, AA150XN02, G150XG01, G150XG02, G150XG03, LB150X02, LB150X06, LC150X01, LC150X01-A3, LC150X01-SL01, LC150X02, LC150X02-A4, LC150X02-TL01, LC151X01-C3, LC171W03, LC171W03-A4, LC171W03-C4, LC230W01, LC230W01-A2, LC260W01, LC260W01-A5K1, LM150X08, LQ150X1LG45,

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

LQ150X1LG55, LQ150X1LGB1, LQ150X1LGN2, LQ150X1LGN2A, LQ150X1LGN2E, LQ150X1LW71N, LQ150X1LW72, LTM150XH, LTM150XH-L01, LTM150XO-L01, M150XN07, M170XW01, NL10276BC30-17, NL10276BC30-18, NL10276BC30-18C, NL10276BC30-32D, NL10276BC30-33D, NL128102AC31-02, NL12876BC26-25, T140VN01, T201VN02V0, T-51863D150J-FW-A-AA, T-51863D150J-FW-A-AB, T-51863D150J-FW-A-AD, T-51863D150J-FW-A-AE, G150X1, G121SN01, G121SN01V1, G121SN01V2, G121SN01V3, G150XG03V2, G121SN01V4, NL10276BC30-33D, LQ150X1LW71N, LQ150X1LG82, G150XG02V1, T-55519D150J-LW-A-AAN, G121SN01-V4, NL10276BC30-34D, HT15X15, G121NX01, G150XG01 V3, LQ150X1LG91

## 2. Pictures



## 3. Dimension

Size: 500.0 (l) (in mm)

## 4. Temperature ranges

Operating temperature: -20°C to 85°C

Storage temperature: -40°C to 85°C

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support



DATASHEET

**KAB-SET-FI-S20S-DF14-XXS-0500RK**

## 5. Weight

Weight without packaging: 32.1 g

Weight with packaging: 40.1 g

KAB-SET-FI-S20S-DF14-XXS-0500RK

**ES&S Solutions GmbH** · Gewerbering 2 · 41751 Viersen · GERMANY · [www.esskabel.de](http://www.esskabel.de)  
fon: +49 (0)2162 - 266 18 0 · fax: +49 (0)2162 - 266 18 88 · [info@esskabel.de](mailto:info@esskabel.de)

REV: 1.00 4/4  
Copyright© 2012

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

DATASHEET