

PRELIMINARY SPEC

Part Number: KAD1-1010SYC28

Super Bright Yellow

Features





- *PLCC-4 PACKAGE.
- *SINGLE COLOR.
- *HIGH LUMINANCE.
- *HIGH POWER, OPERATING CURRENT @350mA.
- *SUITABLE FOR ALL SMT ASSEMBLY METHODS.
- *PACKAGE : 300PCS / REEL.
- *MOISTURE SENSITIVITY LEVEL : LEVEL 4.
- *RoHS COMPLIANT.



Applications

- traffic signaling.
- backlighting (illuminated advertising , general lighting).
- interior and exterior automotive lighting.
- substitution of micro incandescent lamps.
- portable light source (e.g. bicycle flashlight).
- signal and symbol luminaire for orientation.
- marker lights (e.g. steps, exit ways, etc).
- decorative and entertainment lighting.
- indoor and outdoor commercial and residential architectural lighting.

Package Dimensions



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.25 (0.01") unless otherwise noted.
3. Specifications are subject to change without notice.
4. The device has a single mounting surface. The device must be mounted according to the specifications



Selection Guide

Part No.	Dice	Lens Type	luminous Intensity [2] Iv(cd)@ 350 mA		Φ_v (lm) [2] @350mA		Viewing Angle [1]
			Min.	Typ.	Min.	Typ.	
KAD1-1010SYC28	SUPER BRIGHT YELLOW (InGaAlP)	WATER CLEAR	40	80	20	29.33	20°

Notes:

1. $\theta 1/2$ is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.
2. Luminous intensity/ luminous Flux: +/-15%.

Absolute Maximum Ratings at T_A=25°C

Parameter	Symbol	Value	Unit
Power dissipation	P _t	1.2	W
Reverse Voltage	V _R	5	V
Junction temperature	T _J	110	°C
Operating Temperature	T _{op}	-40 To +85	°C
Storage Temperature	T _{stg}	-40 To +85	°C
DC Forward Current[1]	I _F	350	mA
Peak Forward Current [2]	I _{FM}	500	mA
Thermal resistance [1]	R _{th}	80	°C/W

Notes:

1. Results from mounting on PC board FR4(pad size≥100mm²), mounted on pc board-metal core PCB is recommend for lowest thermal Resistance.
2. 1/10 Duty Cycle, 0.1ms Pulse Width.


Electrical / Optical Characteristics at T_A=25°C

Parameter	Symbol	Value	Unit
Wavelength at peak emission I _F =350mA [Typ.]	λ_{peak}	590	nm
Dominant Wavelength I _F =350mA [Typ.]	λ_{dom} [1]	588	nm
Spectral bandwidth at 50% $\Phi_{REL MAX}$ I _F =350mA [Typ.]	$\Delta\lambda$	20	nm
Forward Voltage I _F =350mA [Min.]	V _F [2]	2.0	V
Forward Voltage I _F =350mA [Typ.]		2.5	
Forward Voltage I _F =350mA [Max.]		3.0	
Reverse Current (V _R =5V) [Max.]	I _R	10	μA
Temperature coefficient of λ_{peak} I _F =350mA, -10°C≤T≤100°C [Typ.]	TC λ_{peak}	0.15	nm/°C
Temperature coefficient of λ_{dom} I _F =350mA, -10°C≤T≤100°C [Typ.]	TC λ_{dom}	0.13	nm/°C
Temperature coefficient of V _F I _F =350mA, -10°C≤T≤100°C [Typ.]	TC _V	-2.0	mV/°C


Notes:

1. Wavelength: +/-1nm.
2. Forward Voltage: +/-0.1V.


KAD1-1010SYC28




RELATIVE INTENSITY Vs. WAVELENGTH




SPATIAL DISTRIBUTION




FORWARD CURRENT Vs. FORWARD VOLTAGE



LUMINOUS INTENSITY Vs. FORWARD CURRENT



FORWARD CURRENT Vs. AMBIENT TEMPERATURE



LUMINOUS INTENSITY Vs. AMBIENT TEMPERATURE

