

● Description

The KMOC3041、KMOC3042、KMOC3043 series consist of a GaAs infrared emitting diode optically coupled to a monolithic silicon detector performing the function of a zero voltage crossing bilateral TRIAC driver. They are designed for use with a TRIAC in the interface of logic systems to equipment powered from 115 VAC lines, such as solid-state relays, industrial controls, motors, solenoids and consumer appliances, etc.


● Features

1. Pb free and RoHS compliant.
2. 400V peak blocking voltage.
3. Simplifies logic control of 115 VAC power.
4. Zero voltage crossing.
5. Isolation voltage between input and output (Viso : 5300Vms).
6. MSL class 1
7. Agency Approvals :
 - UL Approved (No. E169586): UL1577
 - c-UL Approved (No. E169586)
 - VDE Approved (No. 101347): DIN EN60747-5-5
 - CQC Approved: GB8898-2011, GB4943.1-2011

● Applications

- Solenoid/Valve controls
- Lighting controls
- Static power switches
- AC motor drives
- Temperature controls
- E.M contactors
- AC motor contactors
- Solid state relay
- Programmable controllers

● Schematic




1. Anode
2. Cathode
3. NC
4. Main terminal
6. Main terminal


● Outside Dimension

Unit : mm


1. Dual-in-line type.




2. Surface mount type.



3. Long creepage distance type.




4. Long creepage distance for surface mount type.



TOLERANCE : ±0.2mm

● Device Marking



Notes :

cosmo

3041、3042、3043

YWW Y : Year code / W : Week code

Absolute Maximum Ratings

(Ta=25°C)

| Parameter | | Symbol | Rating | Unit |
|----------------------------------|--|--------------|-------------|------------|
| Input | Forward current | I_F | 50 | mA |
| | Peak forward current | I_{FM} | 1 | A |
| | Reverse voltage | V_R | 6 | V |
| | Power dissipation | P_D | 70 | mW |
| Output | Off-state output terminal voltage | V_{DRM} | 400 | V_{PEAK} |
| | On-state R.M.S. current | $I_{T(RMS)}$ | 100 | mA |
| | Peak repetitive surge current (PW=10ms.DC 10%) | I_{TSM} | 1 | A |
| | Power dissipation | P_D | 300 | mW |
| Total power dissipation | | P_{tot} | 330 | mW |
| Isolation voltage 1 minute | | V_{iso} | 5300 | Vrms |
| Operating temperature | | T_{opr} | -40 to +115 | °C |
| Storage temperature | | T_{stg} | -50 to +125 | °C |
| Soldering temperature 10 seconds | | T_{sol} | 260 | °C |

Electro-optical Characteristics

(Ta=25°C)

| Parameter | | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|--------------------------|---|------------|---|--------------------|-----------|------|------------|
| Input | Forward voltage | V_F | $I_F=10mA$ | - | 1.2 | 1.4 | V |
| | Reverse current | I_R | $V_R=4V$ | - | - | 10 | μA |
| Output | Peak blocking current | I_{DRM} | V_{DRM} Rated | - | - | 500 | nA |
| | On-state voltage | V_{TM} | $I_{TM}=100mA$ | - | 1.8 | 3 | V |
| Transfer characteristics | Holding current | I_H | | - | 0.1 | - | mA |
| | Critical rate of rise of off-state voltage | dv/dt | $V_{DRM}=(1/\sqrt{2}) \cdot \text{Rated}$ | 1000 | - | - | V/ μs |
| | Inhibit voltage (MT1-MT2 voltage above which device will not trigger) | V_{INH} | $I_F = \text{Rated } I_{FT}$ | - | 10 | 20 | V |
| | Leakage in inhibited state | I_{DRM2} | $I_F = \text{Rated } I_{FT}, \text{ Rated } V_{DRM}, \text{ Off State}$ | - | - | 500 | μA |
| | Isolation resistance | R_{iso} | DC500V | 5×10^{10} | 10^{11} | - | Ω |
| | Minimum trigger current | I_{FT} | Main terminal | - | - | 15 | mA |
| | | | terminal voltage=3V | - | - | 10 | mA |
| | | | | - | - | 5 | mA |

Static dv/dt Test Circuit




Fig.1 Forward Current vs. Ambient Temperature




Fig.2 Diode Power Dissipation vs. Ambient Temperature




Fig.3 On-state R.M.S. Current vs. Ambient Temperature




Fig.4 Total Power Dissipation vs. Ambient Temperature




Fig.5 Peak Forward Current vs. Duty Ratio




Fig.6 Forward Current vs. Forward Voltage




Fig.7 On-state Characteristics




Fig.8 Inhibit Voltage vs. Ambient Temperature




Fig.9 Leakage with LED off vs. Ambient Temperature




Fig.10 I_DRM2, Leakage in Inhibited State vs. Ambient Temperature





Fig.11 Trigger Current vs. Ambient Temperature




● Recommended Soldering Conditions

(a) Infrared reflow soldering :

- Peak reflow soldering : 260°C or below (package surface temperature)
- Time of peak reflow temperature : 10 sec
- Time of temperature higher than 230°C : 30-60 sec
- Time to preheat temperature from 180~190°C : 60-120 sec
- Time(s) of reflow : Two
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

Recommended Temperature Profile of Infrared Reflow



(b) Wave soldering :

- Temperature : 260°C or below (molten solder temperature)
- Time : 10 seconds or less
- Preheating conditions : 120°C or below (package surface temperature)
- Time(s) of reflow : One
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

(c) Cautions :

- Fluxes : Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.
- Avoid shorting between portion of frame and leads.

● Numbering System

KMOC3041 X (Y)

KMOC3042 X (Y)

KMOC3043 X (Y)

Notes :

KMOC3041 / KMOC3042 / KMOC3043 = Part No.


X = Lead form option (blank 、 S 、 H 、 L)

Y = Tape and reel option (TL 、 TR 、 TLD 、 TRU)


| Option | Description | Packing quantity |
|---------|--|---------------------|
| S (TL) | surface mount type package + TL tape & reel option | 1000 units per reel |
| S (TR) | surface mount type package + TR tape & reel option | 1000 units per reel |
| L (TLD) | long creepage distance for surface mount type package + TLD tape & reel option | 1000 units per reel |
| L (TRU) | long creepage distance for surface mount type package + TRU tape & reel option | 1000 units per reel |

● Recommended Pad Layout for Surface Mount Lead Form

1. Surface mount type.







2. Long creepage distance for surface mount type.







Unit : mm

● SMD Carrier Tape & Reel



● L Carrier Tape & Reel



● Application Notice

The statements regarding the suitability of products for certain types of applications are based on cosmo's knowledge of general applications of cosmo products. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to verify the specifications are suitable for use in a particular application. Customers are solely responsible for all aspects of their own product design or applications. The parameters provided in the datasheet may vary in different applications and performance may vary over time. All operating parameters (including typical parameters) must be validated by customer's technical experts for different applications. cosmo assumes no liability for customer' product design or applications. Product specifications do not expand or otherwise change cosmo's terms and conditions of purchase, including but not limited to the warranty expressed therein.

When using cosmo products, please comply with safety standards and instructions. cosmo has no liability and responsibility to the damage caused by improper use of the instructions specified in the specifications.

cosmo products are designed for use in general electronic equipment such as telecommunications, office automation equipments, personal computers, test and measurement equipments, consumer electronics, industrial control, instrumentation, audio, video.

cosmo devices shall not be used in equipment that requires higher level of reliability and safety, such as nuclear power control equipment, telecommunication equipment(trunk lines), space application, medical and other life supporting equipments, and equipment for aircraft, military, automotive or any other application that can cause human injury or death.

cosmo reserves the right to change the specifications, data, characteristics, structure, materials and other contents at any time without notice. Please contact cosmo to obtain the latest specification.

cosmo disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.