

KS54AHCT 266
KS74AHCT
Quad Exclusive-NOR Gates
with Open-Drain Outputs
FEATURES



- Function, pin-out, speed and drive compatibility with 54/74ALS logic family
- Low power consumption characteristic of CMOS
- High-Drive-Current outputs:
 $I_{OL} = 8 \text{ mA} @ V_{OL} = 0.5 \text{ V}$
- Inputs and outputs interface directly with TTL, NMOS and CMOS devices
- Wide operating voltage range: 4.5V to 5.5V
- Characterized for operation over industrial and military temperature ranges:
 KS74AHCT: -40°C to $+85^{\circ}\text{C}$
 KS54AHCT: -55°C to $+125^{\circ}\text{C}$
- Package options include plastic "small outline" packages, standard plastic and ceramic 300-mil DIPs

DESCRIPTION

These devices contain four independent exclusive-NOR gates with open-drain outputs. Using a suitable pull-up resistor, these outputs may be connected to other open-drain outputs to implement wired-AND functions.

These devices provide speeds and drive capability equivalent to their ALSTTL counterparts and yet maintain CMOS power levels. The input and output voltage levels allow direct interface with TTL, NMOS and CMOS devices without any external components.

All inputs and outputs are protected from damage due to static discharge by internal diode clamps to V_{CC} and ground.

PIN CONFIGURATION

LOGIC DIAGRAM

FUNCTION TABLE

Inputs		Output
A	B	Y
L	L	H
L	H	L
H	L	L
H	H	H


SAMSUNG SEMICONDUCTOR

KS54AHCT 266

KS74AHCT

Quad Exclusive-NOR Gates with Open-Drain Outputs

Absolute Maximum Ratings*

Supply Voltage Range V_{CC} -0.5V to +7V
 DC Input Diode Current, I_{IK}
 ($V_I < -0.5V$ or $V_I > V_{CC} + 0.5V$) ± 20 mA
 DC Output Diode Current, I_{OK}
 ($V_O < -0.5V$ or $V_O > V_{CC} + 0.5V$) ± 20 mA
 Continuous Output Current Per Pin, I_O
 ($-0.5V < V_O < V_{CC} + 0.5V$) ± 35 mA
 Continuous Current Through
 V_{CC} or GND pins ± 125 mA
 Storage Temperature Range, T_{stg} -65°C to +150°C
 Power Dissipation Per Package, P_d † 500 mW

* Absolute Maximum Ratings are those values beyond which permanent damage to the device may occur. These are stress ratings only and functional operation of the device at or beyond them is not implied. Long exposure to these conditions may affect device reliability.

† Power Dissipation temperature derating:

Plastic Package (N): -12mW/°C from 65°C to 85°C
 Ceramic Package (J): -12mW/°C from 100°C to 125°C

Recommended Operating Conditions

Supply Voltage, V_{CC} 4.5V to 5.5V
 DC Input & Output Voltages*, V_{IN} , V_{OUT} .. 0V to V_{CC}
 Operating Temperature
 Range KS74AHCT: -40°C to +85°C
 KS54AHCT: -55°C to +125°C
 Input Rise & Fall Times, t_r , t_f Max 500 ns

* Unused inputs must always be tied to an appropriate logic voltage level (either V_{CC} or GND)

DC ELECTRICAL CHARACTERISTICS ($V_{CC}=5V \pm 10\%$ Unless Otherwise Specified)





Characteristic	Symbol	Test Conditions	T _a = 25°C		KS74AHCT	KS54AHCT	Unit
					T _a = − 40°C to + 85°C	T _a = − 55°C to + 125°C	
			Typ	Guaranteed Limits			
Minimum High-Level Input Voltage	V _{IH}			2.0	2.0	2.0	V
Maximum Low-Level Input Voltage	V _{IL}			0.8	0.8	0.8	V
Maximum Low-Level Output Voltage	V _{OL}	V _{IN} =V _{IH} or V _{IL} I _O =20μA I _O =4mA I _O =8mA	0	0.1 0.26 0.39	0.1 0.33 0.5	0.1 0.4	V
Maximum Input Current	I _{IN}	V _{IN} =V _{CC} or GND		±0.1	±1.0	±1.0	μA
Maximum Output Leakage Current	I _{OZ}	V _{IN} =V _{IH} or V _{IL} V _{OUT} =V _{CC}		±0.5	±5.0	±10.0	μA
Maximum Quiescent Supply Current	I _{CC}	V _{IN} =V _{CC} or GND I _{OUT} =0μA		2.0	20.0	40.0	μA
Additional Worst Case Supply Current	ΔI _{CC}	per input pin V _I =2.4V other Inputs: at V _{CC} or GND I _{OUT} =0μA		2.7	2.9	3.0	mA

AC ELECTRICAL CHARACTERISTICS (Input t_r , $t_f \leq 2$ ns), AHCT266

Characteristic	Symbol	Conditions†	$T_A = 25^\circ\text{C}$ $V_{CC} = 5.0V$	KS74AHCT $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$ $V_{CC} = 5.0V \pm 10\%$		KS54AHCT $T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$ $V_{CC} = 5.0V \pm 10\%$		Unit
			Typ	Min	Max	Min	Max	
Propagation Delay	t_{PLH}	$C_L=50\text{pF}$	19		29		35	ns
	t_{PHL}	$R_L=1\text{k}\Omega$	11		18		22	
Input Capacitance	C_{IN}		5					pF
Power Dissipation Capacitance*	C_{PD}	(per gate)	15					pF

* C_{PD} determines the no-load dynamic power dissipation: $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$.

† For AC switching test circuits and timing waveforms see section 2.

PACKAGE DIMENSIONS*T-90-20***1. PLASTIC PACKAGES****14-Pin Plastic DIP Units: mm****16-Pin Plastic DIP Units: mm****20-Pin Plastic DIP Units: mm****24-Pin Plastic DIP Units: mm**

7

**SAMSUNG SEMICONDUCTOR**





1675

A-04

781

PACKAGE DIMENSIONS

T-90-20






SAMSUNG SEMICONDUCTOR

1676




A-05

PACKAGE DIMENSIONS




T-90-20

2. CERAMIC PACKAGES**14-Pin Ceramic DIP Units: mm**




DIM	Millimeters	
	Min	Max
A	—	5.08
B	0.38	0.58
B ₁	1.40	1.78
C	0.20	0.38
D	18.16	19.56
E	8.10	7.49
E ₁	7.62	10.03
F	2.54	
L	3.18	4.19
Q	0.51	1.02
S	1.91	2.29

16-Pin Ceramic DIP Units: mm

DIM	Millimeters	
	Min	Max
A	—	5.08
B	0.38	0.58
B ₁	1.40	1.78
C	0.20	0.38
D	19.05	19.94
E	8.10	7.49
E ₁	7.62	10.03
F	2.54	
L	3.18	4.19
Q	0.51	1.02
S	0.51	1.14

20-Pin Ceramic DIP Units: mm

DIM	Millimeters	
	Min	Max
A	4.06	5.08
B	0.38	0.53
B ₁	1.14	1.52
C	0.20	0.38
D	25.78	26.93
E	8.10	8.60
E ₁	7.77	7.98
F	2.54	
L	3.73	4.01
Q	0.38	0.89
S	0.51	1.14

24-Pin Ceramic DIP Units: mm

DIM	Millimeters	
	Min	Max
A	4.06	5.08
B	0.38	0.53
B ₁	1.14	1.52
C	0.20	0.38
D	31.50	32.84
E	7.24	7.75
E ₁	7.77	7.98
F	2.54	
L	3.73	4.01
Q	0.508	1.778
S	1.85	1.93



SAMSUNG SEMICONDUCTOR

1677

A-06

783