



**KS54AHCT 843/844**  
**KS74AHCT**
**9-Bit Bus Interface D-Type**  
**Latches with 3-State Outputs**

T-46-07-05

**FEATURES**

- Bus-Structured Pinout
- Provide Extra Bus Driving Latches Necessary for Wider Address/Data Paths or Buses with Parity
- Power-Up High Impedance
- Function, pin-out, speed and drive compatibility with 54/74ALS logic family
- Low power consumption characteristic of CMOS
- 3-State outputs with high drive current ( $I_{OL} = 24 \text{ mA}$  @  $V_{OL} = 0.5\text{V}$ ) for direct bus interface
- Inputs and outputs interface directly with TTL, NMOS and CMOS devices
- Wide operating voltage range: 4.5V to 5.5V
- Characterized for operation over industrial and military temperature ranges:  
KS74AHCT:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$   
KS54AHCT:  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$
- Package options include plastic "small outline" packages, standard plastic and ceramic 300-mil DIPs

**PIN CONFIGURATIONS**

**DESCRIPTION**

These 9-bit bus interface latches feature three-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are suitable for implementing wider buffer registers, I/O ports, bidirectional bus drivers and working registers.

The nine latches are transparent D-type. The '843 has noninverting data (D) inputs and the '844 has inverting  $\bar{D}$  inputs.

A buffered output control ( $\overline{OC}$ ) input can be used to place the nine outputs in either a normal logic state (high or low levels) or a high-impedance state. The high-impedance state and increased drive provide the capability to drive the bus lines in a bus-organized system without need for interface or pull-up components.

The output control ( $\overline{OC}$ ) does not affect the internal operation of the flip-flops. Old data can be retained or new data can be entered while the outputs are off.

These devices provide speeds and drive capability equivalent to their ALSTTL counterparts and yet maintain CMOS power levels. The input and output voltage levels allow direct interface with TTL, NMOS and CMOS devices without any external components.

All inputs and outputs are protected from damage due to static discharge by internal diode clamps to  $V_{CC}$  and ground.

**FUNCTION TABLES**

**'843**

| INPUTS |     |                 |   |   | OUTPUT |
|--------|-----|-----------------|---|---|--------|
| PRE    | CLR | $\overline{OC}$ | C | D | Q      |
| L      | X   | L               | X | X | H      |
| H      | L   | L               | X | X | L      |
| H      | H   | L               | H | L | L      |
| H      | H   | L               | H | H | H      |
| H      | H   | L               | L | X | $Q_0$  |
| X      | X   | H               | X | X | Z      |

**'844**

| INPUTS |     |                 |   |           | OUTPUT |
|--------|-----|-----------------|---|-----------|--------|
| PRE    | CLR | $\overline{OC}$ | C | $\bar{D}$ | Q      |
| L      | X   | L               | X | X         | H      |
| H      | L   | L               | X | X         | L      |
| H      | H   | L               | H | L         | H      |
| H      | H   | L               | H | H         | L      |
| H      | H   | L               | L | X         | $Q_0$  |
| X      | X   | H               | X | X         | Z      |





SAMSUNG SEMICONDUCTOR

**KS54AHCT 843/844**  
**KS74AHCT**
**9-Bit Bus Interface D-Type**  
**Latches with 3-State Outputs**

T-46-07-05

## LOGIC DIAGRAMS



**KS54AHCT 843/844**  
**KS74AHCT**
**9-Bit Bus Interface D-Type**  
**Latches with 3-State Outputs**

T-46-07-05

**Absolute Maximum Ratings\***

Supply Voltage Range  $V_{CC}$ , ..... -0.5V to +7V  
 DC Input Diode Current,  $I_{IK}$   
 ( $V_I < -0.5V$  or  $V_I > V_{CC} + 0.5V$ ) .....  $\pm 20$  mA  
 DC Output Diode Current,  $I_{OK}$   
 ( $V_O < -0.5V$  or  $V_O > V_{CC} + 0.5V$ ) .....  $\pm 20$  mA  
 Continuous Output Current Per Pin,  $I_O$   
 ( $-0.5V < V_O < V_{CC} + 0.5V$ ) .....  $\pm 70$  mA  
 Continuous Current Through  
 $V_{CC}$  or GND pins .....  $\pm 250$  mA  
 Storage Temperature Range,  $T_{stg}$  ..... -65°C to +150°C  
 Power Dissipation Per Package,  $P_d$  ..... 500 mW

\* Absolute Maximum Ratings are those values beyond which permanent damage to the device may occur. These are stress ratings only and functional operation of the device at or beyond them is not implied. Long exposure to these conditions may affect device reliability.

† Power Dissipation temperature derating:

Plastic Package (N): -12mW/°C from 65°C to 85°C  
 Ceramic Package (J): -12mW/°C from 100°C to 125°C

**Recommended Operating Conditions**

Supply Voltage,  $V_{CC}$  ..... 4.5V to 5.5V  
 DC Input & Output Voltages\*,  $V_{IN}$ ,  $V_{OUT}$  .. 0V to  $V_{CC}$   
 Operating Temperature  
 Range KS74AHCT: -40°C to +85°C  
 KS54AHCT: -55°C to +125°C

 Input Rise & Fall Times,  $t_r$ ,  $t_f$  ..... Max 500 ns

\* Unused inputs must always be tied to an appropriate logic voltage level (either  $V_{CC}$  or GND)

**DC ELECTRICAL CHARACTERISTICS** ( $V_{CC}=5V \pm 10\%$  Unless Otherwise Specified)

| Characteristic                       | Symbol           | Test Conditions                                                                                                             | T <sub>a</sub> = 25°C  |                              | KS74AHCT                     | KS54AHCT                    |  | Unit |
|--------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------|------------------------------|-----------------------------|--|------|
|                                      |                  |                                                                                                                             | Typ                    | Guaranteed Limits            |                              |                             |  |      |
| Minimum High-Level Input Voltage     | V <sub>IH</sub>  |                                                                                                                             |                        | 2.0                          | 2.0                          | 2.0                         |  | V    |
| Maximum Low-Level Input Voltage      | V <sub>IL</sub>  |                                                                                                                             |                        | 0.8                          | 0.8                          | 0.8                         |  | V    |
| Minimum High-Level Output Voltage    | V <sub>OH</sub>  | V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>O</sub> = -20μA<br>I <sub>O</sub> = -6mA                      | V <sub>CC</sub><br>4.2 | V <sub>CC</sub> -0.1<br>3.98 | V <sub>CC</sub> -0.1<br>3.84 | V <sub>CC</sub> -0.1<br>3.7 |  | V    |
| Maximum Low-Level Output Voltage     | V <sub>OL</sub>  | V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>O</sub> =20μA<br>I <sub>O</sub> =12mA<br>I <sub>O</sub> =24mA | 0                      | 0.1<br>0.26<br>0.39          | 0.1<br>0.33<br>0.5           | 0.1<br>0.4                  |  | V    |
| Maximum Input Current                | I <sub>IN</sub>  | V <sub>IN</sub> =V <sub>CC</sub> or GND                                                                                     |                        | ±0.1                         | ±1.0                         | ±1.0                        |  | μA   |
| Maximum 3-State Leakage Current      | I <sub>OZ</sub>  | Output Enable<br>=V <sub>IH</sub><br>V <sub>OUT</sub> =V <sub>CC</sub> or GND                                               |                        | ±0.5                         | ±5.0                         | ±10.0                       |  | μA   |
| Maximum Quiescent Supply Current     | I <sub>CC</sub>  | V <sub>IN</sub> =V <sub>CC</sub> or GND<br>I <sub>OUT</sub> =0μA                                                            |                        | 8.0                          | 80.0                         | 160.0                       |  | μA   |
| Additional Worst Case Supply Current | ΔI <sub>CC</sub> | per input pin<br>V <sub>I</sub> =2.4V<br>other Inputs:<br>at V <sub>CC</sub> or GND<br>I <sub>OUT</sub> =0μA                |                        | 2.7                          | 2.9                          | 3.0                         |  | mA   |

**KS54AHCT 843/844**  
**KS74AHCT**
**9-Bit Bus Interface D-Type**  
**Latches with 3-State Outputs**

T-46-07-05





**AC ELECTRICAL CHARACTERISTICS** (Input  $t_r, t_f \leq 2$  ns), AHCT843, AHCT844

| Characteristic                                | Symbol    | Conditions†                                                            | $T_a = 25^\circ\text{C}$<br>$V_{CC} = 5.0\text{V}$ | KS74AHCT<br>$T_a = -40^\circ\text{C to } +85^\circ\text{C}$<br>$V_{CC} = 5.0\text{V} \pm 10\%$ |          | KS54AHCT<br>$T_a = -55^\circ\text{C to } +125^\circ\text{C}$<br>$V_{CC} = 5.0\text{V} \pm 10\%$ |          | Unit |
|-----------------------------------------------|-----------|------------------------------------------------------------------------|----------------------------------------------------|------------------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------|----------|------|
|                                               |           |                                                                        | Typ                                                | Min                                                                                            | Max      | Min                                                                                             | Max      |      |
| Propagation Delay,<br>Data to Q               | $t_{PLH}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 13<br>16                                           |                                                                                                | 18<br>23 |                                                                                                 | 22<br>28 | ns   |
|                                               | $t_{PHL}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 13<br>16                                           |                                                                                                | 18<br>23 |                                                                                                 | 22<br>28 |      |
| Propagation Delay,<br>C to any Q              | $t_{PLH}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 16<br>19                                           |                                                                                                | 26<br>31 |                                                                                                 | 31<br>37 | ns   |
|                                               | $t_{PHL}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 16<br>19                                           |                                                                                                | 26<br>31 |                                                                                                 | 31<br>37 |      |
| Propagation Delay,<br>PRE to Q                | $t_{PLH}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 17<br>20                                           |                                                                                                | 27<br>32 |                                                                                                 | 32<br>38 | ns   |
| Propagation Delay,<br>CLR to Q                | $t_{PHL}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 17<br>20                                           |                                                                                                | 27<br>32 |                                                                                                 | 32<br>38 | ns   |
| Output Enable Time,<br>OC to any Q            | $t_{PZL}$ | $C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$                            | 11<br>14                                           |                                                                                                | 18<br>23 |                                                                                                 | 22<br>28 | ns   |
|                                               | $t_{PZL}$ | $R_L = 1\text{k}\Omega$<br>$C_L = 50\text{pF}$<br>$C_L = 150\text{pF}$ | 11<br>14                                           |                                                                                                | 18<br>23 |                                                                                                 | 22<br>28 |      |
| Output Disable Time,<br>OC to any Q           | $t_{PHZ}$ | $R_L = 1\text{k}\Omega$                                                | 13                                                 |                                                                                                | 18       |                                                                                                 | 22       | ns   |
|                                               | $t_{PLZ}$ | $C_L = 50\text{pF}$                                                    | 13                                                 |                                                                                                | 18       |                                                                                                 | 22       |      |
| Pulse Width,<br>C High                        | $t_w$     |                                                                        | 12                                                 | 20                                                                                             |          | 25                                                                                              |          | ns   |
| Setup Time,<br>Data before C↓                 | $t_{SU}$  |                                                                        | 8                                                  | 10                                                                                             |          | 12                                                                                              |          | ns   |
| Hold Time,<br>Data after C↓                   | $t_h$     |                                                                        | 3                                                  | 5                                                                                              |          | 7                                                                                               |          | ns   |
| Input Capacitance                             | $C_{IN}$  |                                                                        | 5                                                  |                                                                                                |          |                                                                                                 |          | pF   |
| Output Capacitance                            | $C_{OUT}$ | Output Disabled                                                        | 10                                                 |                                                                                                |          |                                                                                                 |          | pF   |
| Power Dissipation<br>Capacitance* (per stage) | $C_{PD}$  | $\overline{OC} = V_{CC}$                                               | 5                                                  |                                                                                                |          |                                                                                                 |          | pF   |
|                                               |           | $\overline{OC} = \text{GND}$                                           | 30                                                 |                                                                                                |          |                                                                                                 |          |      |

\*  $C_{PD}$  determines the no-load dynamic power dissipation:  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ .

† For AC switching test circuits and timing waveforms see section 2.



**PACKAGE DIMENSIONS***T-90-20***1. PLASTIC PACKAGES****14-Pin Plastic DIP Units: mm****16-Pin Plastic DIP Units: mm****20-Pin Plastic DIP Units: mm****24-Pin Plastic DIP Units: mm**

7

**SAMSUNG SEMICONDUCTOR**





1675

A-04

781




**PACKAGE DIMENSIONS**

*T-90-20*






**PACKAGE DIMENSIONS**




T-90-20

**2. CERAMIC PACKAGES****14-Pin Ceramic DIP Units: mm**




| DIM            | Millimeters |       |
|----------------|-------------|-------|
|                | Min         | Max   |
| A              | —           | 5.08  |
| B              | 0.38        | 0.58  |
| B <sub>1</sub> | 1.40        | 1.78  |
| C              | 0.20        | 0.38  |
| D              | 18.16       | 19.56 |
| E              | 8.10        | 7.49  |
| E <sub>1</sub> | 7.62        | 10.03 |
| F              | 2.54        |       |
| L              | 3.18        | 4.19  |
| Q              | 0.51        | 1.02  |
| S              | 1.91        | 2.29  |

**16-Pin Ceramic DIP Units: mm**

| DIM            | Millimeters |       |
|----------------|-------------|-------|
|                | Min         | Max   |
| A              | —           | 5.08  |
| B              | 0.38        | 0.58  |
| B <sub>1</sub> | 1.40        | 1.78  |
| C              | 0.20        | 0.38  |
| D              | 19.05       | 19.94 |
| E              | 8.10        | 7.49  |
| E <sub>1</sub> | 7.62        | 10.03 |
| F              | 2.54        |       |
| L              | 3.18        | 4.19  |
| Q              | 0.51        | 1.02  |
| S              | 0.51        | 1.14  |

**20-Pin Ceramic DIP Units: mm**

| DIM            | Millimeters |       |
|----------------|-------------|-------|
|                | Min         | Max   |
| A              | 4.06        | 5.08  |
| B              | 0.38        | 0.53  |
| B <sub>1</sub> | 1.14        | 1.52  |
| C              | 0.20        | 0.38  |
| D              | 25.78       | 26.93 |
| E              | 8.10        | 8.60  |
| E <sub>1</sub> | 7.77        | 7.98  |
| F              | 2.54        |       |
| L              | 3.73        | 4.01  |
| Q              | 0.38        | 0.89  |
| S              | 0.51        | 1.14  |

**24-Pin Ceramic DIP Units: mm**

| DIM            | Millimeters |       |
|----------------|-------------|-------|
|                | Min         | Max   |
| A              | 4.06        | 5.08  |
| B              | 0.38        | 0.53  |
| B <sub>1</sub> | 1.14        | 1.52  |
| C              | 0.20        | 0.38  |
| D              | 31.50       | 32.84 |
| E              | 7.24        | 7.75  |
| E <sub>1</sub> | 7.77        | 7.98  |
| F              | 2.54        |       |
| L              | 3.73        | 4.01  |
| Q              | 0.508       | 1.778 |
| S              | 1.85        | 1.93  |



SAMSUNG SEMICONDUCTOR

1677

A-06

783