



L93H - C S - DC12V

Relay Type: \_\_\_\_\_

Contact Form:- 1C \_\_\_\_\_

Type of Sealing:- S: Sealed Type \_\_\_\_\_

Coil Voltage:- 12~24VDC \_\_\_\_\_

Features	Dimension L * W * H (mm)	32.2 * 27.5 * 27			
	Terminal Type	PCB			
	Weight	28 gm Approximately			
Contact Data	Contact Form/Resistance	1C / 100mΩ Max. @ 1A / 6VDC			
	Contact Material	Ag Alloy			
	Contact Capacity	40A @250VAC / 40A @28VDC			
	Coil Voltage ( DC)	12 ~ 24 VDC			
Coil Data	Coil Power Consumption	0.9W			
		Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage (VDC)	Drop Out Voltage (VDC)
	Coil Specification	12 VDC	155	75%	10%
		24 VDC	640	75%	10%
General Data	Dielectric Strength	1200 VAC (Between Open Contacts)			
		1500 VAC ( Between Coil & Contacts)			
	Insulation Resistance	100MΩ 500VDC			
	Electrical Life	1 x 10 <sup>5</sup>			
	Mechanical Life	1 x 10 <sup>6</sup>			
	Operating Temperature	- 25 °C ~ + 55°C			
Mounting Diagram					
Application	Television, Stereo, Microwave, Air Conditioner, Refrigerator, Iron, Electrical Boiler, Satellite Receiver, etc.				