



200 mA low dropout LDO



DFN 2x2 6L
Wettable Flanks



SOT23 5L

Maturity status link

[LDH40](#)

Features

- AEC-Q100 grade 1 qualified
- Operating temperature range: $-40\text{ }^{\circ}\text{C} < T_J < +150\text{ }^{\circ}\text{C}$
- Input voltage from 3.3 V to 40 V
- Dropout voltage (700 mV typ. at 200 mA load)
- Low ground current (2 μA typ. at no load)
- ADJ from 1.2 V to 22 V
- Output voltage tolerance: 0.5% at 25 $^{\circ}\text{C}$
- 200 mA guaranteed output current
- Power Good
- Logic-controlled electronic shutdown
- Internal current limit
- Thermal shutdown
- Output active discharge function
- Package options:
 - DFN 2x2 6L WF for automotive grade
 - SOT23 5L and DFN 6L for industrial

Applications

- EV powertrain
- Body control modules
- Always-on battery connected application
- Infotainment and instrument cluster
- ADAS

Description

LDH40 is a high accuracy voltage regulator designed to be directly connected to a car battery in automotive applications, or a generic battery connected in industrial applications. Extended input voltage up to 40 V makes the device capable to support a load dump transient, typical in automotive systems. Ultra-low quiescent current at light load increases the battery operation lifetime in always-on-standby systems.


The device is stabilized with a small ceramic capacitor on the input and output.

An enable logic control function puts the LDH40 in shutdown mode allowing a total current consumption lower than 0.3 μA . Thermal protection is also included.

The device is available in automotive grade in a very small footprint DFN package with wettable flank, allowing the maximum space saving in the PCB (printed circuit board) design and AOI (automated optical inspection).

1 Diagram

Figure 1. Block diagram adjustable version



2 Pin configuration

Figure 2. Pin connection (top view)




Table 1. Pin description DFN 2x2 6L


DFN 2x2-6L	Symbol	Function
1	V_{IN}	Input voltage
2	EN	Enable pin logic input: set V_{EN} = high to turn ON the device V_{EN} = low to turn off the device Do not leave this pin floating
3	GND	Ground
4	PG	Power Good
5	ADJ	ADJ: adjust pin on the adjustable version Connect to resistor divider to set the output voltage
6	V_{OUT}	Output voltage
Exp PAD	Exposed pad	Connect to GND

Table 2. Pin description SOT 23 5L

SOT23 5L	Symbol	Function
1	V_{OUT}	Output voltage
2	GND	Ground
3	ADJ	Adjust pin
4	EN	Enable pin logic input: set V_{EN} = high to turn ON the device V_{EN} = low to turn OFF the device Do not leave this pin floating
5	V_{IN}	Input voltage

3 Typical application circuit

Figure 3. Typical application for the adjustable version



Note: PG pin only for DFN version.

Table 3. Typical application components

Symbol	Value	Description	Note
C_{IN}	1 μ F	Input capacitor	Ceramic type
C_{OUT}	From 1 to 200 μ F	Output capacitor	Ceramic type
ESR	From 5 m Ω to 10 Ω		
R_1	2 M Ω max	Output voltage side resistor	
R_2	2 M Ω max	Ground side resistor	
R_{PG}	From 10 K Ω to 2 M Ω		

Including component derating.

4 Absolute maximum ratings

Stressing the device above the ratings listed in Table 4. Absolute maximum ratings may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those indicated in the operating sections of these specifications is not implied. Exposure to absolute maximum rating conditions may affect device reliability.

Table 4. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{IN}	Input voltage	-0.3 to +42	V
V_{OUT}	Output voltage	-0.3 to +25	V
V_{ADJ}	Adjust voltage	-0.3 to +3	V
V_{EN}	Enable input voltage	-0.3 to V_{IN}	V
V_{PG}	Power Good	-0.3 to +25	V
I_{OUT}	Output current	Internally limited	A
T_{STG}	Storage temperature range	-40 to +150	°C
T_{JOP}	Operating junction temperature range	-40 to +150	°C

Table 5. Thermal data

Symbol	Parameter	DFN 2x2 6L	SOT23 5L	Unit
R_{thJA}	Thermal resistance junction-ambient ⁽¹⁾	62	200	°C/W

1. R_{thJA} for DFN6 is based on a 4-layer JEDEC PCB (2S2P) test board with two thermal vias.

Table 6. ESD performance

Symbol	Parameter	Test conditions	Value	Unit
ESD	ESD protection voltage	HBM	2	kV
		CDM on corner pins of DFN WF	750	V
		CDM inner pins of DFN WF	500	V
		CDM industrial packages	500	V

5 Electrical characteristics

$V_{IN} = V_{OUT(NOM)} + 1\text{ V}$ or 3.3 V (whichever is greater); $I_{OUT} = 1\text{ mA}$; $C_{IN} = 4.7\text{ }\mu\text{F}$, $C_{OUT} = 10\text{ }\mu\text{F}$; $V_{EN} = V_{IN}$; typical values are at $T_J = 25\text{ }^\circ\text{C}$; min/max values are at $-40\text{ }^\circ\text{C} \leq T_J \leq 150\text{ }^\circ\text{C}$, unless otherwise specified.

Table 7. Electrical characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IN}	Operating input voltage		$V_{OUT} + V_{DROP}$		40	V
$V_{IN(UVLO)}$	Undervoltage lockout	Rising edge		2.6	3.0	V
		Hysteresis		0.35		
V_{REF}	Reference voltage for adjustable devices	$T_J = 25\text{ }^\circ\text{C}$		1.2		V
V_{OUT}	Output voltage accuracy	All versions, $T_J = 25\text{ }^\circ\text{C}$	-0.5		+0.5	%
		$V_{OUT(NOM)} + 1\text{ V} \leq V_{IN} \leq 32\text{ V}$; $I_{OUT} = 1\text{ mA}$ to 200 mA ; $-40\text{ }^\circ\text{C} \leq T_J \leq 150\text{ }^\circ\text{C}$	-2.5		+2.5	%
ΔV_{OUT-IN}	V_{IN} static regulation	$V_{OUT(NOM)} + 1\text{ V} \leq V_{IN} \leq 32\text{ V}$		0.01	0.03	% / V
$\Delta V_{OUT-LOAD}$	Static load regulation	$I_{OUT} = 1\text{ mA}$ to 200 mA		3.0		mV
V_{DROP}	Dropout voltage	$I_{OUT} = 200\text{ mA}$; $V_{OUT} = 97\%$ of $V_{OUT(NOM)}$		700	1000	mV
I_{LIM}	Output current limit	$V_{OUT} = 90\%$ $V_{OUT(NOM)}$	350	650	1000	mA
I_{ADJ}	ADJ pin operating current			0.1	0.5	μA
I_Q	Quiescent current during regulation	V_{IN} from 3.3 V to 40 V no load		2	5	μA
		10 mA		50		
		100 mA		150		
		200 mA		200	500	
I_{Q_OFF}	Standby current	$V_{IN} = 32\text{ V}$		0.3	1.2	μA
V_{EN}	Enable input logic low	V_{IN} up to 40 V			0.7	V
	Enable input logic high	V_{IN} up to 40 V	2.0			
I_{EN}	Enable pin input current	V_{EN} from 2 V to 40 V		0.01	0.1	μA
V_{PG_OK}	Power Good output threshold, rising		93		98	%Vout ⁽¹⁾
V_{PG_NOK}	Power Good output threshold, falling		86		95	
	Power Good hysteresis		30	70		mV
V_{PG_L}	Power Good output voltage low	$I_{SINK_MAX} = 6\text{ mA}$, open drain output			0.4	V
T_{ON}	Turn on time	From assertion of V_{EN} to $0.98\% \cdot V_{OUT}$. $V_{OUT(NOM)} \cdot V_{OUT(NOM)} = 1.0\text{ V}$		1		ms
SVR Supply voltage rejection		$V_{IN} = 5\text{ V} \pm V_{RIPPLE}$ $V_{RIPPLE} = 0.2\text{ V}$; freq = 1 kHz $I_{OUT} = 10\text{ mA}$; $V_{OUT(NOM)} = 1.2\text{ V}$		65		dB
		$V_{IN} = 15\text{ V} \pm V_{RIPPLE}$ $V_{RIPPLE} = 0.2\text{ V}$; freq = 1 kHz ; $I_{OUT} = 10\text{ mA}$; $V_{OUT(NOM)} = 1.2\text{ V}$		70		dB

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
	e_{N-ADJ} output noise voltage	$V_{IN} = 3\text{ V}$; $V_{OUT(NOM)} = 1.2\text{ V}$; 10 Hz to 100 kHz, $I_{OUT} = 1\text{ mA}$		100		μV_{RMS}
		$V_{IN} = 12\text{ V}$; $V_{OUT(NOM)} = 3.3\text{ V}$; 10 Hz to 100 kHz, $I_{OUT} = 1\text{ mA}$		300		μV_{RMS}
R_{ON}	Output voltage discharge MOSFET			150		Ω
T_{SHDN}	Thermal shutdown			175		$^{\circ}\text{C}$
	Hysteresis			20		

1. The Power Good threshold is calculated as a percentage of the measured V_{out}

6 Application information

6.1 V_{IN} pin voltage requirements

The LDH40 is a low-dropout linear voltage regulator equipped with a low-RDS-(on) P-channel MOSFET used as a pass-element. The device internal circuit is able to start with an input voltage as low as 3.3 V.

6.2 Output discharge function

LDH40 embeds an open drain that allows the output capacitor to discharge, at about 150 Ohm, when the enable pin goes to zero.

6.3 Current limitation

The LDH40 is protected against short circuits on the output. The load current is limited to the maximum value of I_{LIM} when V_{OUT} is equal to 90% of its nominal value.


6.4 Thermal protection

Thermal protection acts when the junction temperature reaches 175 °C typical. At this point, the output of the IC shuts down. As soon as the junction temperature falls below the thermal hysteresis value, the device starts working again.

In order to calculate the maximum power that the device can dissipate, keeping the junction temperature below the maximum operating value, the following formula is used:

$$P_{DMAX} = (150 - T_{AMB}) / R_{thJA} \quad (1)$$

Figure 4. Derating curve



6.5 Input and output capacitors

The LDH40 requires external capacitors to assure the regulator control loop stability.

Any good quality ceramic capacitor can be used, however the X5R and the X7R are suggested since they guarantee a very stable combination of capacitance and ESR overtemperature.

It is recommended to put the input/output capacitors as close as possible to the relative pins. The LDH40 requires a V_{IN} capacitor with a minimum value of 1 μF minimum.

The control loop is designed to be stable with any good quality output ceramic capacitor (such as X5R/X7R types) with a minimum value of 1.0 μF and equivalent series resistance in the [5 m Ω to 10 Ω] range. It is important to highlight that the output capacitor must maintain its capacitance and ESR in the stable region over the full operating temperature, load and input voltage ranges, to assure stability. Therefore, capacitance and ESR variations must be taken into account in the design phase to ensure the device works in the expected stability region.

6.6 Power Good output

The LDH40 features a Power Good open drain output. The pin is High-Z when the output voltage is within the valid range or when the device is disabled ($EN = LOW$). The pin is pulled low when the output voltage is below the minimum PG threshold (see V_{PG_OK} V_{PG_NOK} parameters).

7 Typical characteristics

$C_{IN} = 4.7 \mu F$; $C_{OUT} = 10 \mu F$

Figure 5. Output voltage vs. temperature




Figure 6. Line regulation vs. temperature




Figure 7. Load regulation vs. temperature




Figure 8. Enable threshold ON




Figure 9. Enable threshold OFF




Figure 10. Output current limit




Figure 11. Quiescent current vs. input voltage




Figure 12. Quiescent current vs. output current




Figure 13. Quiescent current vs. temperature




Figure 14. Dropout voltage vs. temperature




Figure 15. Load transient $V_{EN}=2V$

$V_{EN}=2V$, $V_{IN}=22V$, I_{OUT} = from 100μA to 200mA and viceversa, $V_{OUT}=18V$, $t_r=t_f=5\mu s$




Figure 16. Load transient $V_{EN}=1V$

$V_{EN}=1V$, $V_{IN}=22V$, I_{OUT} = from 10mA to 200mA and viceversa, $V_{OUT}=18V$, $t_r=t_f=5\mu s$




Figure 17. Load transient

$V_{EN}=1V$, $V_{IN}=22V$, I_{OUT} =from 100mA to 10mA, $V_{OUT}=18V$, $t_r=t_f=5\mu s$




Figure 18. Line transient

$V_{IN}=V_{EN}=2.7V$ to 10V, $t_r=t_f=1\mu s$, $ADJ=V_{OUT}$, $I_{OUT}=1mA$




Figure 19. Turn on time

Turn on/off with enable $V_{IN}=22V$, $V_{OUT}=18V$, V_{EN} =from 0 to 20V, $I_{OUT}=200mA$




Figure 20. Turn on time

$V_{IN}=V_{EN}$ =from 0 to 13V, $V_{OUT}=12V$, $t_{rise}=10\mu s$, $I_{OUT}=200mA$




Figure 21. Spectral noise density vs. frequency

$V_{EN}=1V$, $V_{OUT}=1.2V$, $V_{IN}=3V$




Figure 22. PSRR vs. frequency $V_{IN}=5V$

$V_{EN}=2V$, $V_{OUT}=1.2V$, $V_{IN}=5V$, $V_{ripple}=200mV_{pkpk}$, $I_{load}=1mA$




Figure 23. PSRR vs. frequency $V_{IN} = 19\text{ V}$

$V_{EN}=2\text{V}$ $V_{OUT}=18\text{V}$ $V_{IN}=19\text{V}$ $V_{ripple}=200\text{mV pkpk}$ $I_{load}=1\text{mA}$




Figure 24. Stability plane for $V_{OUT} = 1.2\text{ V}$

$V_{EN} = 2\text{ V}$ V_{in} =from 3V to 40V I_{out} =from 100 μA to 200mA





Figure 25. Stability plane for $V_{OUT} = 18\text{ V}$

$V_{EN} = 2\text{ V}$ V_{in} =from 19V to 40V $V_{OUT}=18\text{V}$, I_{out} =from 100 μA to 200mA



8 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

8.1 DFN6 (2 x 2) package information

Figure 26. DFN6 (2 x 2) package outline





Table 8. DFN6 (2 x 2) mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	0.70	0.75	0.80
A1	0.00		0.05
A3	0.200 REF		
b	0.25	0.30	0.35
D	1.95	2.00	2.05
D1	1.50	1.60	1.70
e	0.65 BSC		
e2	0.25 REF		
E	1.95	2.00	2.05
E1	0.90	1.00	1.10
K		0.25	
L	0.15	0.25	0.35

Figure 27. DFN6 (2 x 2) recommended footprint




8.2 DFN6 (2 x 2) wettable flanks package information

Figure 28. DFN6 (2 x 2) wettable flanks package outline

BOTTOM VIEW



SIDE VIEW



TOP VIEW





Table 9. DFN6 (2 x 2) wettable flanks mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	0.70	0.75	0.80
A1	0.00		0.05
b	0.25	0.30	0.35
D	1.95	2.00	2.05
D2	1.50	1.60	1.70
e	0.65 BSC		
E	1.95	2.00	2.05
E2	0.80	0.90	1.00
L	0.20	0.30	0.40
K	0.25 BSC		
aaa	0.10		
bbb	0.10		
ccc	0.10		
ddd	0.10		

Figure 29. DFN6 (2 x 2) wettable flanks recommended footprint



8.3 DFN6 WF 2D marking information

Figure 30. DFN6 WF 2D marking



Spec	UTL
A	0.2 mm
B	0.2 mm
C	1.6x1.6 (+/-0.125) mm.
D	1.6x1.6 (+/-0.125) mm.

8.4 SOT23-5L package information

Figure 31. SOT23-5L package outline




Table 10. SOT23-5L mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A			1.25
A1	0.04		0.10
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.33		0.41
b1	0.32	0.35	0.38
c	0.15		0.19
c1	0.14	0.15	0.16
D	2.82	2.92	3.02
E	2.60	2.80	3.00
E1	1.50	1.60	1.70
e	0.95 CS		
e1	1.90 BSC		
L	0.30		0.60
Θ	0		8°


Figure 32. SOT23-5L recommended footprint


Figure 33. DFN6 (2x2 mm) tape outline




Figure 34. DFN6 (2x2 mm) reel outline




Figure 35. Pin 1 orientation





Figure 36. DFN6 (2x2 mm) cover tape outline



COVER TAPE WIDTH* (W ±0.1)	CARRIER TAPE WIDTH
5.3, 5.4, 5.5	8
9.2, 9.3, 9.5	12
13.3, 13.5	16
21.0, 21.3	24
25.5	32
37.5	44
49.5	56
81.5	88

NOTES

- 1 THICKNESS : 0.041 – 0.055
- 2 STANDARD LENGTH : 300m or 500m
- 3 TENSILE STRENGTH : >5.0kg/mm sq.
- 4 ELONGATION : >75%
- 5 SURFACE RESISTANCE: 1E+4 TO 9.9E+10 ohms.
SURFACE RESISTIVITY: 1E+5 TO 9.9E+11 ohms/sq.
- 6 PEEL STRENGTH CONFORMS TO EIA SPEC: 20 TO 80g
- 7 RECOMMENDED SHELF LIFE : 2 YEARS
FROM MANUFACTURING DATE
- 8 LUMINOUS TRANSMITTANCE : 87.8%
- 9 HAZE : 28%
- *10 OTHER COVER TAPE WIDTH REFER TO WI4.08-04.

10 Ordering information

Table 11. Order codes

Order code	Package	V _{OUT}	Marking
LDH40PURY ⁽¹⁾ .	DFN6 2x2 wettable flanks	ADJ	2D code
LDH40MR	SOT23 5L	ADJ	H40A
LDH40PUR	DFN6 2x2	ADJ	H4A

1. Automotive part according to AEC-Q100 Grade1

Revision history

Table 12. Document revision history

Date	Revision	Changes
18-Dec-2023	1	Initial release.
05-Mar-2024	2	Updated Table 7 , Figure 11 and Table 11 .
03-Mar-2025	3	Updated Table 11

Contents

1	Diagram	2
2	Pin configuration	3
3	Typical application circuit.....	4
4	Absolute maximum ratings	5
5	Electrical characteristics.....	6
6	Application information.....	8
6.1	V_{IN} pin voltage requirements	8
6.2	Output discharge function	8
6.3	Current limitation	8
6.4	Thermal protection	8
6.5	Input and output capacitors	8
6.6	Power Good output	9
7	Typical characteristics	10
8	Package information.....	14
8.1	DFN6 (2 x 2) package information	14
8.2	DFN6 (2 x 2) wettable flanks package information	16
8.3	DFN6 WF 2D marking information	19
8.4	SOT23-5L package information.....	20
9	DFN6 (2x2 mm) packing information	22
10	Ordering information	25
	Revision history	26

List of tables

Table 1.	Pin description DFN 2x2 6L	3
Table 2.	Pin description SOT 23 5L	3
Table 3.	Typical application components	4
Table 4.	Absolute maximum ratings	5
Table 5.	Thermal data	5
Table 6.	ESD performance	5
Table 7.	Electrical characteristics	6
Table 8.	DFN6 (2 x 2) mechanical data	15
Table 9.	DFN6 (2 x 2) wettable flanks mechanical data	17
Table 10.	SOT23-5L mechanical data	21
Table 11.	Order codes	25
Table 12.	Document revision history	26

List of figures

Figure 1.	Block diagram adjustable version	2
Figure 2.	Pin connection (top view)	3
Figure 3.	Typical application for the adjustable version	4
Figure 4.	Derating curve	8
Figure 5.	Output voltage vs. temperature	10
Figure 6.	Line regulation vs. temperature	10
Figure 7.	Load regulation vs. temperature	10
Figure 8.	Enable threshold ON	10
Figure 9.	Enable threshold OFF	10
Figure 10.	Output current limit	10
Figure 11.	Quiescent current vs. input voltage	11
Figure 12.	Quiescent current vs. output current	11
Figure 13.	Quiescent current vs. temperature	11
Figure 14.	Dropout voltage vs. temperature	11
Figure 15.	Load transient $V_{EN} = 2\text{ V}$	11
Figure 16.	Load transient $V_{EN} = 1\text{ V}$	11
Figure 17.	Load transient	12
Figure 18.	Line transient	12
Figure 19.	Turn on time	12
Figure 20.	Turn on time	12
Figure 21.	Spectral noise density vs. frequency	12
Figure 22.	PSRR vs. frequency $V_{IN} = 5\text{ V}$	12
Figure 23.	PSRR vs. frequency $V_{IN} = 19\text{ V}$	13
Figure 24.	Stability plane for $V_{OUT} = 1.2\text{ V}$	13
Figure 25.	Stability plane for $V_{OUT} = 18\text{ V}$	13
Figure 26.	DFN6 (2 x 2) package outline	14
Figure 27.	DFN6 (2 x 2) recommended footprint	15
Figure 28.	DFN6 (2 x 2) wettable flanks package outline	16
Figure 29.	DFN6 (2 x 2) wettable flanks recommended footprint	18
Figure 30.	DFN6 WF 2D marking	19
Figure 31.	SOT23-5L package outline	20
Figure 32.	SOT23-5L recommended footprint	21
Figure 33.	DFN6 (2x2 mm) tape outline	22
Figure 34.	DFN6 (2x2 mm) reel outline	23
Figure 35.	Pin 1 orientation	24
Figure 36.	DFN6 (2x2 mm) cover tape outline	24

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved