May 1, 2009



LM3550 PRODUCT BRIEF

5A Flash LED Driver with Automatic Vf and ESR Detection for Mobile Camera Systems

General Description

LM3550 is a low noise, switched capacitor DC/DC converter designed to operate as a current-limited and adjustable (up to 5.3V) super-capacitor charger. LM3550 features user selectable super-capacitor charge termination voltages and an optimal charge termination mode that maximizes flash energy efficiency by accounting for flash element losses. Additionally, the device provides one adjustable constant-current output (up to 200mA) and one NFET controller ideal for driving one or more high current LEDs either in a high power Flash mode or a low power Torch mode.

The LM3550 can be configured to utilize a proprietary supercapacitor charging scheme (Optimal Mode), allowing faster charging times (0 to Target Voltage) and lower current source power dissipation. Optimal Charge mode adapts to changes in the flash LEDs forward voltage as well as the supercapacitor's ESR ensuring that the super-capacitor is charged to the ideal voltage required to sustain constant current flash operation.

The LED current and Flash pulse duration of the LM3550 can be programmed via an I²C compatible interface. The Strobe pin allows the Flash to be toggled via a Flash enable signal from a camera module. The $\overline{\text{EOC}}$ pin sinks current when the output voltage reaches 95% of the final value.

The ALD/TEMP input pin allows either a light sensor to adjust the flash current level based on the ambient light conditions, or it allows for over-temperature detection and protection of the LED during high power operation or high ambient temperature conditions by connecting an NTC thermistor temperature monitoring circuit to the pin.

Notice: This document is not a full datasheet. For more information regarding this product or to order samples, please contact your local National Semiconductor sales office or visit http://www.national.com/support/dtr.html.

Features

- Up to 5A Flash Current
- 4 Selectable Super-Capacitor Charge Voltage Levels (4.5V, 5.0V, 5.3V, Optimized)
- Flash Optimized Charge Mode for Optimal Efficiency -33% Faster Charge Time Using Optimal Mode -49% Less Power Dissipated in Current Source using Optimal Charge Mode
- Fast Super-Capacitor Charger with 500 mA Input Current Limit
- Adjustable Torch Current (60mA to 200mA)
- Ambient Light or LED Thermal Sensing with Current Scaleback
- End-of-Charge Output (EOC)
- Dedicated Indicator LED Current Source
- No Inductor Required
- Manual Flash Enable via Strobe Pin Input
- Programmable Flash Pulse Duration, and Torch and Flash Currents via I²C Compatible Interface
- True Shutdown (LED Disconnect)
- Flash Time-Out Protection
- LED Temperature Protection or Ambient Light Sensing Pin
- Low Profile 20–Pin LLP Package (3.0 mm × 2.5 mm × 0.8 mm)

Applications

- Camera Phones
- Digital Still Camera
- Voltage Rail Management

Notes

For more National Semiconductor product information and proven design tools, visit the following Web sites at:

Products		Design Support	
Amplifiers	www.national.com/amplifiers	WEBENCH® Tools	www.national.com/webench
Audio	www.national.com/audio	App Notes	www.national.com/appnotes
Clock and Timing	www.national.com/timing	Reference Designs	www.national.com/refdesigns
Data Converters	www.national.com/adc	Samples	www.national.com/samples
Interface	www.national.com/interface	Eval Boards	www.national.com/evalboards
LVDS	www.national.com/lvds	Packaging	www.national.com/packaging
Power Management	www.national.com/power	Green Compliance	www.national.com/quality/green
Switching Regulators	www.national.com/switchers	Distributors	www.national.com/contacts
LDOs	www.national.com/ldo	Quality and Reliability	www.national.com/quality
LED Lighting	www.national.com/led	Feedback/Support	www.national.com/feedback
Voltage Reference	www.national.com/vref	Design Made Easy	www.national.com/easy
PowerWise® Solutions	www.national.com/powerwise	Solutions	www.national.com/solutions
Serial Digital Interface (SDI)	www.national.com/sdi	Mil/Aero	www.national.com/milaero
Temperature Sensors	www.national.com/tempsensors	SolarMagic™	www.national.com/solarmagic
Wireless (PLL/VCO)	www.national.com/wireless	Analog University®	www.national.com/AU

THE CONTENTS OF THIS DOCUMENT ARE PROVIDED IN CONNECTION WITH NATIONAL SEMICONDUCTOR CORPORATION ("NATIONAL") PRODUCTS. NATIONAL MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS OF THIS PUBLICATION AND RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE. NO LICENSE, WHETHER EXPRESS, IMPLIED, ARISING BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT.

TESTING AND OTHER QUALITY CONTROLS ARE USED TO THE EXTENT NATIONAL DEEMS NECESSARY TO SUPPORT NATIONAL'S PRODUCT WARRANTY. EXCEPT WHERE MANDATED BY GOVERNMENT REQUIREMENTS, TESTING OF ALL PARAMETERS OF EACH PRODUCT IS NOT NECESSARILY PERFORMED. NATIONAL ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR BUYER PRODUCT DESIGN. BUYERS ARE RESPONSIBLE FOR THEIR PRODUCTS AND APPLICATIONS USING NATIONAL COMPONENTS. PRIOR TO USING OR DISTRIBUTING ANY PRODUCTS THAT INCLUDE NATIONAL COMPONENTS, BUYERS SHOULD PROVIDE ADEQUATE DESIGN, TESTING AND OPERATING SAFEGUARDS.

EXCEPT AS PROVIDED IN NATIONAL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, NATIONAL ASSUMES NO LIABILITY WHATSOEVER, AND NATIONAL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO THE SALE AND/OR USE OF NATIONAL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

Life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness.

National Semiconductor and the National Semiconductor logo are registered trademarks of National Semiconductor Corporation. All other brand or product names may be trademarks or registered trademarks of their respective holders.

Copyright© 2009 National Semiconductor Corporation

For the most current product information visit us at www.national.com



National Semiconductor Americas Technical Support Center Email: support@nsc.com Tel: 1-800-272-9959

National Semiconductor Europe Technical Support Center Email: europe.support@nsc.com National Semiconductor Asia Pacific Technical Support Center Email: ap.support@nsc.com National Semiconductor Japan Technical Support Center Email: jpn.feedback@nsc.com