# LQH2MPN330MGR#

"#" indicates a package specification code.
















< List of part numbers with package codes > LQH2MPN330MGRL

### Shape





#### **Notes**

When rated current is applied to the products, inductance will be within  $\pm 30\%$  of initial inductance value range.

Keep the temperature (ambient temperature plus self-generation of heat) under 125  $^{\circ}\text{C}.$ 

When rated current is applied to the products, the self-temperature rise shall be limited to  $40\,^{\circ}$ C max. (ambient temperature  $85\,^{\circ}$ C).

When rated current is applied to the products, the self-temperature rise shall be limited to  $20\,^{\circ}$ C max. (ambient temperature  $85\,^{\circ}$ C to  $105\,^{\circ}$ C).

### References

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	3000

Ма	ss (Typ.)
1 piece	0.010g

## Specifications

Inductance	33μH ±20%
Inductance test frequency	1MHz
Rated current (Isat) (Based on Inductance change)	310mA
Rated current (Itemp) (Based on Temperature rise)	200mA(Ambient temp.85°C) 120mA(Ambient temp.105°C)
Max. of DC resistance	5.16Ω
Avg. of DC resistance	4.3Ω±20%
Self resonance frequency (min.)	15MHz
Operating temperature range (Self-temperature rise is included)	-40°C to 125°C
Operating temperature range (Self-temperature rise is not included)	-40°C to 105°C
Class of magnetic shield	Ferrite Core
Series	LQH2MPN_GR

1 of 2





<sup>1.</sup>This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications











2 of 2



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.