



Spec No. :DS30-2001-094 Effective Date: 10/05/2024 Revision: A

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

LITE-ON Technology Corp. / Optoelectronics No.90,Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C. Tel: 886-2-2222-6181 Fax: 886-2-2221-1948 / 886-2-2221-0660 http://www.liteon.com/opto



LED DISPLAY LTP-4323JD

LED DISPLAY

LTP-4323JD

<u>Rev</u>	Description	<u>By</u>	<u>Date</u> (DD/MM/YYY)				
01	Original Spec	Meg Huang	16/03/2001				
	Above data for PD and Customer tracking only						
-	NPPR Received and Upload to system	Meg Huang	16/05/2001				
А	Add Reliability Test, Soldering Profile & CAUTIONS	Chrisada P.	07/06/2024				





LED DISPLAY LTP-4323JD

1. Description

The LTP-4323JD is a 0.4 inch (10.0 mm) digit height 16-segment dual alphanumeric display. This device utilizes AllnGaP Hyper Red

LED chips, which are made from AllnGaP on a non-transparent GaAs substrate, and has a gray face and white segments.

1.1 Features

- 0.4 inch (10.0 mm) DIGIT HEIGHT
- CONTINUOUS UNIFORM SEGMENTS
- LOW POWER REQUIREMENTS
- EXCELLENT CHARACTERS AND APPEARANCE
- HIGH CONTRAST
- HIGH BRIGHTNESS
- WIDE VIEWING ANGLE
- SOLID STATE RELIABILITY
- COMMON ANODE OR COMMON CATHODE MODEL
- CATEGORIZED FOR LUMINOUS INTENSITY
- EASY MOUNTING ON P.C. BOARD
- LEAD-FREE PACKAGE (ACCORDING TO ROHS)

1.2 Device

Part No	Description
AllnGap Hyper Red	Duplex Common Cathode
LTP-4323JD	Rt. Hand Decimal





LED DISPLAY LTP-4323JD

2. Package Dimensions



Notes:

- 1. All dimensions are in millimeters. Tolerances are 0.25 mm (0.01") unless otherwise noted.
- 2. Pin tip's shift tolerance is 0.4 mm.
- 3. Foreign material on segment ≤ 10 mils
- 4. Ink contamination (surface) \leq 20mils
- 5. Bending≦1/100 of reflector length
- 6. Bubble in segment ≤ 10 mils
- 7. Recommend the best PCB hole: Ø1.30mm.



LED DISPLAY LTP-4323JD

3. INTERNAL CIRCUIT DIAGRAM



4. PIN CONNECTION

No.	CONNECTION			
1	ANODE F			
2	ANODE T			
3	ANODE S			
4	COMMON CATHODE CHARACTER 1			
5	ANODE DP			
6	ANODE G			
7	ANODE R			
8	ANODE D			
9	ANODE E			
10	COMMON CATHODE CHARACTER 2			
11	ANODE B			
12	ANODE N			
13	ANODE A			
14	NO CONNECTION			
15	ANODE H			
16	ANODE P			
17	ANODE C			
18	ANODE M			
19	ANODE K			
20	ANODE U			







LED DISPLAY LTP-4323JD

5. Rating and Characteristics

5.1 Absolute Maximum Rating at Ta=25°C

Parameter	Maximum Rating	Unit			
Power Dissipation Per Segment	70	mW			
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	90	mA			
Continuous Forward Current Per Segment	25	mA			
Derating Linear from 25°C Per Segment	0.33	mA/℃			
Operating Temperature Range -35°C to +85°C					
Storage Temperature Range -35°C to +85°C					
Solder Condition: 1/16 inch below seating plane for 5 seconds at 260℃ or temperature of unit (during a ssembly)					

not over max. temperature rating above

5.2 Electrical / Optical Characteristics at Ta=25°C

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Test Condition
Average Luminous Intensity	IV	200	650		ucd	IF=1mA
Peak Emission Wavelength	λρ		650		nm	IF=20mA
Spectral Line Half-Width	Δλ		20		nm	IF=20mA
Dominant Wavelength	λd		639		nm	IF=20mA
Forward Voltage Per Segment	VF		2.1	2.6	V	IF=20mA
Reverse Current Per Segment(*3)	IR			100	μΑ	VR=5V
Luminous Intensity Matching Ratio	lv-m			0.4		IF=1mA
(Similar Light Area)				2:1		IF=IMA

Notes:

- 1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commission International De L'Eclariage) eye-response curve
- 2. Cross talk specification $\leq 2.5\%$
- 3. Reverse voltage is only for IR test. It cannot continue to operate at this situation.





LED DISPLAY LTP-4323JD

5.3 Typical Electrical / Optical Characteristics Curves



NOTE : JD=AlInGaP HYPER RED

Part No.: LTP-4323JD BNS-OD-FC002/A4



LED DISPLAY LTP-4323JD

6. Reliability Test

Classification	Test Item		Test Condition	Reference Standard
Endurance Test	Operation Life	RTOL	Ta=Under Room Temperature	MIL-STD-750D:1026 (1995)
			IF=As per data sheet maximum Rating	MIL-STD-883E:1005 (1996)
			* Test Time= 1000Hrs (-24Hrs, +72Hrs)	JIS C 7021: B-1 (1982)
	High Temperature High	THS	$Ta = 65 \pm 5^{\circ}C$	MIL-STD-202G:103B (2002)
	Humidity Storage		RH=90 ~ 95%	JIS C 7021: B-11 (1982)
			Test Time=500Hrs (±2Hrs)	
	High Temperature	HTS	$Ta=105\pm5^{\circ}C$	MIL-STD-883E:1008 (1996)
	Storage		Test Time=1000Hrs (-24Hrs, +72Hrs)	JIS C 7021: B-10 (1982)
	Low Temperature	LTS	$Ta = -35\pm 5^{\circ}C$	JIS C 7021: B-12 (1982)
	Storage		Test Time=1000Hrs (-24Hrs, +72Hrs)	
Environmental Test	Temperturre Cycling	ТС	$105^{\circ}\text{C} \sim 25^{\circ}\text{C} \sim -35^{\circ}\text{C} \sim 25^{\circ}\text{C}$	MIL-STD-202G:107D (2002)
			30mins ~ 5mins ~ 30mins ~ 5mins	MIL-STD-750D:1051 (1995)
			30 Cycles	MIL-STD-883E:1010 (1996)
				JIS C 7021: A-4 (1982)
	Thermal Shock	TS	105 ±5°C ~ -35 ±5°C	MIL-STD-202G:107D (2002)
			30mins ~ 30mins	MIL-STD-750D:1051 (1995)
			30 Cycles	MIL-STD-883E:1011 (1996)
	Solder Resistance	SR	T.Sol=260 ±5°C	MIL-STD-202G:210A (2002)
			Dwell Time= 10 ± 1 secs	MIL-STD-750D:2031 (1995)
			(For solder pin only)	JIS C 7021: A-1 (1982)
	Solderability	SA	T.Sol=245 ±5°C	MIL-STD-202G:208D (2002)
			Dwell Time= 5 ± 1 secs	MIL-STD-750D:2026 (1995)
			(For solder pin only)	MIL-STD-883E:2003 (1996)
				JIS C 7021: A-2 (1982)

* (Check point: 0th, 168th, 500th, 800th, 1000th Hrs)

Follow as : QS-00TP-RELBE-0001 Reliability Test Conditions





LED DISPLAY LTP-4323JD

7. Soldering Profile

7.1 Auto Soldering

Solder Conditions: 1/16 inch below seating plane for 5 seconds at 260°C, or temperature of u nit (during assembly) not over max.

Temperature rating above.





7.2 Manual Soldering

Solder Conditions: 1/16 inch below seating plane within 5 seconds at 350°C±30°C.



LED DISPLAY LTP-4323JD

8. CAUTIONS

8.1 Application

- The display described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household applications). Consult Liteon's Sales in advance for information on applications in which exceptional reliability is required, particularly when the failure or malfunction of the display may directly jeopardize life or health (such as in aviation, transportation, traffic control equipment, medical and life support systems and safety devices).
- When using this LED display, please make sure absolute maximum ratings and the instructions for using outlined in these specification sheets. LITEON will not be responsible for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
- Excess driving current and/or operating temperature higher than recommended conditions may result in severe light degradation or premature failure.
- The driving circuit should be designed to protect the LEDs inside the display against reverse voltages and transient voltage spikes when the circuit is powered up or shut down.
- Constant current driving is recommended to ensure consistent performance.
- Circuit design must cater to the whole range of forward voltage (VF) of the LEDs inside the display to ensure the intended drive current can always be achieved.
- The safe operating current should be chosen after considering the maximum ambient temperature of the operating environment.
- Reverse bias should be avoided, as it could cause metal migration, leading to an increase in leakage current or causing a short circuit.
- Avoid rapid changes in ambient temperatures, especially in high-humidity environments, because they cause condensation on the LED/LED display.
- Do not use unsuitable tool or assembly method to have abnormal force on display body cause damage.
- Printing/pattern film is using pressure sensitive glue to stick on LED display surface, not recommend to let LED display
 pattern film side close contact with front panel/cover, since the printing/pattern film may shift or moved from original
 position by external force.
- Recommend choose same BIN LED display while you assemble 2 or above 2 pcs LED display for one set application to avoid hue uneven problems.





LED DISPLAY LTP-4323JD

8.2 Storage conditions

- LED Display standard storage condition.
 - Product in the original packaging material state is recommended storage conditions.
 - Temperature Condition: 5°C~30°C
 - Humidity Condition: Below 60%RH

If the storage conditions do not meet specification standards, the LED display pins may become oxidized requiring re-plating and re-sorting before use. Suggest customers consume display as soon as possible and avoid long-term storage of large inventories. If unseal package over 6 months, it is recommended baking at 60°C for 48 hours, and assembly within a week.

- LED SMD Display standard storage condition
 - When the package is in factory original sealed bag.
 - Temperature Condition: 5℃~30℃
 - Humidity Condition: Below 60%RH
 - When the package is opened and not in factory original sealed bag.
 - Temperature Condition: 5℃~30℃
 - Humidity Condition: Below 60%RH
 - Storage time: Within 168Hr (MSL as level 3)

If the storage conditions do not meet specification standards, the LED display pins or soldering pads may become oxidized requiring re-plating and re-sorting before use. Suggest customers consume display as soon as possible and avoid long-term storage of large inventories.

- Recommend to baking the LEDs at 60°C for 24hrs before soldering process if the LED SMD Display were unpacked more than 168hrs.
- Recommend using sealed package within 12 months from date code.
- The Displays should not be exposed to an environment where high level of moisture or corrosive gases are present.
- LED display pins and soldering pads are plated with gold, tin, or other metals. Under long-term exposure to open air, the
 exposed pins and pads may become oxidized causing poor solderability. Therefore, opened but unused parts must be
 stored in sealed containers or controlled environment. Suggest to store unused SMD Display parts in the original
 moisture barrier bag and sealed.
- Moisture control for components already mounted on PCB
 If the PCB will not undergo additional reflow soldering or high-temperature processes, then no special treatment is required for the mounted moisture-sensitive SMD components. If the PCB will undergo multiple reflow soldering or other high-temperature processes, including rework, then the SMD component's cumulative exposure time until the final high-temperature process must be controlled to within the specified time limit.





LED DISPLAY LTP-4323JD

Part No.: LTP-4323JD BNS-OD-FC002/A4

8.3 Cleaning

Do not use unspecified chemical liquid to clean display they could harm the package.

8.4 ESD (Electrostatic Discharge)

Static Electricity or power surge will damage LED inside the display.

Suggestions to prevent ESD damage:

- Use of a conductive wrist band or anti-electrostatic glove when handling these LED displays.
- All devices, equipment, and machinery, working tables, storage racks, etc. must be properly grounded.
- Use ion blower to neutralize the static charge which might have built up on surface of the LED display plastic as a result of friction between LED display during storage and handling.

8.5 Terms and conditions for the usage of this document

- Keep same appearance and performance the contents of the product may be modified for productivity and reliability improvement without prior notice.
- The information included in this document reflects representative usage scenarios and is intended for technical reference only.
- When using the products referenced in this document, please make sure the product is being operated within the
 environmental and electrical limits specified in the datasheet. If customer usage exceeds the specified limits, LITEON will
 not be responsible for any subsequent issues.
- Excess driving current and/or operating temperature higher than recommended conditions may result in severe light degradation or premature failure.
- The information in this document applies to typical usage in consumer electronics applications. If customer's application
 has special reliability requirements or have life-threatening liabilities, such as automotive or medical usage, please
 consult with LITEON representative for further assistance.
- The contents and information of this document may not be reproduced or re-transmitted without permission by LITEON.
- When any special process such as potting is required for LED display assembly, please consult with LITEON representative before proceeding.
- Over-current-proof
 Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).