

LED Display
Product Data Sheet
LTS-4812SKR-P

Spec No. :DS30-2006-040
Effective Date: 01/04/2020
Revision: H

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

**LED DISPLAY
LTS-4812SKR-P**

LED DISPLAY

LTS-4812SKR-P

<u>Rev</u>	<u>Description</u>	<u>By</u>	<u>Date</u>
01	Preliminary Spec.	YG Shi	04/20/2006
Above data for PD and Customer tracking only			
-	NPPR Received and Upload on System	YG Shi	04/20/2006
A	Add tape & reel oriented 3D drawing	Vincent Yu	10/31/2006
B	Change temperature curve	Nancy Du	01/17/2008
C	Change gray face to light gray face	Angelrgao	01/30/2008
D	Modify DS spec (Accessories Description)	ChunChun Lee	03/14/2009
E	Add bin table (J1~M2)	ChunChun Lee	10/17/2009
F	Change marking customer p/n and part no.	Mina Lin	05/18/2010
G	Change packing quantity	Mina Lin	06/11/2011
H	Update Packing spec. in page 10	Reo Lin	12/30/2019

LED DISPLAY LTS-4812SKR-P

1. Description

The LTS-4812SKR-P is a 0.39 inch (10.0 mm) digit height single digit SMD display. This device uses AS-AlInGaP Super Red LED chips (AlInGaP epi on GaAs substrate). The display has gray face and white segments.

1.1 Features


- 0.39 inch (10.0 mm) DIGIT HEIGHT
- CONTINUOUS UNIFORM SEGMENTS
- LOW POWER REQUIREMENT
- EXCELLENT CHARACTERS APPEARANCE
- HIGH BRIGHTNESS & HIGH CONTRAST
- WIDE VIEWING ANGLE
- SOLID STATE RELIABILITY
- CATEGORIZED FOR LUMINOUS INTENSITY.
- LEAD-FREE PACKAGE (ACCORDING TO ROHS)

1.2 Device

Part No	Description
AlInGaP Super Red	Common Anode
LTS-4812SKR-P	
	Rt. Hand Decimal

LED DISPLAY LTS-4812SKR-P

2. Package Dimensions




Notes :

1. All dimensions are in millimeters. Tolerances are ±0.25 mm (0.01") unless otherwise noted
2. Foreign material on segment ≤10mil
3. Ink contamination (surface) ≤20mils
4. Bubble in segment ≤10mil
5. Bending ≤ 1% of reflector length
6. Plastic pin's burr max is 0.1 mm

LED DISPLAY LTS-4812SKR-P

3. Internal Circuit Diagram



4. Pin Connection

No	Connection
1	CATHODE E
2	CATHODE D
3	COMMON ANODE
4	CATHODE C
5	CATHODE DP
6	CATHODE B
7	CATHODE A
8	COMMON ANODE
9	CATHODE F
10	CATHODE G

LED DISPLAY LTS-4812SKR-P

5. Rating and Characteristics

5.1. Absolute Maximum Rating at Ta=25°C

Parameter	Maximum Rating	Unit
Power Dissipation Per Segment	70	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	90	mA
Continuous Forward Current Per Segment	25	mA
Derating Linear From 25°C Per Segment	0.28	mA/°C
Operating Temperature Range	-35°C to +105°C	
Storage Temperature Range	-35°C to +105°C	
Iron Soldering Conditions: 1/16 inch Below Seating Plane for 3 Seconds at 260°C		

5.2. Electrical / Optical Characteristics at Ta=25°C

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Test Condition
Average Luminous Intensity Per Segment	IV	1301	3000	8600	μcd	IF=2mA
Peak Emission Wavelength	λp		639		nm	IF=20mA
Spectral Line Half-Width	Δλ		20		nm	IF=20mA
Dominant Wavelength	λd		631		nm	IF=20mA
Forward Voltage Per Chip	VF		2.0	2.6	V	IF=20mA
Reverse Current Per Segment ⁽²⁾	IR			100	μA	VR=5V
Luminous Intensity Matching Ratio (Similar Light Area)	IV-m			2:1		IF=2mA

Notes :

- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commission International De L'Eclairage) eye-response curve
- Reverse voltage is only for IR test. It cannot continue to operate at this situation
- Cross talk specification ≤ 2.5%

LED DISPLAY LTS-4812SKR-P

5.3.Bin Range Distribution






Bin	J1	J2	K1	K2
Min.	1301	1651	2101	2681
Max.	1650	2100	2680	3400

Bin	L1	L2	M1	M2
Min.	3401	4301	5401	6851
Max.	4300	5400	6850	8600

Unit is μcd , Tolerance is $\pm 15\%$

LED DISPLAY LTS-4812SKR-P

5.4. Typical Electrical / Optical Characteristics Curves




NOTE : KR=AlInGaP SUPER RED

LED DISPLAY LTS-4812SKR-P

6. SMT SOLDERING INSTRUCTION

(Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process)



Notes :


1. Recommended soldering condition

Reflow Soldering (Two times only)		Soldering Iron (One time only)	
Pre-heat:	120~150°C.	Temperature	300°C Max.
Pre-heat time:	120sec. Max.	Soldering time	3sec. Max.
Peak temperature:	260°C Max.		
Soldering time:	5sec. Max.		

2. Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process.


**LED DISPLAY
LTS-4812SKR-P**

7. Recommended Soldering Pattern




8. Packing Specification

8.1. Packing Reel Dimensions




LED DISPLAY LTS-4812SKR-P

8.2. Packing Carrier Dimensions



1. 10 sprocket hole pitch cumulative tolerance ± 0.20 .
2. Carrier camber is within 1 mm in 250 mm.
3. Material : Black Conductive Polystyrene Alloy.
4. All dimensions meet EIA-481-D requirements.
5. Thickness : 0.40 ± 0.05 mm.
6. Packing length per 22" reel : 44.5 Meters.(1:3)
7. Component load per 13" reel : 800 pcs.
8. Minimum packing quantity is 200 pcs for remainders


8.3.Trailer part / Leader part



LED DISPLAY LTS-4812SKR-P

9. Moisture Proof Packing

All N/D SMD displays are shipped in moisture proof package. The displays should be stored at 30°C or less and 60% RH or less. Once the package opened, moisture absorption begins.



If the parts are not stored in dry conditions, they must be baked before reflow to prevent damage to the parts. Baking should only be done once

Package	Temperature	Time
In Reel	60°C	≥ 48hours
In Bulk	100°C	≥ 4hours
	125°C	≥ 2hours