



Photocoupler

Product Data Sheet

LTV-071L

Spec No.: DS70-2016-0026

Effective Date: 06/04/2016

Revision: -

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

PHOTOCOUPLER LTV-071L

1. DESCRIPTION

The LTV-071L consists of a high efficient AlGaAs Light Emitting Diode and a high speed optical detector. This design provides excellent AC and DC isolation between the input and output sides of the Optocoupler. The output of the optical detector features a totem pole output. The internal shield ensures high common mode transient immunity. A guaranteed common mode transient immunity is up to 10KV/ μ s. The Optocoupler operational parameters are guaranteed over the temperature range from -40°C to +105°C.


1.1 Features

- Dual channel High speed 15MBd
- 3.3V and 5.5V CMOS Compatible
- Available in SO8.
- Safety approval
UL 1577
VDE DIN/EN 60747-5-5
- RoHS Compliance

1.2 Applications

- High Voltage Isolation
- Isolation in line receivers
- Ground loop elimination
- Feedback Element in Switching Mode Power Supplier
- Data transmission
- CANBus, RS485, USB
- Interface between Microprocessor system, computer and their peripheral

1.3 Functional Diagram



Truth Table (Positive Logic)


LED	OUT
ON	L
OFF	H

A 0.1 μ F bypass Capacitor must

PHOTOCOUPLER

LTV-071L

2. PACKAGE DIMENSIONS



Part No : LTV-071L


Notes :

1. Part numbers
2. "V" to represent VDE0884
3. The first digit is year code, second and third digit is week code

Dimensions are in Millimeters

PHOTOCOUPLER LTV-071L

3. TAPING DIMENSIONS



Description	Symbol	Dimension in mm (inch)
Tape wide	W	16±0.3 (0.63)
Pitch of sprocket holes	P ₀	4±0.1 (0.15)
Distance of compartment	F	7.5±0.1 (0.295)
	P ₂	2±0.1 (0.079)
Distance of compartment to compartment	P ₁	8±0.1 (0.47)

Quantities Per Reel

Package Type	LTV-071L
Quantities (pcs)	3000

PHOTOCOUPLER LTV-071L

4. RATING AND CHARACTERISTICS

4.1 Absolute Maximum Ratings at Ta=25°C *1

	Parameter	Symbol	Rating	Unit
Input	Average Forward Input Current *2	I_F	20	mA/ch
	Reverse Input Voltage	V_R	5	V
Output	Output Collector Current	I_O	10	mA
	Output Collector Voltage	V_O	7	V
	Output Collector Power Dissipation	P_O	60	mW
	Isolation Voltage	V_{iso}	3750	V_{rms}
	Supply Voltage	V_{CC}	7	V
	Operating Temperature	T_{opr}	-40 ~ +105	°C
	Storage Temperature	T_{stg}	-55 ~ +125	°C
	Lead Solder Temperature	T_{sol}	260	°C

1. Ambient temperature = 25°C, unless otherwise specified. Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.
2. 260°C for 10 seconds. Refer to Lead Free Reflow Profile.

4.2 Recommended Operation Condition

Parameter	Symbol	Min.	Max.	Units
Ambient Operation Temperature	T_A	-40	+105	°C
Supply Voltage	V_{CC}	4.5	5.5	V
		3.0	3.6	V
Input Current (ON)	I_F	7	14	mA

PHOTOCOUPLER LTV-071L

4.3 ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Input						
Input Forward Voltage	V_F	1.3	1.55	1.80	V	$I_F = 14\text{mA}$
Input Forward Voltage Temperature Coefficient	$\Delta V_F / \Delta T$	—	-1.143	—	mV/°C	$I_F = 14\text{mA}$
Input Reverse Voltage	BV_R	5.0	—	—	V	$I_R = 10\mu\text{A}$
Input Threshold Current	I_{TH}	—	4	6.5	mA	$V_O < 0.8\text{V}$
Input Capacitance	C_{IN}	—	34	—	pF	$f = 1\text{MHz}, V_F = 0\text{V}$
Detector						
High Level Supply Current	I_{CCH}	—	3	8	mA	$I_F = 0\text{mA}$
Low Level Supply Current	I_{CCL}	—	3	8	mA	$I_F = 14\text{mA}$
High Level Output Current	V_{OH}	$V_{CC}-1$	$V_{CC}-0.3$	-	V	$V_{CC} = 3.3\text{V}, I_O = -4\text{mA}, I_F = 0\text{mA}$
		$V_{CC}-1$	$V_{CC}-0.2$			$V_{CC} = 5\text{V}, I_O = -4\text{mA}, I_F = 0\text{mA}$
Low Level Output Voltage	V_{OL}	—	0.22	0.80	V	$V_{CC} = 3.3\text{V}, I_O = 4\text{mA}, I_F = 14\text{mA}$
		—	0.16	0.80		$V_{CC} = 5\text{V}, I_O = 4\text{mA}, I_F = 14\text{mA},$

Specified over recommended temperature ($T_A = -40^\circ\text{C}$ to $+105^\circ\text{C}$) unless otherwise specified.

Typical values applies to $V_{CC} = 5\text{V}$, $T_A = 25^\circ\text{C}$. See note 1.

PHOTOCOUPLER LTV-071L

5. SWITCHING SPECIFICATION

$T_A=0\sim70^{\circ}\text{C}$, $V_{CC}=5\text{V}$, unless otherwise specified.

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Propagation Delay Time to Low Output Level *4	t_{PHL}	—	31	60	ns	$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=3.3\text{V}$
		—	30	60		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=5\text{V}$
Propagation Delay Time to High Output Level *3	t_{PLH}	—	40	60		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=3.3\text{V}$
		—	40	60		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=5\text{V}$
Pulse Width Distortion	$ t_{PLH} - t_{PHL} $	—	9	30		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=3.3\text{V}$
		—	10	30		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=5\text{V}$
Propagation Delay Skew	t_{PSK}			40		$C_L = 15\text{pF}$, $V_{CC}=5\text{V}$
Output Rise Time (10 to 90%)	t_r	—	8	—		$I_F=14\text{mA}$, $C_L = 15\text{pF}$, $V_{CC}=5\text{V}$
Output Fall Time (90 to 10%)	t_f	—	6	—		
Pulse width	t_{PW}	66.7	—	—		—
Common Mode Transient Immunity at High Output Level*5	$ CM_H $	10	—	—	kV/ μs	$ V_{CM} = 1\text{KV}$, $V_{CC} = 5\text{V}$, $I_F = 0\text{mA}$, $V_O > 3\text{V}$, $T_A = 25^{\circ}\text{C}$
Common Mode Transient Immunity at Low Output Level*6	$ CM_L $	10	—	—	kV/ μs	$ V_{CM} = 1\text{KV}$, $V_{CC} = 5\text{V}$, $I_F = 14\text{mA}$, $V_O < 0.8\text{V}$, $T_A = 25^{\circ}\text{C}$

Specified over recommended temperature ($T_A = -40^{\circ}\text{C}$ to $+105^{\circ}\text{C}$) unless otherwise specified. Typical values applies to $T_A = 25^{\circ}\text{C}$

PHOTOCOUPLER LTV-071L

6. ISOLATION CHARACTERISTIC

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Input-Output Insulation Leakage Current *7	I_{I-O}	—	—	1.0	μA	45% RH, $t = 5s$, $V_{I-O} = 3kV$ DC, $T_A = 25^{\circ}C$
Withstand Insulation Test Voltage *7	V_{ISO}	3750	—	—	V_{RMS}	$RH \leq 50\%$, $t = 1min$, $T_A = 25^{\circ}C$
Input-Output Resistance *7	R_{I-O}	—	10^{12}	—	Ω	$V_{I-O} = 1kV$ DC
Input-Output Capacitance *7	C_{I-O}	—	0.6	—	pF	$f = 1MHz$, $T_A = 25^{\circ}C$

Specified over recommended temperature ($T_A = -40^{\circ}C$ to $+105^{\circ}C$) unless otherwise specified. Typical values applies to $T_A = 25^{\circ}C$

Notes

1. A $0.1\mu F$ or bigger bypass capacitor for V_{CC} is needed as shown in Fig.1
2. Peaking driving circuit may be used to speed up the LED. The peak drive current of LED may go up to 50mA and maximum pulse width 50ns, as long as average current doesn't exceed 20mA.
3. t_{PLH} (propagation delay) is measured from the 6.5 mA point on the falling edge of the input pulse to the 1.5 V point on the rising edge of the output pulse.
4. t_{PHL} (propagation delay) is measured from the 6.5 mA point on the rising edge of the input pulse to the 1.5 V point on the falling edge of the output pulse.
5. $|CM_H|$ is the maximum tolerable rate of rise of the common mode voltage to assure that the output will remain in a high logic state (i.e., $VO > 3.0 V$).
6. $|CM_L|$ is the maximum tolerable rate of fall of the common mode voltage to assure that the output will remain in a low logic state (i.e., $VO < 0.8 V$).
7. Device is considered a two-terminal device: pins 1, 2, 3, and 4 shorted together, and pins 5, 6, 7, and 8 shorted together.

PHOTOCOUPLER LTV-071L

7. SWITCHING TIME TEST CIRCUIT




Figure 1: One Channel Test Circuit for t_{PHL} and t_{PLH}




Figure 2: One Channel Test Circuit for Common Mode Transient Immunity

PHOTOCOUPLER LTV-071L

8. TYPICAL PERFORMANCE CURVES

Figure 3: Input Current vs Forward Voltage




Figure 4: Forward Voltage vs Temperature




Figure 5: Supply Current High vs Temperature




Figure 6: Supply Current Low vs Supply Voltage




Figure 7: Switching Speed vs Input Current at 5V






Figure 8: Switching Speed vs Input Current at .3V



**PHOTOCOUPLER
LTV-071L**

Figure 9: Input Threshold Current vs Temperature




PHOTOCOUPLER LTV-071L

9. TEMPERATURE PROFILE OF SOLDERING

9.1 IR Reflow soldering (JEDEC-STD-020 compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

Profile item	Conditions
Preheat	
- Temperature Min (T_{Smin})	150°C
- Temperature Max (T_{Smax})	200°C
- Time (min to max) (t_s)	90±30 sec
Soldering zone	
- Temperature (T_L)	217°C
- Time (t_L)	60 sec
Peak Temperature (T_P)	260°C
Ramp-up rate	3°C / sec max.
Ramp-down rate	3~6°C / sec



PHOTOCOUPLER LTV-071L

9.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature: $260 \pm 0/-5^{\circ}\text{C}$

Time: 10 sec.

Preheat temperature: 25 to 140°C

Preheat time: 30 to 80 sec.



9.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature: $380 \pm 0/-5^{\circ}\text{C}$

Time: 3 sec max.

10. Notes:

Specifications of the products displayed herein are subject to change without notice.

The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical instrumentation and application. For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.