

MITSUBISHI ELEK {LINEAR} 80 DE 6249826 0009328

MITSUBISHI BIPOLAR DIGITAL ICs

**M54569P**

6249826 MITSUBISHI ELEK (LINEAR)

8-UNIT 30mA PNP TRANSISTOR ARRAY

80C 09328 D

T-43-25

**DESCRIPTION**

The M54569P, general purpose transistor array, consists of 8 PNP transistors connected in a common-emitter configuration.

**FEATURES**


- 20V breakdown
- 30mA output source current capability
- Wide operating temperature range ( $T_a = -20\text{--}+75^\circ\text{C}$ )

**APPLICATION**


LED or incandescent display driver

**FUNCTION**


The M54569P is comprised of 8 PNP transistors. All emitters are connected to pin 10. Each transistor is capable of switching 30mA and will withstand 20V in the OFF state.



18-pin molded plastic DIP

**PIN CONFIGURATION (TOP VIEW)**

Outline 18P4

**CIRCUIT SCHEMATIC****ABSOLUTE MAXIMUM RATINGS** ( $T_a = -20\text{--}+75^\circ\text{C}$ , unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
$V_{CBO}$	Collector-base sustaining voltage	Base voltage : 0V	-40	V
$V_{EBO}$	Emitter-base sustaining voltage	Base voltage : 0V	-40	V
$V_{CEO}$	Collector-emitter sustaining voltage	Emitter voltage : 0V	-20	V
$I_C$	Collector current per transistor		-30	mA
$I_B$	Base current per transistor		-20	mA
$P_d$	Power dissipation	$T_a = 25^\circ\text{C}$	1.47	W
$T_{opr}$	Operating ambient temperature range		-20~+75	°C
$T_{stg}$	Storage temperature range		-55~+125	°C

MITSUBISHI ELEK (LINEAR) 80 DE 6249826 0009329 M54569P

6249826 MITSUBISHI ELEK (LINEAR)

8-UNIT 30mA PNP TRANSISTOR ARRAY

80C 09329 D

T-43-25

RECOMMENDED OPERATIONAL CONDITIONS ( $T_a = -20 \sim +75^\circ\text{C}$ , unless otherwise noted)


Symbol	Parameter	Limits			Unit
		Min	Typ	Max	
$I_C$	Collector current $I_B = -3\text{mA}$	0		-20	mA
$I_B$	Base current	0		-10	mA
$V_E$	Emitter voltage	-0.3		20	V
$V_B$	Base voltage	-0.3		$V_E$	V

ELECTRICAL CHARACTERISTICS ( $T_a = -20 \sim +75^\circ\text{C}$ , unless otherwise noted)

Symbol	Parameter	Test conditions	Limits			Unit
			Min	Typ	Max	
$V_{(BR)CEO}$	Collector-emitter sustaining voltage	$I_C = -10\mu\text{A}, V_B = 0\text{V}$ $V_E : \text{OPEN}$	-40			V
$V_{(BR)EBO}$	Emitter-base sustaining voltage	$I_E = -10\mu\text{A}, V_B = 0\text{V}$ $V_C : \text{OPEN}$	-40			V
$V_{(BR)CEO}$	Collector-emitter sustaining voltage	$I_C = -100\mu\text{A}, V_E = 0\text{V}$ $V_B : \text{OPEN}$	-20			V
$V_{CE(\text{sat})}$	Collector-emitter saturation voltage	$I_C = -20\text{mA}, I_B = -3\text{mA}, V_E = 5\text{V}$		-0.09	-0.3	V
		$I_C = -2\text{mA}, I_B = -0.2\text{mA}, V_E = 5\text{V}$		-0.02	-0.28	
$h_{FE}$	DC forward current gain	$V_{CE} = -4\text{V}$	20	100		—
		$T_a = 25^\circ\text{C}$	15	70		

## TYPICAL CHARACTERISTICS

## OUTPUT CHARACTERISTICS



## DC CURRENT GAIN CHARACTERISTICS

