








M5R Series

9x14 mm, 3.3 Volt, LVPECL/LVDS, Clock Oscillator



All dimensions in inches (mm).

SUGGESTED SOLDER PAD LAYOUT



Pin Connections

FUNCTION	4 Pin	6 Pin
N/C or Output \bar{Q}	1	1
Enable		2
Ground/Cover	2	3
Output Q	3	4
N/C		5
+Vcc	4	6

Ordering Information

	M5R	1	8	Z	Q	J	-R	00.0000 MHz
Product Series								
Temperature Range								
1: 0°C to +70°C	2: -40°C to +85°C							
6: -20°C to +70°C	7: -0°C to +85°C							
8: 0°C to +50°C								
Stability								
3: ±100 ppm	4: ±50 ppm	5: ±35 ppm						
6: ±25 ppm	8: ±20 ppm							
Output Type								
R: Complementary Enable	T: Single Enable							
Z: Complementary w/o Enable	X: Single w/o Enable							
Symmetry/Output Logic Type								
L: 45/55% LVDS	P: 45/55% PECL							
H: 40/60% LVDS	Q: 40/60% PECL							
Package/Lead Configurations								
J: J-lead								
RoHS Compliance								
Blank: non-RoHS compliant part								
-R: RoHS compliant part								
Frequency (customer specified)								

1. Calibration, deviation over temperature, shock, vibration, and aging.
2. PECL load - see load circuit diagram #5. LVDS load - see load circuit diagram #9.

Electrical Specifications	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
	Frequency Range	F	0.75		800	MHz	
	Operating Temperature	T _A	(See Ordering Information)				
	Storage Temperature	T _s	-55		+125	°C	
	Frequency Stability	ΔF/F	(See Ordering Information)				
	Aging						
	1st Year			±2	ppm		
	Thereafter (per year)			±1	ppm		
	Input Voltage	V _{cc}	3.135	3.3	3.465	V	
	PECL Input Current	I _{cc}			60	mA	0.75 to 24 MHz
					95	mA	24 to 96 MHz
					105	mA	96 to 800 MHz
	LVDS Input Current	I _{cc}			30	mA	0.75 to 24 MHz
					60	mA	24 to 800 MHz
	Output Type						PECL/LVDS
	Load		50 Ohms to V _{cc} -2 VDC 100 Ohm differential load				See Note 2 PECL Waveform LVDS Waveform
	Symmetry (Duty Cycle)		(See Ordering Information)				@ V _{cc} -1.3 VDC (LVPECL) @ 50% of waveform (LVDS)
	Output Skew				200	ps	PECL
	Differential Voltage		250	340	450	mV	LVDS
	Logic "1" Level	V _{oh}	V _{cc} -1.02			V	PECL
	Logic "0" Level	V _{ol}			V _{cc} -1.63	V	PECL
	Rise/Fall Time	T _r /T _f		0.35 .50	0.55 1.0	ns ns	@ 20/80% LVPECL @ 20/80% LVDS
	Enable Function		80% V _{cc} min. Or N/C: output active 20% V _{cc} max.: output disables to high-Z				"R" & "T" output types
	Start up Time			5		ms	
	Phase Jitter	φ _J		3	5	ps RMS	Integrated 12 kHz - 20 MHz

1. Calibration, deviation over temperature, shock, vibration, and aging.
2. PECL load - see load circuit diagram #5. LVDS load - see load circuit diagram #9.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

MtronPTI Lead Free Solder Profile

