


0.510 INCH (13 MM) SEVEN SEGMENT DISPLAYS

**YELLOW MAN5350/5360
GREEN MAN5450/5460**

**RED MAN5750/5760
ORANGE-RED MAN5950/5960**



FEATURES

- Large, easy to read, digits
- Common anode or common cathode models
- Fast switching - excellent for multiplexing
- Low power consumption
- Bold solid segments that are highly legible
- Solid state reliability - long operation life
- Rugged plastic construction
- Directly compatible with integrated circuits
- High brightness with high contrast
- Categorized for luminous intensity (see Note 5)
- Wide angle viewing . . . 150°
- Low forward voltage
- Untinted segments on grey face

DESCRIPTION

This display series is a family of large digits 0.510 inches in height. All models have right hand decimal points and are available in common anode or common cathode configurations. All units are constructed with untinted segments on grey face to enhance ON/OFF contrast. Standard units are available in red, orange-red, green and yellow.

APPLICATIONS

For industrial and consumer applications such as:

- Digital readout displays
- Instrument panels
- Point of sale equipment
- Digital clocks
- TV and radios

MODEL NUMBERS

PART NUMBER	COLOR	DESCRIPTION	PIN OUT SPECIFICATION (See Page 5)
MAN5350	Yellow	Common Anode	A
MAN5360	Yellow	Common Cathode	B
MAN5450	Green	Common Anode	A
MAN5460	Green	Common Cathode	B
MAN5750	Red	Common Anode	A
MAN5760	Red	Common Cathode	B
MAN5950	Orange-Red	Common Anode	A
MAN5960	Orange-Red	Common Cathode	B



**0.510 INCH (13 MM)
SEVEN SEGMENT DISPLAYS**

ELECTRO-OPTICAL CHARACTERISTICS (TA = 25° Unless Otherwise Specified)

	MIN.	TYP.	MAX.	UNITS	TEST CONDITION
YELLOW MAN5350/MAN5360					
Luminous Intensity, digit average (See Note 1)	820	1200 480		μ cd μ cd	$I_f=10$ mA $I_f=5$ mA
Peak emission wavelength		585		nm	$I_f=10$ mA
Dominant wavelength	582		593	nm	$I_f=10$ mA
Spectral line half width		40		nm	
Forward voltage	2.4		3.0	V	$I_f=20$ mA
Dynamic resistance		26			$I_f=20$ mA
Capacitance		35		pF	$V_h=0$, f=1MHz
Reverse current			10	μ A	$V_h=6.0$ V
GREEN MAN5450/MAN5460					
Luminous Intensity, digit average (See Note 1)	820	3000 1000		μ cd μ cd	$I_f=10$ mA $I_f=5$ mA
Peak emission wavelength		562		nm	$I_f=10$ mA
Dominant wavelength	564		574	nm	$I_f=10$ mA
Spectral line half width		30		nm	
Forward voltage	2.4		3.0	V	$I_f=20$ mA
Dynamic resistance		12			$I_f=20$ mA
Capacitance		40		pF	$V_h=0$, f=1MHz
Reverse current			10	μ A	$V_h=6.0$ V



**0.510 INCH (13 MM)
SEVEN SEGMENT DISPLAYS**

ELECTRO-OPTICAL CHARACTERISTICS ($T_A = 25^\circ$ Unless Otherwise Specified)				
	MIN.	TYP.	MAX.	UNITS
TEST CONDITION				
RED MAN5750/MAN5760				
Luminous Intensity, digit average (See Note 1)	280	500	250	μcd μcd
Peak emission wavelength	655			nm
Dominant wavelength	645			nm
Spectral line half width	20			nm
Forward voltage	1.6	2.0	2.0	V
Dynamic resistance	2			$I_F=20 \text{ mA}$
Capacitance	35			pF
Reverse current	10			$V_R=6.0 \text{ V}$
ORANGE-RED MAN5950/MAN5960				
Luminous Intensity, digit average (See Note 1)	820	2500	700	μcd μcd
Peak emission wavelength	635			nm
Dominant wavelength	615	630		nm
Spectral line half width	40			nm
Forward voltage	2.0	3.0	2.0	V
Dynamic resistance	26			$I_F=20 \text{ mA}$
Capacitance	35			pF
Reverse current	10			$V_R=6.0 \text{ V}$



0.510 INCH (13 MM) SEVEN SEGMENT DISPLAYS

ABSOLUTE MAXIMUM RATINGS

	MAN5350 MAN5360	MAN5450 MAN5460	MAN5750 MAN5760	MAN5950 MAN5960
Power Dissipation at 25°C Ambient	600 mW	570 mW	480 mW	600 mW
Derate linearly from 50°C	-10.3 mW/°C	-12 mW/°C	-6.9 mW/°C	-8.6 mW/°C
Storage and operating temperature	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Continuous forward current				
Total	200 mA	240 mA	240 mA	240 mA
Per segment	25 mA	30 mA	30 mA	30 mA
Decimal point	25 mA	30 mA	30 mA	30 mA
Reverse voltage				
Per segment	6.0 V	6.0 V	6.0 V	6.0 V
Decimal point	6.0 V	6.0 V	6.0 V	6.0 V
Soldering time at 260°C (See Notes 3 and 4)	5 sec.	5 sec.	5 sec.	5 sec.


NOTES

1. The digit average Luminous Intensity is obtained by summing the Luminous Intensity of each segment and dividing by the total number of segments. Intensity will not vary more than $\pm 33.3\%$ between all segments within a digit.
2. The relative luminous intensity in this curve is normalized to the brightness at 25°C to indicate the relative efficiency over the operating temperature range.
3. Leads of the device immersed to 1/16 inch from the body. Maximum device surface temperature is 140°C.
4. For flux removal, Freon TF, Freon TE, Isopropanol or water may be used up to their boiling points.
5. All displays are categorized for Luminous Intensity. The intensity category is marked on each part as a suffix letter to the part number.

RECOMMENDED OPTICAL FILTERS


For optimum ON and OFF contrast, one of the following filters or equivalents should be used over the display:

DEVICE TYPE	FILTER	DEVICE TYPE	FILTER
MAN5350	Panelgraphic Yellow 25 or Amber 23 Homalite 100-1720 or 100-1726	MAN5450	Panelgraphic Green 48 Homalite 100-1440 Green
MAN5360	Panelgraphic Grey 10 Homalite 100-1266 Grey	MAN5460	Panelgraphic Grey 10 Homalite 100-1266 Grey
MAN5750	Panelgraphic Red 60	MAN5950	Panelgraphic Scarlet 65
MAN5760	Homalite 100-1605	MAN5960	Homalite 100-1670



0.510 INCH (13 MM) SEVEN SEGMENT DISPLAYS

PACKAGE DIMENSIONS




NOTE: Dimensions in inches (mm)
Tolerances $\pm 0.010"$ unless otherwise specified


ELECTRICAL CONNECTIONS

PIN NO.	A MAN 5 X 50	B MAN 5 X 60
1	Cathode E	Anode E
2	Cathode D	Anode D
3	Com. Anode	Com. Cathode
4	Cathode C	Anode C
5	Cathode D.P.	Anode D.P.
6	Cathode B	Anode B
7	Cathode A	Anode A
8	Com. Anode	Com. Cathode
9	Cathode F	Anode F
10	Cathode G	Anode G


INTERNAL CONNECTIONS



MAN 5 X 50



MAN 5 X 60



0.510 INCH (13 MM) SEVEN SEGMENT DISPLAYS

TYPICAL CHARACTERISTIC CURVES






Fig. 1A. Relative Luminous Intensity vs. DC Forward Current

Fig. 1B. Forward Current vs. Forward Voltage

Fig. 1C. Relative Luminous Intensity vs. Temperature (See Note 2)





Fig. 1D. Max Peak Current vs. Duty Cycle

Fig. 1E. Relative Luminous Intensity vs. Duty Cycle

FIGURE 1: MAN5350/MAN5360






Fig. 2A. Relative Luminous Intensity vs. Forward Current

Fig. 2B. Forward Current vs. Forward Voltage

Fig. 2C. Relative Luminous Intensity vs. Temperature (See Note 2)






Fig. 2D. Relative Efficiency vs. Duty Cycle

Fig. 2E. Maximum Peak Current vs. Pulse Duration

FIGURE 2: MAN5450/MAN5460



0.510 INCH (13 MM) SEVEN SEGMENT DISPLAYS

TYPICAL CHARACTERISTIC CURVES






Fig. 3A. Relative Luminous Intensity vs. DC Forward Current

Fig. 3B. Forward Current vs. Forward Voltage

Fig. 3C. Relative Luminous Intensity vs. Temperature (See Note 2)




Fig. 3D. Max Peak Current vs. Duty Cycle




Fig. 3E. Relative Luminous Intensity vs. Duty Cycle

FIGURE 3: MAN5750/MAN5760






Fig. 4A. Relative Luminous Intensity vs. Forward Current

Fig. 4B. Forward Current vs. Forward Voltage

Fig. 4C. Relative Luminous Intensity vs. Temperature (See Note 2)




Fig. 4D. Maximum Peak Current vs. Duty Cycle




Fig. 4E. Relative Luminous Intensity vs. Duty Cycle

FIGURE 4: MAN5950/MAN5960