

Schottky Barrier Rectifier

MBR3060

FEATURES



- Low forward voltage
- Guarding for stress protection
- 150°C operating junction temperature
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

MECHANICAL CHARACTERISTICS

- Case: TO-220 package
- Mounting position: Any

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{RRM}	Peak Repetitive Reverse Voltage	60	V
V _{RMS}	Maximum RMS Voltage	42	V
V _{DC}	Maximum DC Blocking Voltage	60	V
I _{F(AV)}	Average Rectified Forward Current	30	A
I _{FSM}	Peak Forward Surge Current, 8.3 ms single halfsine-wave superimposed on rated load (JEDEC method)	300	A
T _J	Junction Temperature	-65~150	°C
T _{stg}	Storage Temperature Range	-65~150	°C



Schottky Barrier Rectifier**MBR3060****THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	1.4	°C/W
R _{th j-a}	Thermal Resistance, Junction to Ambient	40	°C/W

ELECTRICAL CHARACTERISTICS(Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 1%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V _F	Maximum Instantaneous Forward Voltage	I _F = 15A	0.75	V
I _R	Maximum Instantaneous Reverse Current	Rated DC Voltage, T _C = 25°C Rated DC Voltage, T _C = 100°C	5.0 50	mA

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.