

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

### MBR545F

# 5 Amp Schottky Barrier Rectifier 45 Volts

## **Features**

- Low Forward Voltage Drop
- High frequency properties and switching speed
- High Current Capability
- Guard Ring for over-voltage protection
- Case Material: Molded plastic UL Flammability Classification Rating 94V-0


# **Maximum Ratings**

- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C
- Maximum Thermal Resistance, Rthjc: 4.5°C/W

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBR545F	MBR545F	45V	31.5V	45V

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	5 A	T <sub>C</sub> = 120°C
Peak Forward Surge Current	I <sub>FSM</sub>	80A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V <sub>F</sub>	0.55V 0.49V	I <sub>F</sub> = 5A; T <sub>C</sub> = 25°C I <sub>F</sub> = 5A; T <sub>C</sub> =125°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	1mA 40mA	T <sub>C</sub> = 25°C T <sub>C</sub> = 125°C



		DIME	NSIONS		
	INCH	HES	ES MM		
DIM	MIN	MAX	MIN	MAX	
Α	.583	.606	14.80	15.40	
В		.406		10.30	
С	.100	.112	2.55	2.85	
D	.248	.272	6.30	6.90	
Е		.161		4.10	
F	.512	.543	13.00	13.80	
G	.200		5.10		
Н		.035		0.90	
- 1		.032		0.80	
J	.118	.134	3.00	3.40	Ø
K		.189		4.80	
L		.123		3.10	
М	.098	.114	2.50	2.90	



## **MBR545F**

### **Typical Characteristics**




Figure 1. Typical Forward Voltage Characteristics




Figure 3. Typical Junction Capacitance




Figure 5. Forward Current Derating Curve




Figure 2. Typical Reverse Current vs. Reverse Voltage




Figure 4. Thermal Impedance Characteristics




Figure 6. Non-Repetitive Surge Current



**Micro Commercial Components** 

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.