

isc Silicon NPN Power Transistor

MD2310FX

DESCRIPTION

- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 700V$ (Min)
- High Switching Speed
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Horizontal deflection output for monitor and real flat TV
- Switch mode power supplies for CRT TV

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	1500	V
V_{CEO}	Collector-Emitter Voltage	700	V
V_{EBO}	Emitter-Base Voltage	9	V
I_C	Collector Current- Continuous	14	A
I_{CM}	Collector peak current ($t_p < 5ms$)	21	A
I_B	Base Current- Continuous	7	A
P_{TOT}	Total dissipation at $T_C=25^\circ C$	62	W
T_J	Junction Temperature	150	$^\circ C$
T_{stg}	Storage Temperature Range	-65~150	$^\circ C$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th j-c}$	Thermal Resistance, Junction to Case	2.0	$^\circ C/W$



isc Silicon NPN Power Transistor**MD2310FX****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(sus)} ⁽¹⁾	Collector-emitter sustaining Voltage	I _C = 50mA; I _C = 0	700			V
V _{CE(sat)} ⁽¹⁾	Collector-Emitter Saturation Voltage	I _C = 7.0A; I _B =1.75A			2.5	V
V _{BE(sat)} ⁽¹⁾	Base-Emitter Saturation Voltage	I _C = 7.0A; I _B =1.75A			1.1	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 1500V ; I _E = 0 V _{CB} = 1500V ; I _E = 0 ,TC=125			0.2 2	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 9V ; I _C = 0			1	mA
h _{FE-1} ⁽¹⁾	DC Current Gain	I _C =1A ; V _{CE} = 5V		28		
h _{FE-2} ⁽¹⁾	DC Current Gain	I _C = 7A ; V _{CE} = 1V		5.5		
h _{FE-3} ⁽¹⁾	DC Current Gain	I _C = 7A ; V _{CE} = 5V	6		8.5	

Switching times

t _s	Storage Time	I _{CP} = 6A , I _{B(on)} = 0.9A ; f _H = 64kHz V _{BE(off)} = -2.7V, L _{BB(OFF)} =1.6uH		2.3	2.8	μs
t _f	Fall Time			0.12	0.25	μs

1. Pulsed duration =300us,duty cycle ≤1.5%

Notice:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.