



Military-Fasteners.com

MS16995-39 SOCKET HEAD SCREW SPEC

Description:

Fastener Length: 7/8", Thread: 10-24, Head Width: 5/32", Thread Length: 7/8"

MS16995-39 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-988-7610
NIIN:	009887610
FSC:	Screws / 5305
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

See page 2 for technical characteristics

MS16995-39 Specifications

End Item Identification:	Mrap Rg-33; Mrap Rg-33 Auv
Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Hardness Rating:	80.0 Rockwell B Minimum Overall
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Head Style:	Flat Chamfer
Material:	Steel Corrosion Resisting Overall
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Nondefinitive Spec/std Data:	6 Type
Internal Drive Style:	Hexagon
Material Document And Classification:	66 Fed Std Single Material Response Overall
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.762 Inches Minimum And 0.875 Inches Maximum
Thread Quantity Per Inch:	24
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/MS16995-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.