

Description

The MSL-194BV, a BLUE source Chip LED device, is designed in an indnstry standard package suitable for SMT assembly method. It utilizes GaN on SiC LED chip technology and water clear epoxy package.

Applications

- Small Size
- Industry Standard Footprint(0603)
- Compatible with IR Solder process
- Availalble in 8 mm Tape on 7"(178mm)

Diameteer Reels


Features

- Push-Button Backlighting
- LCD Backlighting
- Symbol Backlighting
- Front Panel Indicator


Absolute Maximum Ratings

Parameter	Symbol	Maximum Rating	Unit
Peak Forward Current(1/10 Duty Cycle@1KHz)	I _{FP}	70	mA
DC Forward Current	I _F	30	mA
Power Dissipation	P _D	140	mW
Reverse Voltage	V _R	5	V
Operating Temperature Range	T _{OPR}	-20°C to +80°C	
Storage Temperature Range	T _{STG}	-30°C to +100°C	
Electrostatic Discharge Threshold	E _{OT}	1000	V

Package Dimensions



Recommended Solder Patterns



- NOTE:
1. All dimensions are in millimeter (inches)
 2. Tolerance is $\pm 0.1\text{mm}$ (.004") unless otherwise specified.

@ T_A=25°C

Optical-Electrical Characteristics

@ $T_A=25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Min .	Typ .	Max .	Unit .
Luminous Intensity	$I_F=20\text{mA}$	I_V	4	8	-	mcd
Forward Voltage	$I_F=20\text{mA}$	V_F	-	3.8	4.5	V
Reverse Current	$V_R=5\text{V}$	I_R	-	-	10	μA
Peak/Dominant Wavelength	$I_F=20\text{mA}$	λ_p/λ_d	-	428/466	-	nm
Spectral Linewidth	$I_F=20\text{mA}$	$\Delta\lambda$	-	65	-	nm
Viewing Angle	$I_F=20\text{mA}$	$2\theta_{1/2}$	-	130	-	deg.

Typical Optical-Electrical Characteristic Curves




FIG.1 RELATIVE INTENSITY LUMINOUS VS. WAVELENGTH




FIG.2 FORWARD CURRENT VS. FORWARD VOLTAGE




FIG.3 FORWARD CURRENT VS. AMBIENT TEMPERATURE




FIG.4 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




FIG.5 LUMINOUS INTENSITY VS. AMBIENT TEMPERATURE




FIG.6 RADIATION DIAGRAM