

### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

32K x 36 SRAM

AND OUTPUTS AND BURST COUNTER

+3.3V SUPPLY, FULLY REGISTERED INPUTS

**PIN ASSIGNMENT (Top View)** 

100-Pin TQFP

(SC-1)

100 99 98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81

DQP3 

DQ17

**DQ18** 

Vcca

Vssq DQ19 DQ20

DQ21

Vssa ΗH 10

Vccq DQ23 DQ24 12

NC 

Vcc 

NC HH 16

Vss

DQ25

DQ26 19

Vcca

Vssq 

DQ28

DQ29 П

DQ30 25

Vssa

Vccq Η 27

DQ31 H 28

DQ32

DQP4

**HHH** 

6 **F**T

DQ22

> ETT. 13

> 18

DQ27

> 26

m

15

20

21

22

23

24

29

3

()

# SYNCHRONOUS SRAM

### **FEATURES**

- Fast access times: 7, 10, 12 and 15ns
- Fast OE: 5, 6, 7 and 8ns ٠
- Single  $+3.3V \pm 5\%$  power supply •
- 5V-tolerant I/O ٠
- · Common data inputs and data outputs
- Individual BYTE WRITE control ٠
- Three chip enables for simple depth expansion
- ٠ Clock controlled, registered, address, data I/O and control for fully pipelined applications
- Internally self-timed WRITE cycle
- WRITE pass-through capability •
- Burst control pins (486/Pentium<sup>™</sup> burst sequence) .
- 100-lead TQFP package for high density, high speed
- ٠ Low capacitive bus loading
- High 30pF output drive capability at rated access time ٠
- ٠ Parity Disable function for 32-bit operation

### **OPTIONS** MARKING Timing 7ns access/15ns cycle - 7 10ns access/20ns cycle -10 12ns access/25ns cycle -12 15ns access/30ns cycle -15 Packages 100-pin TQFP LG

Part Number Example: MT58LC32K36C4LG-10

NOTE: Not all combinations of operating temperature, speed, data retention and low power are necessarily available. Please contact the factory for availability of specific part number combinations.

### **GENERAL DESCRIPTION**

The Micron Synchronous SRAM family employs highspeed, low-power CMOS designs using a four-transistor memory cell. Micron SRAMs are fabricated using doublelayer metal, double-layer polysilicon technology.

The MT58LC32K36C4SRAM integrates a 32K x 36SRAM core with advanced synchronous peripheral circuitry, a 2bit burst counter and output register. All synchronous inputs pass through registers controlled by a positive-edgetriggered single clock input (CLK). The synchronous inputs include all addresses, all data inputs, active LOW chip enable, two additional chip enables for easy depth expansion (CE2, CE2), burst control inputs (ADSC, ADSP, ADV) and the byte write enables (BW1, BW2, BW3, BW4).

31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50

ННННН

Asynchronous inputs include the output enable (OE) and the clock (CLK). The data-out (Q), enabled by  $\overline{OE}$ , is also asynchronous. The output register is controlled by the clock. WRITE cycles can be from one to four bytes wide as controlled by the byte write enables.

Burst operation can be initiated with either address status processor (ADSP) or address status controller (ADSC) input pins. Subsequent burst addresses can be internally generated as controlled by the burst advance pin (ADV).

NEW N **3.3 VOLT SYNCHRONOUS SRAN** 

DQP2

79

78 77

76 HHH

75 74

51 -

HHHF

DQ16

DQ12

1 Vssq Vccq HHH

-Vss NC

H

NC

H 002

DQ15 Vccq Vssq DQ14

DQ13

DQ11

DQ10 DQ9

Vcc

DQ8

DQ7

Vssq DQ6

DQ5

DQ4

DQ3

Vssa

Vccq

DQ1

DQP1

Vccq

### **GENERAL DESCRIPTION (continued)**

MICRON

Address and write control are registered on-chip to simplify WRITE cycles. This allows self-timed WRITE cycles. Individual byte enables allow individual bytes to be written. WRITE pass-through makes written data immediately available at the output register during the READ cycle following a WRITE as controlled solely by  $\overline{\text{OE}}$  to improve cache system response.

The MT58LC32K36C4 operates from a +3.3V power supply and all inputs and outputs are TTL compatible and 5V tolerant. The device is ideal for Pentium (P5) pipelined applications and 32-, 64- and 72-bit-wide applications.

### FUNCTIONAL BLOCK DIAGRAM



NOTE: 1. The Functional Block Diagram illustrates simplified device operation. See Truth Table, pin descriptions and timing diagrams for detailed information.



## MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

### **PIN DESCRIPTIONS**

TQFP PIN NUMBERS	SYMBOL	TYPE	DESCRIPTION
37, 36, 35, 34, 33, 32, 100, 99, 82, 81, 44, 45, 46, 47, 48	A0-A14	Input	Synchronous Address Inputs: These inputs are registered and must meet the setup and hold times around the rising edge of CLK.
93, 94, 95, 96	<u>BW1, BW2,</u> BW3, BW4	Input	Synchronous Byte Write Enables: These active LOW inputs allow individual bytes to be written and must meet the setup and hold times around the rising edge of CLK. A byte write enable is LOW for a WRITE cycle and HIGH for a READ cycle.BW1 controls DQ1-DQ8 and DQP1. BW2 controls DQ9-DQ16 and DQP2. BW3 controls DQ17-DQ24 and DQP3. BW4 controls DQ25-DQ32 and DQP4. Data I/O are tristated if any of these four inputs are LOW.
89	CLK	Input	Clock: This signal registers the address, data, chip enables, byte write enables and burst control inputs on its rising edge. All synchronous inputs must meet setup and hold times around the clock's rising edge.
98	CE	Input	Synchronous Chip Enable: This active LOW input is used to enable the device and conditions internal use of ADSP. This input is sampled only when a new external address is loaded.
92	CE2	Input	Synchronous Chip Enable: This active LOW input is used to enable the device. This input is sampled only when a new external address is loaded. This input can be used for memory depth expansion.
97	CE2	Input	Synchronous Chip Enable: This active HIGH input is used to enable the device. This input is sampled only when a new external address is loaded. This input can be used for memory depth expansion.
86	ŌĒ	Input	Output Enable: This active LOW asynchronous input enables the data I/O output drivers.
83	ĀDV	Input	Synchronous Address Advance: This active LOW input is used to advance the internal burst counter, controlling burst access after the external address is loaded. A HIGH on this pin effectively causes wait states to be generated (no address advance). This pin must be HIGH at the rising edge of the first clock after an ADSP cycle is initiated if a WRITE cycle is desired (to ensure use of correct address).
84	ADSP	Input	Synchronous Address Status Processor: This active LOW input interrupts any ongoing burst, causing a new external address to be registered. A READ is performed using the new address, independent of the byte write enables and $\overline{ADSC}$ but dependent upon CE2 and $\overline{CE2}$ . $\overline{ADSP}$ is ignored if $\overline{CE}$ is HIGH. Power-down state is entered if CE2 is LOW or $\overline{CE2}$ is HIGH.
85	ADSC	Input	Synchronous Address Status Controller: This active LOW input interrupts any ongoing burst and causes a new external address to be registered. A READ or WRITE is performed using the new address if all chip enables are active. Power- down state is entered if one or more chip enables are inactive.



**PIN DESCRIPTIONS (continued)** 

**IRON** 

MIC

TQFP PIN NUMBERS	SYMBOL	TYPE	DESCRIPTION
14, 16, 31, 38, 39, 42, 43, 49, 50, 64, 66, 88	NC	-	No Connect: These signals are not internally connected.
52, 53, 56, 57, 58, 59, 62, 63 68, 69, 72, 73, 74, 75, 78, 79, 2, 3, 6, 7, 8, 9, 12, 13, 18, 19, 22, 23, 24, 25, 28, 29	DQ1-DQ32	Input/ Output	SRAM Data I/O: Byte 1 is DQ1-DQ8; Byte 2 is DQ9-DQ16; Byte 3 is DQ17-DQ24; Byte 4 is DQ25-DQ32. Input data must meet setup and hold times around the rising edge of CLK.
51, 80, 1, 30	DQP1-DQP4	Input/ Output	Parity Data I/O: Byte 1 Parity is DQP1; Byte 2 Parity is DQP2; Byte 3 Parity is DQP3; Byte 4 Parity is DQP4.
87	PDIS	Input	Parity Disable: When HIGH, this input disables DQP1 through DQP4 for 32-bit data bus width. A LOW on PDIS enables control of DQP1 through DQP4 in the same manner as DQ1-DQ32 are controlled.
15, 41, 65, 91	Vcc	Supply	Power Supply: +3.3V ±5%
17, 40, 67, 90	Vss	Supply	Ground: GND
4, 11, 20, 27, 54, 61, 70, 77	VccQ	Supply	Isolated Output Buffer Supply: +3.3V ±5%
5, 10, 21, 26, 55, 60, 71, 76	VssQ	Supply	Isolated Output Buffer Ground: GND

### **PASS-THROUGH TRUTH TABLE**

PREVIOUS CYCLE		PRESENT CYC	NEXT CYCLE			
OPERATION	BWs	OPERATION	CE	BWs	ŌE	OPERATION
Initiate WRITE cycle, all bytes Address = A(n-1), data = D(n-1)	All L	Initiate READ cycle Register A(n), Q = D(n-1)	L	Н	L	Read D(n)
Initiate WRITE cycle, all bytes Address = A(n-1), data = D(n-1)	All L	No new cycle Q = D(n-1)	н	Н	L	No carryover from previous cycle
Initiate WRITE cycle, all bytes Address = $A(n-1)$ , data = $D(n-1)$	Ali L	No new cycle Q = HIGH-Z	н	Н	Н	No carryover from previous cycle
Initiate WRITE cycle, one byte Address = A(n-1), data = D(n-1)	One L	No new cycle $Q = D(n-1)$ for one byte	Н	Н	L	No carryover from previous cycle

NOTE: Previous cycle may be either BURST or NONBURST cycle.

### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

### BURST SEQUENCE TABLE

	Address Used							
Operation	A14-A2	A1	AO					
First access, register external address	A14-A2	A1	A0					
Second access (first burst address)	registered A14-A2	registered A1	registered A0					
Third access (second burst address)	registered A14-A2	registered A1	registered A0					
Fourth access (third burst address)	registered A14-A2	registered A1	registered A0					

NOTE: The burst sequence wraps around to its initial state upon completion.

RON

### **BURST ADDRESS TABLE**

First Address	Second Address	Third Address	Fourth Address
XX00	XX01	XX10	XX11
XX01	XX00	XX11	XX10
XX10	XX11	XX00	XX01
XX11	XX10	XX01	XX00
(a) A start of the property of the second s second second seco			

# NEW 3.3 VOLT SYNCHRONOUS SRAM



### TRUTH TABLE

OPERATION	ADDRESS USED	CE	CE2	CE2	ADSP	ADSC	ADV	WRITE	ŌE	CLK	DQ
Deselected Cycle, Power-down	None	н	Х	Х	Х	L	Х	Х	Х	L-H	High-Z
Deselected Cycle, Power-down	None	L	Х	L	L	Х	X	Х	Х	L-H	High-Z
Deselected Cycle, Power-down	None	L	Н	Х	L	Х	Х	Х	Х	L-H	High-Z
Deselected Cycle, Power-down	None	L	Х	L	Н	L	Х	Х	Х	L-H	High-Z
Deselected Cycle, Power-down	None	L	Н	Х	Н	L	Х	Х	Х	L-H	High-Z
READ Cycle, Begin Burst	External	L	L	н	L	Х	Х	Х	L	L-H	Q
READ Cycle, Begin Burst	External	L	L	н	L	Х	Х	Х	н	L-H	High-Z
WRITE Cycle, Begin Burst	External	L	L	н	Н	L	Х	L	Х	L-H	D
READ Cycle, Begin Burst	External	L	L	н	Н	L	Х	Н	L	L-H	Q
READ Cycle, Begin Burst	External	L	L	н	Н	L	Х	Н	н	L-H	High-Z
READ Cycle, Continue Burst	Next	Х	Х	Х	Н	Н	L	н	L	L-H	Q
READ Cycle, Continue Burst	Next	Х	Х	Х	Н	Н	L	Н	н	L-H	High-Z
READ Cycle, Continue Burst	Next	н	Х	Х	Х	Н	L	Н	L	L-H	Q
READ Cycle, Continue Burst	Next	Н	Х	Х	Х	Н	L	Н	н	L-H	High-Z
WRITE Cycle, Continue Burst	Next	Х	Х	Х	Н	Н	L	L	Х	L-H	D
WRITE Cycle, Continue Burst	Next	Н	Х	Х	Х	Н	L	L	Х	L-H	D
READ Cycle, Suspend Burst	Current	Х	Х	Х	н	Н	н	Н	L	L-H	Q
READ Cycle, Suspend Burst	Current	Х	Х	Х	Н	Н	Н	Н	н	L-H	High-Z
READ Cycle, Suspend Burst	Current	Н	Х	Х	X	Н	н	Н	L	L-H	Q
READ Cycle, Suspend Burst	Current	Н	Х	Х	Х	Н	Н	Н	Н	L-H	High-Z
WRITE Cycle, Suspend Burst	Current	Х	Х	Х	Н	Н	Н	L	Х	L-H	D
WRITE Cycle, Suspend Burst	Current	Н	Х	Х	Х	Н	Н	L	Х	L-H	D

- NOTE: 1. X means "don't care." H means logic HIGH. L means logic LOW. WRITE=L means any one or more byte write enable signals (BW1, BW2, BW3 or BW4) are LOW. WRITE=H means all byte write enable signals are HIGH.
  - 2. BW1 enables writes to Byte 1 (DQ1-DQ8, DQP1). BW2 enables writes to Byte 2 (DQ9-DQ16, DQP2). BW3 enables writes to Byte 3 (DQ17-DQ24, DQP3). BW4 enables writes to Byte 4 (DQ25-DQ32, DQP4).
  - 3. All inputs except OE must meet setup and hold times around the rising edge (LOW to HIGH) of CLK.
  - 4. Wait states are inserted by suspending burst.
  - 5. For a write operation following a read operation, OE must be HIGH before the input data required setup time and held HIGH throughout the input data hold time.
  - 6. This device contains circuitry that will ensure the outputs will be in High-Z during power-up.
  - 7. PDIS disables the DQP lines when HIGH and enables the DQP lines when LOW.
  - ADSP LOW always initiates an internal READ at the L-H edge of CLK. A WRITE is performed by setting one or more byte write enable signals LOW for the subsequent L-H edge of CLK. Refer to WRITE timing diagram for clarification.

Π

<

**3.3 VOLT SYNCHRONOUS SRAM** 



### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

### **ABSOLUTE MAXIMUM RATINGS\***

Voltage on Vcc Supply Relative to Vss	0.5V to +4.6V
VIN	0.5V to +6V
Storage Temperature (plastic)	55°C to +150°C
JunctionTemperature	+150°C
Power Dissipation	1.6W
Short Circuit Output Current	100mA

\*Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

### ELECTRICAL CHARACTERISTICS AND RECOMMENDED DC OPERATING CONDITIONS

(0°C  $\leq$  T\_A  $\leq$  70°C; T\_C  $\leq$  110°C; Vcc = 3.3V ±5% unless otherwise noted)

DESCRIPTION	CONDITIONS	SYMBOL	MIN	MAX	UNITS	NOTES
Input High (Logic 1) Voltage		Viн	2.0	5.5	V	1, 2
Input Low (Logic 0) Voltage		ViL	-0.3	0.8	V	1, 2
Input Leakage Current	$0V \le V_{IN} \le V_{CC}$	IL	-1	1	μΑ	
Output Leakage Current	Output(s) disabled, 0V ≤ Vou⊤ ≤ Vcc	ILo	-1	1	μA	
Output High Voltage	Іон = -4.0mA	Vон	2.4	·. · ·	V	1. J
Output Low Voltage	IoL = 8.0mA	Vol		0.4	V	1
Supply Voltage		Vcc	3.1	3.5	V	1.1

					М	AX			
DESCRIPTION	CONDITIONS	SYMBOL	TYPICAL	-7	-10	-12	-15	UNITS	NOTES
Power Supply Current: Operating	Device selected; all inputs $\leq$ VIL or $\geq$ VIH; cycle time $\geq$ <sup>t</sup> KC min; Vcc = MAX; outputs open	Icc	200	275	250	225	200	mA	3, 12, 13
Power Supply Current: Idle	Device selected; ADSC, ADSP, ADV ≥ Viн; all inputs ≤ Vi∟ oR ≥ Viн; Vcc = MAX; cycle time ≥ <sup>t</sup> KC min	ISB1	50	85	70	60	55	mA	12, 13
CMOS Standby	Device deselected; Vcc = MAX; all inputs $\leq$ Vss +0.2 or $\geq$ Vcc -0.2; all inputs static; CLK frequency = 0	ISB2	0.2	2	2	2	2	mA	12, 13
TTL Standby	Device deselected; all inputs $\leq$ VIL OR $\geq$ VIH; all inputs static; Vcc = MAX; CLK frequency = 0	ISB3	10	18	18	18	18	mA	12, 13
Clock Running	Device deselected; all inputs $\leq$ VIL OR $\geq$ VIH; Vcc = MAX; CLK cycle time $\geq$ <sup>t</sup> KC min	ISB4	20	35	30	25	20	mA	12, 13

### CAPACITANCE

DESCRIPTION	CONDITIONS	SYMBOL	ТҮР	MAX	UNITS	NOTES
Input Capacitance	T <sub>A</sub> = 25°C; f = 1 MHz	Cı	3	4	pF	4
Input/Output Capacitance (DQ)	Vcc = 3.3V	Co	5	6	pF	4

### THERMAL CONSIDERATIONS

DESCRIPTION	CONDITIONS	SYMBOL	ТҮР	UNITS	NOTES
Thermal resistance - Junction to Ambient	Still Air	θ <sub>JA</sub>	65	°C/W	
Thermal resistance - Junction to Case		θ <sub>JC</sub>	6	°C/W	
Maximum Case Temperature		TC	110	°C	11



### ELECTRICAL CHARACTERISTICS AND RECOMMENDED AC OPERATING CONDITIONS

(Note 5) (0°C  $\leq$  T<sub>A</sub>  $\leq$  70°C; Vcc = 3.3V  $\pm$ 5%)

		-	7	-1	10	-12		-1	15		
DESCRIPTION	SYM	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	UNITS	NOTES
Clock											
Clock cycle time	<sup>t</sup> KC	15		20		25		30		ns	
Clock HIGH time	<sup>t</sup> KH	5		7		9		11		ns	
Clock LOW time	<sup>t</sup> KL	5		7		9		11		ns	
Output Times											
Clock to output valid	<sup>t</sup> KQ		7		10		12		15	ns	
Clock to output invalid	<sup>t</sup> KQX	3		3		3		3		ns	
Clock to output in Low-Z	<sup>t</sup> KQLZ	2		2		2		2		ns	6, 7
Clock to output in High-Z	<sup>t</sup> KQHZ		5		6		6		6	ns	6, 7
OE to output valid	<sup>t</sup> OEQ		5		6		7		8	ns	9
OE to output in Low-Z	<sup>t</sup> OELZ	0		.0		0		0		ns	6, 7
OE to output in High-Z	<sup>t</sup> OEHZ		5		6		6		6	ns	6, 7
Setup Times											
Address	<sup>t</sup> AS	2.5		3		3	-	3		ns	8, 10
Address Status (ADSC, ADSP)	<sup>t</sup> ADSS	2.5		3		3		3		ns	8, 10
Address Advance ( ADV)	<sup>t</sup> AAS	2.5		3		3		3		ns	8, 10
Byte Write Enables (BW1, BW2, BW3, BW4)	tWS	2.5		3		3		3		ns	8, 10
Data-in	<sup>t</sup> DS	2.5		3		3		3		ns	8, 10
Chip Enables (CE, CE2, CE2)	<sup>t</sup> CES	2.5		3		3		3		ns	8, 10
Hold Times											
Address	<sup>t</sup> AH	0.5		0.5		0.5		0.5		ns	8, 10
Address Status (ADSC, ADSP)	<sup>t</sup> ADSH	0.5		0.5		0.5		0.5		ns	8, 10
Address Advance ( ADV)	tAAH	0.5		0.5		0.5		0.5		ns	8, 10
Byte Write Enables (BW1, BW2, BW3, BW4)	tWH	0.5		0.5		0.5		0.5		ns	8, 10
Data-in	<sup>t</sup> D	0.5		0.5		0.5		0.5		ns	8, 10
Chip Enables (CE, CE2, CE2)	<sup>t</sup> CEH	0.5		0.5		0.5		0.5		ns	8, 10



# AC TEST CONDITIONS

Input pulse levels	Vss to 3.0V
Input rise and fall times	1.5ns
Input timing reference levels	1.5V
Output reference levels	1.5V
Output load	.See Figures 1 and 2





Fig. 1 OUTPUT LOAD EQUIVALENT



Fig. 2 OUTPUT LOAD EQUIVALENT

### NOTES

- 1. All voltages referenced to Vss (GND).
- 2. Overshoot:  $V_{IH} \le +6.0V$  for  $t \le {}^{t}KC / 2$ .
- Undershoot: $VIL \ge -2.0V$  for  $t \le tKC /2$ .Power-up: $VIH \le +6.0V$  and  $Vcc \le 3.1V$ <br/>for  $t \le 200msec$ .
- 3. Icc is given with no output current. Icc increases with greater output loading and faster cycle times.
- 4. This parameter is sampled.
- 5. Test conditions as specified with the output loading as shown in Fig. 1 unless otherwise noted.
- Output loading is specified with CL = 5pF as in Fig. 2. Transition is measured ±500mV from steady state voltage.
- 7. At any given temperature and voltage condition, <sup>t</sup>KQHZ is less than <sup>t</sup>KQLZ and <sup>t</sup>OEHZ is less than <sup>t</sup>OELZ.
- 8. A READ cycle is defined by byte write enables all HIGH or ADSP LOW for the required setup and hold times. A WRITE cycle is defined by at least one byte write enable LOW and ADSP HIGH for the required setup and hold times.

- 9. OE is a "don't care" when a byte write enable is sampled LOW.
- 10. This is a synchronous device. All addresses must meet the specified setup and hold times for all rising edges of CLK when either ADSP or ADSC is LOW and chip enabled. All other synchronous inputs must meet the setup and hold times with stable logic levels for all rising edges of clock (CLK) when chip is enabled. Chip enable must be valid at each rising edge of CLK (when either ADSP or ADSC is LOW) to remain enabled.
- 11. Micron does not warrant the functionality or reliability of any product in which the case temperature exceeds 110°C. Care should be taken to limit case temperature to acceptable levels.
- 12. "Device Deselected" means device is in POWER-DOWN mode as defined in the truth table. "Device Selected" means device is active (not in POWER-DOWN mode).
- 13. Typical values are measured at 3.3V, 25°C and 20ns cycle time.

### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

**READ TIMING** 



- NOTE: 1. Q(A2) refers to output from address A2. Q(A2+1) refers to output from the next internal burst address following A2.
  - 2. CE2 and CE2 have timing identical to CE. On this diagram, when CE is LOW, CE2 is LOW and CE2 is HIGH. When CE is HIGH, CE2 is HIGH and CE2 is LOW.

NEW 3.3 VOLT SYNCHRONOUS SRAM

MICRON

### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

### WRITE TIMING



**3.3 VOLT SYNCHRONOUS SRAM** 

NOTE: 1. Q(A2) refers to output from address A2. Q(A2+1) refers to output from the next internal burst address following A2.

- 2. CE2 and CE2 have timing identical to CE. On this diagram, when CE is LOW, CE2 is LOW and CE2 is HIGH. When CE is HIGH, CE2 is HIGH and CE2 is LOW.
- 3. OE must be HIGH before the input data setup and held HIGH throughout the the data hold time. This prevents input/output data contention for the time period prior to the byte write enable inputs being sampled.
- 4. ADV must be HIGH to permit a WRITE to the loaded address.

ICRON

# NCRONUCTOR, INC.

### MT58LC32K36C4 32K x 36 SYNCHRONOUS SRAM

**READ/WRITE TIMING** 



- NOTE: 1. Q(A3) refers to output from address A3. Q(A3+1) refers to output from the next internal burst address following A3.
  - 2. CE2 and CE2 have timing identical to CE. On this diagram, when CE is LOW, CE2 is LOW and CE2 is HIGH. When CE is HIGH, CE2 is HIGH and CE2 is LOW.

### APPLICATION INFORMATION

### **32-BIT-WIDE SYSTEMS**

The Micron 32K x 36 Synchronous SRAM may be used in a 32-bit-wide system without the use of any external components by connecting PDIS to Vcc. This disables the output buffer on the data parity input/output lines (DQP1, DQP2, DQP3 and DQP4).

### LOAD DERATING CURVES

The Micron  $32K \times 36$  Synchronous SRAM timing is dependent upon the capacitive loading on the outputs. The data sheet is written assuming a load of 30pF. Access time changes with load capacitance as follows:

 $\Delta^{t}KC = 0.016 \text{ ns/pF} \times \Delta C_{L} \text{ pF}.$ 

(Note: this is preliminary information subject to change.)

For example, if the SRAM loading is 22pF,  $\Delta C_L$  is -8pF (8pF less than rated load). The clock to valid output time of the SRAM is reduced by 0.016 x 8 = 0.128ns. If the device is a 7ns part, the worse case <sup>t</sup>KC becomes 6.87ns (approximately).

Consult the factory for copies of I/O current versus voltage curves and Quad Design models.

### DEPTH EXPANSION

The Micron 32K x 36 Synchronous SRAM incorporates two additional chip enables to facilitate simple depth expansion. This permits easy cache upgrades from 32K depth to 64K depth with no extra logic as shown in Figure 3.



Figure 3 DEPTH EXPANSION FROM 32K x 36 TO 64K x 36

٨



Figure 4 128K BYTE SECONDARY CACHE WITH PARITY AND BURST FOR 50 MHz 80486 USING ONE MT58LC32K36C4LG-10 SYNCHRONOUS SRAM



Figure 5 256K BYTE SECONDARY CACHE WITH PARITY AND BURST FOR 66 MHz PENTIUM MICROPROCESSOR USING TWO MT58LC32K36C4LG-7 SYNCHRONOUS SRAMs

MICRON

ADS CONTROL