


Ultra-Fast Recovery Diodes 30A FRED



Features

- Adopt FRED chip
- Low forward Voltage drop
- Fast reverse recovery time
- High frequency operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- 2500V Insulating capability

Typical Applications

- Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-220AC
Inner-Insulated Instructure
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MURI3060L
Device marking code			MURI3060L
Repetitive Peak Reverse Voltage	VRRM	V	600
Average Rectified Output Current @60Hz sine wave, R-load, T _c (FIG.1)	I _O	A	30
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T _a =25°C	I _{FSM}	A	250
Current Squared Time @1ms≤t≤8.3ms T _j =25°C	I ² t	A ² s	260
Single Pulse Avalanche Energy @ T _p =40uS, T _j =25°C, L=15mH	EAS	mJ	150
Storage Temperature	T _{stg}	°C	-55 ~ +175
Junction Temperature	T _j	°C	-55 ~ +175
Junction capacitance @4V,1MHz	C _j	pF	145



MURI3060L

■Electrical Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V_{FM}	V	$I_{FM}=30.0A$ @ $T_J=25^{\circ}C$	-	2.1	2.5
			$I_{FM}=30.0A$ @ $T_J=125^{\circ}C$		1.6	2.0
DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	μA	$V_{RM}=V_{RRM}$ $T_J=25^{\circ}C$	-	-	5.0
	I_{RRM2}		$V_{RM}=V_{RRM}$ $T_J=125^{\circ}C$	-	-	200.0
Reverse Recovery Time	T_{rr}	ns	$I_F=0.5A$ $I_{RM}=1A$ $I_{RR}=0.25A$ $T_J=25^{\circ}C$	-	27.0	50.0
			$T_J=25^{\circ}C$	-	58.0	-
			$T_J=125^{\circ}C$	-	92.0	-
Peak recovery current	I_{RRM}	A	$T_J=25^{\circ}C$	-	3.25	-
			$T_J=125^{\circ}C$	-	9.8	-
Reverse recovery charge	Q_{rr}	nC	$T_J=25^{\circ}C$	-	95.0	-
			$T_J=125^{\circ}C$	-	450.0	-

■Thermal Characteristics ($T_J=25^{\circ}C$ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	MURI3060L
Thermal Resistance	Between junction and case	$R_{\theta J-C}$	$^{\circ}C/W$	1.5
	Between junction and Air	$R_{\theta J-A}$	$^{\circ}C/W$	30.0

■Ordering Information (Example)

PREFERRED P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MURI3060L	Approximate 1.8	50	1000	5000	Tube

■ Characteristics(Typical)





FIG3: Forward Voltage




FIG.4: Instantaneous Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time





MURI3060L

■ Outline Dimensions



TO-220AC		
Dim	Min	Max
A	4.40	4.60
A1	1.25	1.35
A2	2.30	2.50
b	0.70	0.90
b1	1.25	1.42
c	0.45	0.55
D	15.50	16.00
D1	9.10	9.30
D2	12.90	13.30
D3	18.45	19.15
E	9.80	10.15
E1	7.40	7.80
e	TYP 5.08	
H	6.40	6.60
L	13.00	13.45
L1	/	3.40
L2	4.50	4.80
L3	1.10	1.50
ΦP	3.65	3.85
Q	2.65	2.85
$\theta 1$	2°	7°



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.