



Military-Fasteners.com

NAS1100-02-4 SCREW SPEC

Description:

Fastener Length: 1/4", Thread: 2-56, Thread Length: 1/4"

NAS1100-02-4 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-849-9585
NIIN:	008499585
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1100-02-4 Specifications

Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.063 Inches Maximum
Head Style:	Pan
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.086 Inches
Internal Drive Style:	Torque Set
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-15464 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams6300 Assn Std 6th Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
Screw Surface Treatment:	Cadmium And Chromate
Screw Material:	Steel Comp 4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Or Steel Comp 4140 Or Steel Comp 4037
Thread Length:	0.214 Inches Minimum And 0.250 Inches Maximum
Thread Class:	3a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	56
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS1100-02-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.