

NAS1102E06-4 MACHINE SCREW SPEC

Description:

Fastener Length: 1/4", Thread: 6-32, Thread Length: 3/16", NAS1102 series screw

NAS1102E06-4 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name: Screw, Machine

NSN: 5305-01-010-3679

NIIN: 010103679

FSC: Screws / 5305

Schedule B: 7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

Manufacturer Country: United States

NAS1102E06-4 Specifications

Countersink Angle:	100.0 Degrees Nominal
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Diameter:	0.231 Inches Minimum And 0.279 Inches Maximum
Head Style:	Flat Countersunk
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.138 Inches
Internal Drive Style:	Torque Set
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Material:	Iron Alloy 660
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Screw Surface Treatment:	Passivate
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.100 Inches Minimum And 0.193 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine-screws/NAS1102E06-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine-screws/NAS1102E06-4 and selecting the quantity you