



Military-Fasteners.com

NAS1351N6-20 SOCKET HEAD SCREW SPEC

Description:

Fastener Length: 1-1/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4"

NAS1351N6-20 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-01-378-9348
NIIN:	013789348
FSC:	Screws / 5305
Schedule B:	7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1351N6-20 Specifications

Fastener Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.375 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1531 Professional/industrial Association Standard
Width Across Flats:	0.3125 Inches Minimum And 0.3160 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Maximum
Thread Quantity Per Inch:	24
Thread Series Designator:	Unrf

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1351N6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.